

Carbide 鎢鋼材質

- C** 超微粒鎢鋼 0.8u m/m Co10%
Micro Grain 0.8u m/m Co10%
- 2D** 超微粒鎢鋼 0.6u m/m Co9%
Micro Grain 0.6u m/m Co9%
- 2** 超微粒鎢鋼 0.6u m/m Co10%
Micro Grain 0.6u m/m Co10%
- 5** 極細超微粒鎢鋼 0.3u m/m Co12%
Super Micro Grain 0.3u m/m Co12%
- 638** 極細超微粒鎢鋼 0.3u m/m Co8%
Super Micro Grain 0.3u m/m Co8%

Coating 塗層

- TXM** 適用於一般加工、難切削材，乾、溼兩用
Good at for difficult material. For dry & wet cutting
- R7** 適用於一般加工、溼式切削
Good at for wet cutting
- SF** 適用於一般加工、溼式切削
Good at for wet cutting
- OL** 適用於一般加工、難切削材，乾、溼兩用
Good at for difficult material. For dry & wet cutting
- TX** 適用於難切削材高速加工，乾、溼兩用
Good at difficult material. For dry & wet cutting
- GR** 適用於難切削材高速加工，乾、溼兩用
Good at difficult material. For dry & wet cutting
- NB** 適用於高速高硬度，乾式切削
Good at high speed cutting & high hard cutting. For dry cutting
- OS** 適用於高速高硬度，乾式切削
Good at high speed cutting & high hard cutting. For dry cutting

Helix Angle 螺旋角



螺旋角是 20° 35° 40° 45° 50° 55° 5° 20° 30° 35° 45°
Helix Angle is 20° 35° 40° 45° 50° 55° 5° 20° 30° 35° 45°

Shank 柄部精度



Work Material Hardness 可加工硬度



被切削工件硬度達 HRC35, HRC45, HRC52, HRC55, HRC62, HRC65
Work Material Hardness is up to HRC35, HRC45, HRC52, HRC55, HRC62, HRC65

高效率加工用銑刀

Milling Cutters for High Efficiency Machining

>>> 產品零件加工用刀

Milling cutters for product parts processing



N 有色金屬系列 THE COLOER SERIES

使用超微粒 0.8u m/m Co10% 鎢鋼製成，搭配特有的幾何角度特殊切刃設計，特別適用於有色金屬，鋁鎂合金以及銅合金之專用銑刀。

Made of Micro Grain 0.8u m/m Co10%.
Suitable: non-ferrous metal, aluminum magnesium alloy and copper alloy of end mill.



S 耐熱合金系列 THE HEAT RESISTANT ALLOY SERIES

使用超微粒 0.6u m/m Co9% 鎢鋼製成，搭配特有的幾何角度特殊切刃設計，特別適用於合金鋼、工具鋼、不鏽鋼、鈦合金、耐熱合金鋼、鎳基合金專用銑刀。

Made of Micro Grain 0.6u m/m Co 9%.
Suitable: non-ferrous metal, stainless steel, titanium alloy, heat-resisting alloy steel, and nickel alloy of end mill.

>>> 模具用刀

Milling cutter for mold



2 太陽戰士系列 THE SUN SERIES

使用超微粒 0.6u m/m Co10% 鎢鋼製成，搭配TXM 高潤滑性塗層，適用於溼式加工，碳素鋼、合金鋼 ~HRC52 之鋼材、不鏽鋼、鈦合金廣泛運用。


Made of Micro Grain 0.6u m/m Co10%. Coating TXM.
Suitable: wet cutting, stainless steel, titanium alloy, Carbon steel, alloy steel, HRC52.



5 黃金戰神系列 THE GOLD SERIES

使用極細超微粒 0.3u m/m Co12% 鎢鋼製成，搭配高耐熱及高潤滑性之TX級塗層，特別適用於溼式高速切削、合金鋼、模具鋼 ~HRC55之鋼材。

Made of Super Micro Grain 0.3u m/m Co12%. Coating TX.
Suitable: stainless steel, titanium alloy, steel for molding~HRC55.



























638 藍天門神系列 THE BLUE SKY SERIES

使用極細超微粒 0.3u m/m Co8% 鎢鋼製成，搭配高耐熱、高耐磨NB塗層，特別適用於合金鋼、模具鋼 HRC45~HRC68 之高速高硬度乾式加工。

Made of Super Micro Grain 0.3u m/m Co8%. Coating NB.
Suitable: titanium alloy, steel for molding HRC45~HRC68.












INDEX

系列	產品編號	切削工具	刃數	刀具名稱	頁數
高效能防震系列 Heavy-Duty & Anti-Vibration Operation Series	EAVD		4T	高效能防震鎢鋼立銑刀 Highly-Efficiency Anti-Vibration Operation Type	8
	EALD		4T	高效能長刃防震鎢鋼立銑刀 Highly-Efficiency Anti-Vibration Operation, Long Flute Length	9
	ERVD		4T	高效能防震鎢鋼立銑刀 Highly-Efficiency & Anti-Vibration Operation Type	10
	ERLD		4T	高效能長刃防震鎢鋼立銑刀 Highly-Efficiency Anti-Vibration Operation, Long Flute Length	12
	MLERVD		4T	高效能長柄防震鎢鋼立銑刀 Highly-Efficiency Anti-Vibration Operation Long Shank	13
	ERVB		4T	高效能防震鎢鋼球刀 Highly-Efficiency & Anti-Vibration Operation, Ball Nose	14
	ERVR		4T	高效能防震鎢鋼R角立銑刀 Highly-Efficiency & Anti-Vibration Operation Type Corner Radius	15
	SEW		4T	高效能防震波浪型刃銑刀 Highly-Efficiency & Anti-Vibration Operation, Wave Edge	16
	2PE3		3T	鎢鋼立銑刀 Flat End Mill	17
	MHR		4T	鎢鋼粗銑刀 Roughing End Mills	18
	MHH		4T	鎢鋼斷屑粗銑刀 Tungsten Carbide End Mills for Roughing with Chip Breaker	18
	CED		4T	高效率防震立銑刀 Highly Efficient Operation	20
	CEB		2T	高效率精密球刀 Highly Efficient Operation, Ball Nose	21
	CER		4T	高效率R角銑刀 Highly Efficient Operation, Corner Radius	22
	CHD		4T	金鑽高效能圓溝銑刀 For Highly Efficient Operation Milling Cutter	23
	CHD		4T	金鑽高效能點數銑刀 For Highly Efficient Operation (Decimal Diameter) Milling Cutter	24
	鋁銅合金專用系列 Aluminum & Copper Alloy Series	AED		3T	戰鬥機鋁合金專用鎢鋼立銑刀 For Aluminum Alloy
AEW			3T	波浪鋁用刀 Aluminum End Mills-Wave Helix Blades Type	27
AEC			3T	鋁合金專用鎢鋼立銑刀 For Aluminum Alloy	28
AELC			3T	鋁合金專用長刃鎢鋼立銑刀 Long Flute Length, For Aluminum Alloy	29
AE			3T	龍捲風鋁合金專用鎢鋼立銑刀 For Aluminum Alloy	30
SLAE			3T	龍捲風鋁合金專用長柄鎢鋼立銑刀 Long Shank, For Aluminum Alloy	31
AEL			3T	龍捲風鋁合金專用長刃鎢鋼立銑刀 Long Flute Length, For Aluminum Alloy	32
ACB			2T	鋁銅專用鎢鋼球刀 Ball Nose, Aluminum Alloy	34






















INDEX

系列	產品編號	切削工具	刃數	刀具名稱	頁數
鋁銅合金專用系列 Aluminum & Copper Alloy Series	SLACB		2T	鋁銅專用長柄鎢鋼球刀 Long Shank Ball Nose End Mill for Aluminum Alloy	35
	AR		3T	鋁銅專用鎢鋼R角銑刀 Corner Radius, For Aluminum Alloy	36
	SLAR		3T	鋁銅專用長柄鎢鋼R角銑刀 Long Shank Corner Radius, For Aluminum Alloy	38
一般鋼材通用加工 General Steel Material Processing	2MPE		4T	重切削鎢鋼立銑刀 Heavy Cutting Operation Type	41
	2MHD		4T	重切削鎢鋼立銑刀 Heavy Cutting Operation Type	41
	2SLE4		4T	長柄鎢鋼立銑刀 Long Shank, Regular Length	42
	2LET4		4T	長刃鎢鋼立銑刀 Long Flute Length End Mill	44
	2SE2		2T	鎢鋼立銑刀 Regular Length	45
	2SE2		2T	點數鎢鋼立銑刀 (Flat End Mill), 2 Flutes-Micro Decimal Diameter	46
	2MSB2		2T	鎢鋼球刀 Ball Nose	49
	2SLB2		2T	長柄鎢鋼球刀 Ball Nose, Long Shank	50
	2RTA		4T	鎢鋼R角銑刀 Corner Radius	52
	2SLR4		4T	長柄鎢鋼R角銑刀 Corner Radius, Long Shank	54
	5MSE		4T	重切削鎢鋼立銑刀 Heavy Cutting Operation Type	57
	5MHD		4T	重切削鎢鋼立銑刀 Heavy Cutting Operation Type	57
	5MSE2		2T	小徑鎢鋼立銑刀 (Flat End Mill), 2 Flutes Decimal Diameter	58
	5SLE4		4T	長柄鎢鋼立銑刀 Long Shank, Regular Length	60
5LET4		4T	長刃鎢鋼立銑刀 Long Flute Length End Mill	62	
5SB2		2T	鎢鋼球刀 Ball Nose	64	
5MSB		2T	小徑鎢鋼球刀 (Ball Nose), 2 Flutes-Decimal Diameter	65	
5SLB2		2T	長柄鎢鋼球刀 Ball Nose, Long Shank	66	
5RTA		4T	鎢鋼R角銑刀 Corner Radius	68	
5SLR4		4T	長柄鎢鋼R角銑刀 Corner Radius, Long Shank	70	
模具加工專用 Mold Processing					

INDEX

系列	產品編號	切削工具	刃數	刀具名稱	頁數
模具加工專用 Mold Processing	5LNT		2T	深溝加工用鎢鋼立銑刀 For Deep Processing, Long Neck	72
	5LNB		2T	深溝加工用鎢鋼球刀 Ball Nose For Deep Processing, Long Neck	73
	5LNR		4T	深溝加工用鎢鋼R角銑刀 Corner Radius For Deep Processing, Long Neck	74
熱處理專用 Heat Treatment Dry Cutting Processing	638MSE4		4T	高速·高硬度專用鎢鋼立銑刀 Regular Length, For High Hardness Material	76
	638SE4		4T	高速·高硬度專用鎢鋼立銑刀 Regular Length, For High Hardness Material	76
	638MSE2		2T	高速·高硬度專用小徑鎢鋼立銑刀 (Flat End Mill, For High Hardness Material), 2 Flutes-Micro Decimal Diameter	77
	638MSE2		2T	高速·高硬度專用鎢鋼立銑刀 Regular Length, For High Hardness Material	78
	638SE2		2T	高速·高硬度專用鎢鋼立銑刀 Regular Length, For High Hardness Material	78
	638MSP6		6T	高速·高硬度專用鎢鋼立銑刀 High Hardness Material	79
	638MLP6		6T	高速·高硬度專用鎢鋼長刃立銑刀 (High Hardness Material), Long Flute Length	79
	638SB2		2T	高速·高硬度專用鎢鋼球刀 Ball Nose	80
	638MSB2		2T	高速·高硬度專用小徑鎢鋼球刀 (Ball Nose, For High Hardness Material), 2 Flutes-Micro Diameter	81
	638SLB2		2T	高速·高硬度專用長柄鎢鋼球刀 Ball Nose, Long Shank	82
	638RTA		4T	高速·高硬度專用鎢鋼R角銑刀 Conner Radius	84
	638SLR		4T	高速·高硬度專用長柄鎢鋼R角銑刀 Corner Radius, Long Shank	86
車銑複合機專用 Car Milling composite Machine is Dedicated	TMAE		3T	車銑複合機專用鋁用立銑刀 Compound Lathe End Mill for Aluminum Alloy	88
	TMTAE		3T	車銑複合機專用小柄鋁用銑刀 Compound Lathe End Mill for Aluminum Alloy-Small handle	88
	TMSB		2T	車銑複合機專用鎢鋼球型銑刀 Compound Lathe Ball Nose End Mill	89
	TMTSB		2T	車銑複合機專用小柄球銑刀 Compound Lathe Ball Nose End Mill-Small handle	89
	TMPE		3T	車銑複合機專用三刃立銑刀 For Compound Lathe End Mill	90
	TMTPE		3T	車銑複合機專用小柄立銑刀 For Compound Lathe End Mill-Small handle mill	90
螺紋加工 Thread Machining	VUA		3T	鎢鋼螺旋銑牙刀-ISO規格(三峰) (Thread Milling Tools-Helical Flutes-ISO Metric)-Three teeth	91
	VUB		3T/4T	鎢鋼螺旋銑牙刀-ISO規格(全齒) Thread Milling Tools-Helical Flutes-ISO Metric)-Full teeth	91

INDEX

系列	產品編號	切削工具	刃數	刀具名稱	頁數
螺紋加工 Thread Machining	VUA		3T	鎢鋼銑牙刀 - UN 內牙/外牙(三峰) Tungsten Carbide Tread Milling Tools-American-UN (Internal/External)	92
	VUB		3T/4T	鎢鋼銑牙刀 - UN (內牙) Tungsten Carbide Tread Milling Tools-American-UN (Internal)	93
	VUC		3T/4T	鎢鋼銑牙刀 - NPT/NPTF (內牙/外牙) Tungsten Carbide Thread Milling Tools-NPT/NPTF (Internal/External)	94
	VUC		3T	鎢鋼螺旋斜度銑牙刀 Taper Thread Milling Cutter	95
	22R2WC		2T/4T	鎢鋼倒角刀 Tungsten Carbide Chamfering End Mill	96
22R2UD		4T	鎢鋼上下倒角刀 Tungsten Carbide Back and Front Chamfering Cutter	97	
V22SD		2T	鎢鋼鑽銑刀 Tungsten Carbide V-Pointed End Mill (Drilling and Milling)	98	
SDNCWC		2T	鎢鋼定位鑽 Tungsten Carbide Spot Drills	99	
5TTA		1T	鎢鋼雕刻銑刀 Tungsten Carbide Engraving End Mill	99	
RC		4T	鎢鋼外R角銑刀 Tungsten Carbide Outer Radius End Mill	100	
5MTB		2T	鎢鋼棒棒糖球刀-280° 280° Lollipop Tungsten Carbide Ball Nose milling cutter	100	
638XXE		X	碳纖維專用鎢鋼銑刀 - XX刀 For Composite Materials, Carbon Fiber tungsten Carbide milling cutter	101	
638YYE		4T	碳纖維專用鎢鋼銑刀 - YY刀 YYE For Composite Materials Tungsten Carbide Milling Cutter	101	
2TE		4T/6T	鎢鋼T型銑刀 Tungsten Carbide, T-Shape End Mill	102	
CBTE			焊刃鎢鋼T型槽銑刀(直刃) Brazed Carbide T-Slot Cutter (Straight Flute)	104	
2RJ		4T	鎢鋼鳩尾刀 - 45°/60° Carbide Dove-Tail End Mills	105	
5TTA		2T/4T	鎢鋼斜度銑刀 Tungsten Carbide Taper End Mills	106	
鎢鋼刀頭 Tungsten Carbide End mill Head	HESD		4T	鎖牙鎢鋼平刀頭 Three Energy-Efficient Science Endmill head	108
	HSB		2T	鎖牙鎢鋼球刀頭 Three Energy-Efficient Science Endmill heads	108
	HESR		4T	鎖牙鎢鋼R角刀頭 Three Energy-Efficient Science Endmill heads	108
	HAE		3T	鎖牙鋁合金平刀頭 Three Energy-Efficient Science Endmill heads	109
	HACB		2T	鎖牙鋁合金球刀頭 Three Energy-Efficient Science Endmill heads	109
	HAR		3T	鎖牙鋁合金R角刀頭 Three Energy-Efficient Science Endmill heads	109

INDEX

系列	產品編號	切削工具	刃數	刀具名稱	頁數
錫鋼刀柄 Tungsten Carbide Holder	GL			錫鋼抗震刀柄 Tungsten Carbide Anti-Vibration Tools Holder	110
	HDC/HUC			錫鋼後拉刀桿 Tungsten Carbide Tools Holder-HDC/HUC Collect Chuck	112
	HDC/HUC			後拉筒夾 Collet Chuck	113
	GLCK			錫鋼抗震搪刀柄 Tungsten Carbide Anti-Vibration Boring System Tool Holder	114
小徑車刀 Micro Turning Cutter	MPR			微型車刀 Micro Turning Cutter	116
	MGR			微型車刀(切槽) Micro Turning Cutter (Recessed)	116
	MIR			微型車刀(60°螺紋加工) Micro Turning Cutter (60° Thread Processing)	117
錫鋼鑽頭、鉸刀 Tungsten carbide drill & Tungsten carbide Reamer	HQDEXZ		2T	錫鋼平底鑽頭 Tungsten Carbide Flat-Bottom Drill	118
	SDWC R			泛用型加工外冷錫鋼鑽頭3D.5D.7D High Performance Tungsten Carbide Drill Bit-3D.5D.7D	120
	SDWC O			水孔內冷錫鋼鑽頭3D.5D.8D Coolant Hole High Performance Tungsten Carbide Drill Bit-3D.5D.8D	126
				錫鋼直柄短刃鑽頭 Solid Carbide Straight Shank Drills	132
				錫鋼直柄長刃鑽頭 Solid Carbide Long Flute Straight Shank Drills	133
				錫鋼直柄機械鉸刀 Solid Carbide Straight Shank Machine Reamers	134
				錫鋼機械鉸刀銑刀柄 Solid Carbide Machine Reamers	136
手工工具系列 Hand Tool Series				HSS高速鋼星型六角起子頭 HSS High Speed Steel TORX Professional Bit	137
				HSS高速鋼十字起子頭 HSS High Speed Steel Phillips Professional Bit	137
				HSS高速鋼六角起子頭 HSS High Speed Steel HEX Professional Bit	138
				HSS高速鋼捨棄式刀具專用星型起子 HSS High Speed Steel TORX Screwdriver	139
				專利走心式車床專用螺帽棘輪扳手 Ratchet Wrench for Swiss Type CNC Lathe	140
				專利走心式車床專用星型棘輪扳手 TORX Bit of Ratchet Wrench for Swiss Type CNC Lathe	140
				錫鋼倒角起子頭 Tungsten Carbide Steel Chamfering/Deburring Tool	141

ERVD 高效能防震


ERVD High-efficiency & Anti-Vibration

錫鋼立銑刀

tungsten Carbide end mills

$\alpha \neq \beta$

A \neq B



MIT 製造

- ▶ 極佳的加工垂直度
Process with Excellent Perpendicularity.
- ▶ 不等分及不等螺旋的設計能最大限度地減少
高效穩定銑削時的振動
Unequal end fact & variable spiral designed will
minimizes vibration on stable milling under highly efficient.
- ▶ 工作效率提升30%~100%
Improves the working efficiency up to 30%~100%.
- ▶ 刀具壽命提升50%
Tool service life will up to 50%.



應用材質：難切削材、不鏽鋼、鈦合金、合金鋼、一般鋼材
預硬鋼材、銅合金、鋁合金、耐熱合金鋼


產品編號：2D ERVD 1004GRJ

影片加工材料：SUS304



2 EAVD 高效能防震鎢鋼立銑刀

EAVD (Highly-Efficiency Anti-Vibration Operation Type), 4 Flutes



單位：mm (Unit : mm)

產品編號 Model No.	刃徑 D Diameter	刃長 l Flute Length	柄徑 d Shank Diameter	全長 L Overall Length	價格 Price	備註
2 EAVD 0204TX	2	6	4	50		
2 EAVD 0254TX	2.5	8	4	50		
2 EAVD 0304TX	3	8	4	50		
2 EAVD 0304TXD6	3	8	6	50		
2 EAVD 0404TX	4	11	4	50		
2 EAVD 0404TXD6	4	11	6	50		
2 EAVD 0504TX	5	13	6	50		
2 EAVD 0604TX	6	18	6	50		
2 EAVD 0704TX	7	21	8	60		
2 EAVD 0804TX	8	20	8	60		
2 EAVD 0804TXS24	8	24	8	60		
2 EAVD 0904TX	9	25	10	75		
2 EAVD 1004TX	10	30	10	75		
2 EAVD 1104TX	11	30	12	75		
2 EAVD 1204TX	12	30	12	75		
2 EAVD 1204TXS36	12	36	12	75		
2 EAVD 1604TX	16	50	16	100		
2 EAVD 2004TX	20	50	20	100		


備註：其他規格，請來電洽詢。 For other specifications, please call to inquire

適用材質 Work Material : ★ 最適合 Excellent ● 適合 Better ▲ 佳 Good

碳素鋼 Carbon steels	合金鋼 Alloy steels	預硬鋼材	高硬度鋼					不銹鋼 Stainless steels	鈦合金 Titanium alloys	鎳基合金 Nickel Based alloys	銅合金 Copper alloys	鋁合金 Aluminum alloys
		Pre-hardened steels	High-hardened									
		~HRC45	~HRC50	~HRC55	~HRC60	~HRC65						
★	★	●	▲				●			●	▲	

2 EALD 高效能長刃防震鎢鋼立銑刀

EALD (Highly-Efficiency Anti-Vibration Operation, Long Flute Length), 4 Flutes



單位：mm (Unit : mm)

產品編號 Model No.	刃徑 D Diameter	刃長 l Flute Length	柄徑 d Shank Diameter	全長 L Overall Length	價格 Price	備註
2 EALD 0304TXD6	3	15	6	50		
2 EALD 0404TXD6	4	20	6	75		
2 EALD 0504TX	5	25	6	75		
2 EALD 0604TX	6	30	6	75		
2 EALD 0704TX	7	35	8	100		
2 EALD 0804TX	8	40	8	100		
2 EALD 0904TX	9	45	10	100		
2 EALD 1004TX	10	50	10	100		
2 EALD 1204TX	12	50	12	100		
2 EALD 1604TX	16	80	16	150		
2 EALD 2004TX	20	80	20	150		

備註：其他規格，請來電洽詢。 For other specifications, please call to inquire

適用材質 Work Material : ★ 最適合 Excellent ● 適合 Better ▲ 佳 Good


碳素鋼 Carbon steels	合金鋼 Alloy steels	預硬鋼材	高硬度鋼					不銹鋼 Stainless steels	鈦合金 Titanium alloys	鎳基合金 Nickel Based alloys	銅合金 Copper alloys	鋁合金 Aluminum alloys
		Pre-hardened steels	High-hardened									
		~HRC45	~HRC50	~HRC55	~HRC60	~HRC65						
★	★	●	▲				●			●	▲	

高效能防震系列

高效能防震系列

2D ERVD 高效能防震鎢鋼立銑刀

ERVD (Highly-Efficiency & Anti-Vibration Operation Type), 4 Flutes



單位：mm (Unit : mm)

產品編號 Model No.	刃徑 D Diameter	刃長 I Flute Length	倒角 C Chamfer	柄徑 d Shank Diameter	全長 L Overall Length	價格 Price	備註
2D ERVD 0104GR	1	2.5		4	50		
2D ERVD 0104GRD6	1	2.5		6	50		
2D ERVD 0104GRC0.1	1	2.5	0.1	6	50		
2D ERVD 0154GR	1.5	4		4	50		
2D ERVD 0154GRD6	1.5	4		6	50		
2D ERVD 0154GRC0.1	1.5	4	0.1	6	50		
2D ERVD 0204GR	2	6		4	50		
2D ERVD 0204GRD6	2	6		6	50		
2D ERVD 0204GRC0.1	2	6	0.1	6	50		
2D ERVD 0254GR	2.5	7		4	50		
2D ERVD 0254GRD6	2.5	7		6	50		
2D ERVD 0254GRC0.1	2.5	7	0.1	6	50		
2D ERVD 0304GR	3	8		4	50		
2D ERVD 0304GRD6	3	8		6	50		
2D ERVD 0304GRC0.1	3	8	0.1	6	50		
2D ERVD 0404GR	4	11		4	50		
2D ERVD 0404GRD6	4	11		6	50		
2D ERVD 0404GRC0.1	4	11	0.1	6	50		
2D ERVD 0504GR	5	13		6	50		
2D ERVD 0504GRC0.1	5	13	0.1	6	50		
2D ERVD 0604GR	6	15	0.2	6	50		
2D ERVD 0604GRS18	6	18	0.2	6	50		
2D ERVD 0704GR	7	18	0.2	8	60		
2D ERVD 0804GR	8	20	0.2	8	60		
2D ERVD 0804GRS24	8	24	0.2	8	60		
2D ERVD 0904GR	9	25	0.2	10	75		
2D ERVD 1004GR	10	30	0.2	10	75		
2D ERVD 1104GR	11	30	0.2	12	75		
2D ERVD 1204GR	12	30	0.2	12	75		
2D ERVD 1204GRS36	12	36	0.2	12	75		

單位：mm (Unit : mm)

產品編號 Model No.	刃徑 D Diameter	刃長 I Flute Length	倒角 C Chamfer	柄徑 d Shank Diameter	全長 L Overall Length	價格 Price	備註
2D ERVD 1404GR	14	35	0.2	16	100		
2D ERVD 1604GRS45	16	45	0.2	16	100		
2D ERVD 1604GR	16	50	0.2	16	100		
2D ERVD 2004GR	20	50	0.2	20	100		

備註：其他規格，請來電洽詢。 For other specifications, please call to inquire

適用材質 Work Material :

★最適合 Excellent ●適合 Better ▲佳 Good

碳素鋼 Carbon steels	合金鋼 Alloy steels	預硬鋼材	高硬度鋼				不銹鋼 Stainless steels	鈦合金 Titanium alloys	鎳基合金 Nickel Based alloys	銅合金 Copper alloys	鋁合金 Aluminum alloys
		Pre-hardened steels	High-hardened								
		~HRC45	~HRC50	~HRC55	~HRC60	~HRC65					
★	★	●	▲				★	★	●	●	▲


高效能防震系列

高效能防震系列

2D HIDO ERLD 高效能長刃防震鎢鋼立銑刀



ERLD (Highly-Efficiency Anti-Vibration Operation, Long Flute Length), 4 Flutes



單位：mm (Unit : mm)

產品編號 Model No.	刃徑 D Diameter	刃長 l Flute Length	倒角 C Chamfer	柄徑 d Shank Diameter	全長 L Overall Length	價格 Price	備註
2D ERLD 0104GR	1	5		4	50		
2D ERLD 0104GRD6	1	5		6	50		
2D ERLD 0154GR	1.5	8		4	50		
2D ERLD 0154GRD6	1.5	8		6	50		
2D ERLD 0204GRD6	2	10		6	50		
2D ERLD 0254GRD6	2.5	13		6	50		
2D ERLD 0304GRD6	3	15		6	50		
2D ERLD 0404GRD6	4	20		6	75		
2D ERLD 0504GR	5	25		6	75		
2D ERLD 0604GR	6	30	0.2	6	75		
2D ERLD 0704GR	7	35	0.2	8	100		
2D ERLD 0804GR	8	40	0.2	8	100		
2D ERLD 0904GR	9	45	0.2	10	100		
2D ERLD 1004GR	10	50	0.2	10	100		
2D ERLD 1204GR	12	50	0.2	12	100		
2D ERLD 1604GR	16	80	0.2	16	150		
2D ERLD 2004GR	20	80	0.2	20	150		

備註：其他規格，請來電洽詢。 For other specifications, please call to inquire

適用材質 Work Material :


★最適合 Excellent ●適合 Better ▲佳 Good

碳素鋼 Carbon steels	合金鋼 Alloy steels	預硬鋼材 Pre-hardened steels	高硬度鋼 High-hardened				不銹鋼 Stainless steels	鈦合金 Titanium alloys	鎳基合金 Nickel Based alloys	銅合金 Copper alloys	鋁合金 Aluminum alloys
		~HRC45	~HRC50	~HRC55	~HRC60	~HRC65					
★	★	●	▲				★	★	●	●	▲

2D HIDO MLERVD 高效能長柄防震鎢鋼立銑刀



MLERVD (Highly-Efficiency Anti-Vibration Operation Long Shank), 4 Flutes



單位：mm (Unit : mm)

產品編號 Model No.	刃徑 D Diameter	刃長 l Flute Length	倒角 C Chamfer	柄徑 d Shank Diameter	全長 L Overall Length	價格 Price	備註
2D SLERVD 0304GRD6	3	8		6	75		
2D MLERVD 0304GRD6	3	8		6	100		
2D SLERVD 0404GRD6	4	11		6	75		
2D MLERVD 0404GRD6	4	11		6	100		
2D SLERVD 0504GR	5	13		6	75		
2D MLERVD 0504GR	5	13		6	100		
2D SLERVD 0604GR	6	15	0.2	6	75		
2D MLERVD 0604GR	6	15	0.2	6	100		
2D MLERVD 0704GR	7	18	0.2	8	100		
2D SLERVD 0804GR	8	20	0.2	8	75		
2D MLERVD 0804GR	8	20	0.2	8	100		
2D MLERVD 0904GR	9	23	0.2	10	100		
2D MLERVD 1004GR	10	30	0.2	10	100		
2D MLERVD 1204GR	12	30	0.2	12	100		
2D MLERVD 1604GR	16	50	0.2	16	150		

備註：其他規格，請來電洽詢。 For other specifications, please call to inquire

適用材質 Work Material :

★最適合 Excellent ●適合 Better ▲佳 Good


碳素鋼 Carbon steels	合金鋼 Alloy steels	預硬鋼材 Pre-hardened steels	高硬度鋼 High-hardened				不銹鋼 Stainless steels	鈦合金 Titanium alloys	鎳基合金 Nickel Based alloys	銅合金 Copper alloys	鋁合金 Aluminum alloys
		~HRC45	~HRC50	~HRC55	~HRC60	~HRC65					
★	★	●	▲				★	★	●	●	▲

高效能防震系列

高效能防震系列

2D ERVB 高效能防震鎢鋼球刀

ERVB (Highly-Efficiency & Anti-Vibration Operation, Ball Nose), 4 Flutes



單位: mm (Unit: mm)

產品編號 Model No.	球頭半徑 R Radius	刃徑 D Diameter	刃長 l Flute Length	柄徑 d Shank Diameter	全長 L Overall Length	價格 Price	備註
2D ERVB 0102GR	0.5R	1	2	4	50		
2D ERVB 0102GRD6	0.5R	1	2	6	50		
2D ERVB 0152GR	0.75R	1.5	3	4	50		
2D ERVB 0152GRD6	0.75R	1.5	3	6	50		
2D ERVB 0202GR	1R	2	4	4	50		
2D ERVB 0202GRD6	1R	2	4	6	50		
2D ERVB 0302GRD3	1.5R	3	6	3	50		
2D ERVB 0302GR	1.5R	3	6	4	50		
2D ERVB 0302GRD6	1.5R	3	6	6	50		
2D ERVB 0402GR	2R	4	8	4	50		
2D ERVB 0402GRD6	2R	4	8	6	50		
2D ERVB 0502GR	2.5R	5	10	6	50		
2D ERVB 0602GR	3R	6	12	6	50		
2D ERVB 0802GR	4R	8	16	8	60		
2D ERVB 1002GR	5R	10	20	10	75		
2D ERVB 1202GR	6R	12	24	12	75		

備註: 其他規格, 請來電洽詢。 For other specifications, please call to inquire


適用材質 Work Material:

★最適合 Excellent ●適合 Better ▲佳 Good

碳素鋼 Carbon steels	合金鋼 Alloy steels	預硬鋼材	高硬度鋼					不銹鋼 Stainless steels	鈦合金 Titanium alloys	鎳基合金 Nickel Based alloys	銅合金 Copper alloys	鋁合金 Aluminum alloys
		Pre-hardened steels	High-hardened									
		~HRC45	~HRC50	~HRC55	~HRC60	~HRC65						
★	★	●	▲				★	★	●	●	▲	

2D ERVR 高效能防震鎢鋼R角立銑刀

ERVR (Highly-Efficiency & Anti-Vibration Operation Type Corner Radius), 4 Flutes



單位: mm (Unit: mm)

產品編號 Model No.	刃徑 × R角 D × R Diameter × Corner Radius	刃長 l Flute Length	柄徑 d Shank Diameter	全長 L Overall Length	價格 Price	備註
2D ERVR 020024GR	2 × 0.2R	6	6	50		
2D ERVR 020054GR	2 × 0.5R	6	6	50		
2D ERVR 025024GR	2.5 × 0.2R	7	6	50		
2D ERVR 025054GR	2.5 × 0.5R	7	6	50		
2D ERVR 030014GR	3 × 0.1R	8	6	50		
2D ERVR 030024GR	3 × 0.2R	8	6	50		
2D ERVR 030054GR	3 × 0.5R	8	6	50		
2D ERVR 030104GR	3 × 1R	8	6	50		
2D ERVR 040024GR	4 × 0.2R	11	6	50		
2D ERVR 040054GR	4 × 0.5R	11	6	50		
2D ERVR 040104GR	4 × 1R	11	6	50		
2D ERVR 050024GR	5 × 0.2R	13	6	50		
2D ERVR 050054GR	5 × 0.5R	13	6	50		
2D ERVR 050104GR	5 × 1R	13	6	50		
2D ERVR 060024GR	6 × 0.2R	15	6	50		
2D ERVR 060054GR	6 × 0.5R	15	6	50		
2D ERVR 060104GR	6 × 1R	15	6	50		
2D ERVR 080054GR	8 × 0.5R	20	8	60		
2D ERVR 080104GR	8 × 1R	20	8	60		
2D ERVR 100054GR	10 × 0.5R	30	10	75		
2D ERVR 100104GR	10 × 1R	30	10	75		
2D ERVR 100154GR	10 × 1.5R	30	10	75		
2D ERVR 100204GR	10 × 2R	30	10	75		
2D ERVR 100304GR	10 × 3R	30	10	75		
2D ERVR 120054GR	12 × 0.5R	30	12	75		
2D ERVR 120104GR	12 × 1R	30	12	75		
2D ERVR 120204GR	12 × 2R	30	12	75		
2D ERVR 160054GR	16 × 0.5R	50	16	100		
2D ERVR 160104GR	16 × 1R	50	16	100		
2D ERVR 160204GR	16 × 2R	50	16	100		
2D ERVR 160304GR	16 × 3R	50	16	100		
2D ERVR 200104GR	20 × 1R	50	20	100		
2D ERVR 200204GR	20 × 2R	50	20	100		
2D ERVR 200304GR	20 × 3R	50	20	100		

備註: 其他規格, 請來電洽詢。 For other specifications, please call to inquire

適用材質 Work Material:

★最適合 Excellent ●適合 Better ▲佳 Good


碳素鋼 Carbon steels	合金鋼 Alloy steels	預硬鋼材	高硬度鋼					不銹鋼 Stainless steels	鈦合金 Titanium alloys	鎳基合金 Nickel Based alloys	銅合金 Copper alloys	鋁合金 Aluminum alloys
		Pre-hardened steels	High-hardened									
		~HRC45	~HRC50	~HRC55	~HRC60	~HRC65						
★	★	●	▲				★	★	●	●	▲	

高效能防震系列

高效能防震系列

2D SEW 高效能防震波浪型刀刃銑刀

SEW (Highly-Efficiency & Anti-Vibration Operation, Wave Edge), 4 Flutes



單位：mm (Unit : mm)

產品編號 Model No.	刃徑 D Diameter	刃長 l Flute Length	柄徑 d Shank Diameter	全長 L Overall Length	價格 Price	備註
2D SEW 0204GR	2	6	4	50		
2D SEW 0254GR	2.5	7	4	50		
2D SEW 0304GR	3	8	4	50		
2D SEW 0404GR	4	10	4	50		
2D SEW 0504GR	5	13	6	50		
2D SEW 0604GR	6	15	6	50		
2D SEW 0704GR	7	18	8	60		
2D SEW 0804GR	8	20	8	60		
2D SEW 0904GR	9	25	10	75		
2D SEW 1004GR	10	25	10	75		
2D SEW 1104GR	11	30	12	75		
2D SEW 1204GR	12	30	12	75		
2D SEW 1604GR	16	50	16	100		
2D SEW 2004GR	20	50	20	100		

備註：其他規格，請來電洽詢。 For other specifications, please call to inquire


適用材質 Work Material :

★ 最適合 Excellent ● 適合 Better ▲ 佳 Good

碳素鋼 Carbon steels	合金鋼 Alloy steels	預硬鋼材 Pre-hardened steels					高硬度鋼 High-hardened					不銹鋼 Stainless steels	鈦合金 Titanium alloys	鎳基合金 Nickel Based alloys	銅合金 Copper alloys	鋁合金 Aluminum alloys
		~HRC45	~HRC50	~HRC55	~HRC60	~HRC65										
★	★	●					★	★	●	●	●					

2 PE3 三刃鎢鋼立銑刀

PE3 (Flat End Mill), 3 Flutes



單位：mm (Unit : mm)

產品編號 Model No.	刃徑 D Diameter	刃長 l Flute Length	柄徑 d Shank Diameter	全長 L Overall Length	價格 Price	備註
2 PE 0103SF	1	3	6	50		
2 MPE 0153SF	1.5	4	4	50		
2 PE 0153SF	1.5	4	6	50		
2 PE 0203SF	2	6	6	50		
2 PE 0253SF	2.5	7	6	50		
2 MPE 0303SF	3	9	4	50		
2 PE 0303SF	3	9	6	50		
2 PE 0353SF	3.5	10	6	50		
2 PE 0403SF	4	12	6	50		
2 PE 0453SF	4.5	13	6	50		
2 PE 0503SF	5	13	6	50		
2 PE 0553SF	5.5	15	6	50		
2 PE 0603SF	6	16	6	50		
2 PE 0703SF	7	18	8	60		
2 PE 0753SF	7.5	20	8	60		
2 PE 0803SF	8	20	8	60		
2 PE 0903SF	9	25	10	75		
2 PE 1003SF	10	25	10	75		
2 PE 1103SF	11	30	12	75		
2 PE 1203SF	12	30	12	75		
2 PE 1403SF	14	40	16	100		
2 PE 1603SF	16	45	16	100		

備註：其他規格，請來電洽詢。 For other specifications, please call to inquire


適用材質 Work Material :

★ 最適合 Excellent ● 適合 Better ▲ 佳 Good

碳素鋼 Carbon steels	合金鋼 Alloy steels	預硬鋼材 Pre-hardened steels					高硬度鋼 High-hardened					不銹鋼 Stainless steels	鈦合金 Titanium alloys	鎳基合金 Nickel Based alloys	銅合金 Copper alloys	鋁合金 Aluminum alloys
		~HRC45	~HRC50	~HRC55	~HRC60	~HRC65										
★	★	●					★	●				★	●		●	●

2 MHR 鎢鋼粗銑刀

MHR (Roughing End Mills),4 Flutes




單位：mm (Unit : mm)

產品編號 Model No.	刃徑 D Diameter	刃長 l Flute Length	柄徑 d Shank Diameter	全長 L Overall Length	價格 Price	備註
2 MHR 0604TXM	6	15	6	50		
2 MHR 0804TXM	8	20	8	60		
2 MHR 1004TXM	10	25	10	75		
2 MHR 1204TXM	12	30	12	75		
2 MHR 1404TXM	14	40	16	100		
2 MHR 1604TXM	16	50	16	100		
2 MHR 2004TXM	20	50	20	100		

備註：其他規格，請來電洽詢。 For other specifications, please call to inquire

2 MHH 鎢鋼斷屑粗銑刀

MHH (Tungsten Carbide End Mills for Roughing with Chip Breaker),4 Flutes



單位：mm (Unit : mm)

產品編號 Model No.	刃徑 D Diameter	刃長 l Flute Length	柄徑 d Shank Diameter	全長 L Overall Length	價格 Price	備註
2 MHH 0604TXM	6	15	6	50		
2 MHH 0804TXM	8	20	8	60		
2 MHH 1004TXM	10	25	10	75		
2 MHH 1204TXM	12	30	12	75		
2 MHH 1404TXM	14	40	16	100		
2 MHH 1604TXM	16	50	16	100		
2 MHH 2004TXM	20	50	20	100		

備註：其他規格，請來電洽詢。 For other specifications, please call to inquire

適用材質 Work Material :

★ 最適合 Excellent ● 適合 Better ▲ 佳 Good

碳素鋼 Carbon steels	合金鋼 Alloy steels	預硬鋼材 Pre-hardened steels					高硬度鋼 High-hardened					不銹鋼 Stainless steels	鈦合金 Titanium alloys	鎳基合金 Nickel Based alloys	銅合金 Copper alloys	鋁合金 Aluminum alloys
		~HRC45	~HRC50	~HRC55	~HRC60	~HRC65										
★	★	●	●					●	●				●	●		

成型刀訂製
Customized Carbide Forming Cutter




1. 提供圖面、樣品或手稿皆可訂製專屬刀具。
We can customize exclusive Cutter based on provided drawings, samples, or sketches.
2. 依客戶加工材質，客製最適合的塗層。
We'll apply the most suitable coating based on the material you provide for processing.

高效能防震系列

CED 高效率防震立銑刀

CED (Highly Efficient Operation), 4 Flutes



單位：mm (Unit : mm)

產品編號 Model No.	刃徑 D Diameter	刃長 l Flute Length	柄徑 d Shank Diameter	全長 L Overall Length	價格 Price	備註
CED 0104GR	1	3	4	50		
CED 0154GR	1.5	4.5	4	50		
CED 0204GR	2	6	4	50		
CED 0254GR	2.5	8	4	50		
CED 0304GR	3	9	4	50		
CED 0304GRD6	3	9	6	50		
CED 0354GRD6	3.5	11	6	50		
CED 0404GR	4	12	4	50		
CED 0404GRD6	4	12	6	50		
CED 0454GR	4.5	13	6	50		
CED 0504GR	5	15	6	50		
CED 0554GR	5.5	16	6	50		
CED 0604GR	6	18	6	50		
CED 0804GR	8	24	8	60		
CED 1004GR	10	30	10	75		
CED 1204GR	12	36	12	75		
CED 1604GR	16	50	16	100		
CED 2004GR	20	50	20	100		

備註：其他規格，請來電洽詢。 For other specifications, please call to inquire

適用材質 Work Material :

★最適合 Excellent ●適合 Better ▲佳 Good

碳素鋼 Carbon steels	合金鋼 Alloy steels	預硬鋼材 Pre-hardened steels					高硬度鋼 High-hardened					不銹鋼 Stainless steels	鈦合金 Titanium alloys	鎳基合金 Nickel Based alloys	銅合金 Copper alloys	鋁合金 Aluminum alloys
		~HRC45	~HRC50	~HRC55	~HRC60	~HRC65										
★	★	●					★	●			●	●				

CEB 高效率精密球刀

CEB (Highly Efficient Operation, Ball Nose), 2 Flutes



單位：mm (Unit : mm)

產品編號 Model No.	球頭半徑 R Radius	刃徑 D Diameter	刃長 l Flute Length	柄徑 d Shank Diameter	全長 L Overall Length	價格 Price	備註
CEB 0102GR	0.5R	1	2	4	50		
CEB 0102GRD6	0.5R	1	2	6	50		
CEB 0152GR	0.75R	1.5	3	4	50		
CEB 0152GRD6	0.75R	1.5	3	6	50		
CEB 0202GR	1R	2	4	4	50		
CEB 0202GRD6	1R	2	4	6	50		
CEB 0302GRD3	1.5R	3	6	3	50		
CEB 0302GR	1.5R	3	6	4	50		
CEB 0302GRD6	1.5R	3	6	6	50		
CEB 0402GR	2R	4	8	4	50		
CEB 0402GRD6	2R	4	8	6	50		
CEB 0502GR	2.5R	5	10	6	50		
CEB 0602GR	3R	6	12	6	50		
CEB 0802GR	4R	8	16	8	60		
CEB 1002GR	5R	10	20	10	75		
CEB 1202GR	6R	12	24	12	75		

備註：其他規格，請來電洽詢。 For other specifications, please call to inquire

適用材質 Work Material :

★最適合 Excellent ●適合 Better ▲佳 Good


碳素鋼 Carbon steels	合金鋼 Alloy steels	預硬鋼材 Pre-hardened steels					高硬度鋼 High-hardened					不銹鋼 Stainless steels	鈦合金 Titanium alloys	鎳基合金 Nickel Based alloys	銅合金 Copper alloys	鋁合金 Aluminum alloys
		~HRC45	~HRC50	~HRC55	~HRC60	~HRC65										
★	★	●					★	●			●	●				

高
效
能
防
震
系
列

高
效
能
防
震
系
列

CER 高效率R角銑刀

CER (Highly Efficient Operation, Corner Radius), 4 Flutes



單位: mm (Unit: mm)

產品編號 Model No.	刃徑 D × R角 R Diameter × Corner Radius	刃長 l Flute Length	柄徑 d Shank Diameter	全長 L Overall Length	價格 Price	備註
CER 010024GR	1 × 0.2R	3	4	50		
CER 015024GR	1.5 × 0.2R	4.5	4	50		
CER 015054GR	1.5 × 0.5R	4.5	4	50		
CER 020024GR	2 × 0.2R	6	4	50		
CER 020054GR	2 × 0.5R	6	4	50		
CER 025024GR	2.5 × 0.2R	7.5	4	50		
CER 025054GR	2.5 × 0.5R	7.5	4	50		
CER 030024GRD3	3 × 0.2R	9	3	50		
CER 030024GR	3 × 0.2R	9	4	50		
CER 030054GRD3	3 × 0.5R	9	3	50		
CER 030054GR	3 × 0.5R	9	4	50		
CER 030104GR	3 × 1R	9	4	50		
CER 040024GR	4 × 0.2R	12	4	50		
CER 040054GR	4 × 0.5R	12	4	50		
CER 040104GR	4 × 1R	12	4	50		
CER 060054GR	6 × 0.5R	18	6	50		
CER 060104GR	6 × 1R	18	6	50		
CER 080054GR	8 × 0.5R	24	8	60		
CER 080104GR	8 × 1R	24	8	60		
CER 100054GR	10 × 0.5R	30	10	75		
CER 100104GR	10 × 1R	30	10	75		
CER 120054GR	12 × 0.5R	36	12	75		
CER 120104GR	12 × 1R	36	12	75		
CER 120204GR	12 × 2R	36	12	75		

備註: 其他規格, 請來電洽詢。 For other specifications, please call to inquire


適用材質 Work Material:

★ 最適合 Excellent ● 適合 Better ▲ 佳 Good

碳素鋼 Carbon steels	合金鋼 Alloy steels	預硬鋼材 Pre-hardened steels	高硬度鋼 High-hardened					不銹鋼 Stainless steels	鈦合金 Titanium alloys	鎳基合金 Nickel Based alloys	銅合金 Copper alloys	鋁合金 Aluminum alloys
			~HRC45	~HRC50	~HRC55	~HRC60	~HRC65					
★	★	●						★	●		●	●

CHD 金鑽高性能圓溝銑刀

CHD For Highly Efficient Operation Milling Cutter, 4 Flutes



單位: mm (Unit: mm)

產品編號 Model No.	刃徑 D Diameter	刃長 l Flute Length	柄徑 d Shank Diameter	全長 L Overall Length	價格 Price	備註
CHD 0104ST	1	2.5	4	50		
CHD 0154ST	1.5	4	4	50		
CHD 0204ST	2	5	4	50		
CHD 0204STD6	2	5	6	50		
CHD 0254ST	2.5	7	4	50		
CHD 0254STD6	2.5	7	6	50		
CHD 0304ST	3	8	4	50		
CHD 0304STD6	3	8	6	50		
CHD 0354STD6	3.5	10	6	50		
CHD 0404ST	4	11	4	50		
CHD 0404STD6	4	11	6	50		
CHD 0454ST	4.5	13	6	50		
CHD 0504ST	5	13	6	50		
CHD 0554ST	5.5	15	6	50		
CHD 0604ST	6	15	6	50		
CHD 0654ST	6.5	18	8	60		
CHD 0704ST	7	18	8	60		
CHD 0754ST	7.5	20	8	60		
CHD 0804ST	8	20	8	60		
CHD 0854ST	8.5	23	10	75		
CHD 0904ST	9	23	10	75		
CHD 0954ST	9.5	25	10	75		
CHD 1004ST	10	30	10	75		
CHD 1054ST	10.5	28	12	75		
CHD 1104ST	11	28	12	75		
CHD 1154ST	11.5	30	12	75		
CHD 1204ST	12	30	12	75		
CHD 1304ST	13	40	16	100		
CHD 1404ST	14	40	16	100		
CHD 1504ST	15	45	16	100		
CHD 1604ST	16	50	16	100		
CHD 2004ST	20	50	20	100		

備註: 其他規格, 請來電洽詢。 For other specifications, please call to inquire

適用材質 Work Material:

★ 最適合 Excellent ● 適合 Better ▲ 佳 Good

碳素鋼 Carbon steels	合金鋼 Alloy steels	預硬鋼材 Pre-hardened steels	高硬度鋼 High-hardened					不銹鋼 Stainless steels	鈦合金 Titanium alloys	鎳基合金 Nickel Based alloys	銅合金 Copper alloys	鋁合金 Aluminum alloys
			~HRC45	~HRC50	~HRC55	~HRC60	~HRC65					
★	★	●						★	●		●	●

高效能防震系列

高效能防震系列

CHD 金鑽高效能四刃點數銑刀



CHD For Highly Efficient Operation (Decimal Diameter) Milling Cutter, 4 Flutes



單位：mm (Unit : mm)

產品編號 Model No.	刃徑 D Diameter	刃長 l Flute Length	柄徑 d Shank Diameter	全長 L Overall Length	價格 Price	備註
CHD 0214STD6	2.1	6	6	50		
CHD 0224STD6	2.2	6	6	50		
CHD 0234STD6	2.3	6	6	50		
CHD 0244STD6	2.4	6	6	50		
CHD 0264STD6	2.6	8	6	50		
CHD 0274STD6	2.7	8	6	50		
CHD 0284STD6	2.8	8	6	50		
CHD 0294STD6	2.9	8	6	50		
CHD 0314STD6	3.1	9	6	50		
CHD 0324STD6	3.2	9	6	50		
CHD 0334STD6	3.3	9	6	50		
CHD 0344STD6	3.4	9	6	50		
CHD 0364STD6	3.6	10	6	50		
CHD 0374STD6	3.7	10	6	50		
CHD 0384STD6	3.8	10	6	50		
CHD 0394STD6	3.9	10	6	50		
CHD 0414ST	4.1	11	6	50		
CHD 0424ST	4.2	11	6	50		
CHD 0434ST	4.3	11	6	50		
CHD 0444ST	4.4	11	6	50		
CHD 0464ST	4.6	13	6	50		
CHD 0474ST	4.7	13	6	50		
CHD 0484ST	4.8	13	6	50		
CHD 0494ST	4.9	13	6	50		
CHD 0514ST	5.1	14	6	50		
CHD 0524ST	5.2	14	6	50		
CHD 0534ST	5.3	14	6	50		
CHD 0544ST	5.4	14	6	50		
CHD 0564ST	5.6	15	6	50		
CHD 0574ST	5.7	15	6	50		
CHD 0584ST	5.8	15	6	50		
CHD 0594ST	5.9	15	6	50		
CHD 0614ST	6.1	17	8	60		
CHD 0624ST	6.2	17	8	60		
CHD 0634ST	6.3	17	8	60		
CHD 0644ST	6.4	17	8	60		
CHD 0664ST	6.6	18	8	60		
CHD 0674ST	6.7	18	8	60		

單位：mm (Unit : mm)

產品編號 Model No.	刃徑 D Diameter	刃長 l Flute Length	柄徑 d Shank Diameter	全長 L Overall Length	價格 Price	備註
CHD 0684ST	6.8	18	8	60		
CHD 0694ST	6.9	18	8	60		
CHD 0714ST	7.1	19	8	60		
CHD 0724ST	7.2	19	8	60		
CHD 0734ST	7.3	19	8	60		
CHD 0744ST	7.4	19	8	60		
CHD 0764ST	7.6	20	8	60		
CHD 0774ST	7.7	20	8	60		
CHD 0784ST	7.8	20	8	60		
CHD 0794ST	7.9	20	8	60		
CHD 0814ST	8.1	21	10	75		
CHD 0824ST	8.2	21	10	75		
CHD 0834ST	8.3	21	10	75		
CHD 0844ST	8.4	21	10	75		
CHD 0864ST	8.6	23	10	75		
CHD 0874ST	8.7	23	10	75		
CHD 0884ST	8.8	23	10	75		
CHD 0894ST	8.9	23	10	75		
CHD 0914ST	9.1	25	10	75		
CHD 0924ST	9.2	25	10	75		
CHD 0934ST	9.3	25	10	75		
CHD 0944ST	9.4	25	10	75		
CHD 0964ST	9.6	25	10	75		
CHD 0974ST	9.7	25	10	75		
CHD 0984ST	9.8	25	10	75		
CHD 0994ST	9.9	25	10	75		
CHD 1014ST	10.1	28	12	75		
CHD 1024ST	10.2	28	12	75		
CHD 1034ST	10.3	28	12	75		
CHD 1044ST	10.4	28	12	75		
CHD 1064ST	10.6	28	12	75		
CHD 1074ST	10.7	28	12	75		
CHD 1084ST	10.8	28	12	75		
CHD 1094ST	10.9	28	12	75		
CHD 1114ST	11.1	30	12	75		
CHD 1124ST	11.2	30	12	75		
CHD 1134ST	11.3	30	12	75		
CHD 1144ST	11.4	30	12	75		
CHD 1164ST	11.6	30	12	75		
CHD 1174ST	11.7	30	12	75		
CHD 1184ST	11.8	30	12	75		
CHD 1194ST	11.9	30	12	75		

備註：其他規格，請來電洽詢。 For other specifications, please call to inquire

高效能防震系列

高效能防震系列

AE 系列鋁用立銑刀

AE End Mills for Aluminum

極 致的垂直加工精度

Extreme verticality on machining

優 異的排屑性能

Excellent chip removal performance

快 速的進給速度

High speed for deep feed

實 現高速與精細的體現

Achieve high speed and fine performance



特別適用：鋁合金、銅合金、銅鋁合金

最好

Excellent

很好

Best

良好

Better

好

Good

特 性	垂直度	平滑度	效率
產品編號： AE 	好 Good	良好 Better	好 Good
產品編號： AEC 	很好 Best	很好 Best	良好 Better
產品編號： AED 	最好 Excellent	最好 Excellent	很好 Best
產品編號： AEW 	良好 Better	好 Good	最好 Excellent



HD MIT


慧德刀具五金有限公司 / 和東五金商行

TEL:886-4-7559458.886-4-7567158 FAX:886-4-7564341

專業 刀具 製造 廠
Specialized cutting tool factory

2 AED 戰鬥機鋁合金專用鎢鋼立銑刀

AED (For Aluminum Alloy), 3 Flutes




■ 高進給 high feed ■ 吸震佳 Good Anti-Vibration

單位：mm (Unit : mm)

產品編號 Model No.	刃徑 D Diameter	刃長 l Flute Length	柄徑 d Shank Diameter	全長 L Overall Length	價格 Price	備註
2 AED 0303	3	10	6	50		
2 AED 0353	3.5	11	6	50		
2 AED 0403	4	12	6	50		
2 AED 0453	4.5	13	6	50		
2 AED 0503	5	15	6	50		
2 AED 0553	5.5	17	6	50		
2 AED 0603	6	18	6	50		
2 AED 0803	8	24	8	60		
2 AED 1003	10	30	10	75		
2 AED 1203	12	36	12	75		
2 AED 1603	16	50	16	100		
2 AED 2003	20	50	20	100		

2 AEW 波浪鋁用刀

AEW (Aluminum End Mills - Wave Helix Blades Type), 3 Flutes



■ 高進給 high feed

■ 低負載 low load

單位：mm (Unit : mm)

產品編號 Model No.	刃徑 D Diameter	刃長 l Flute Length	柄徑 d Shank Diameter	全長 L Overall Length	價格 Price	備註
2 AEW 0603	6	16	6	50		
2 AEW 0803	8	20	8	60		
2 AEW 1003	10	25	10	75		
2 AEW 1203	12	30	12	75		
2 AEW 1603	16	45	16	100		
2 AEW 2003	20	50	20	100		

備註：其他規格，請來電洽詢。 For other specifications, please call to inquire


適用材質 Work Material：

★ 最適合 Excellent ● 適合 Better ▲ 佳 Good

碳素鋼 Carbon steels	合金鋼 Alloy steels	預硬鋼材	高硬度鋼					不銹鋼 Stainless steels	鈦合金 Titanium alloys	鎳基合金 Nickel Based alloys	銅合金 Copper alloys	鋁合金 Aluminum alloys
		Pre-hardened steels ~HRC45	~HRC50	~HRC55	~HRC60	~HRC65						
											★	★

2 AEC 鋁合金專用錫鋼立銑刀

AEC (For Aluminum Alloy), 3 Flutes



極致的垂直加工精度。
優異的排屑性能。
快速的進給速度。
實現高速與精細的體現。

單位：mm (Unit : mm)

產品編號 Model No.	刃徑 D Diameter	刃長 l Flute Length	柄徑 d Shank Diameter	全長 L Overall Length	價格 Price	備註
2 AEC 0103	1	3	4	50		
2 AEC 0153	1.5	5	4	50		
2 AEC 0203	2	6	4	50		
2 AEC 0203D6	2	6	6	50		
2 AEC 0253	2.5	8	4	50		
2 AEC 0253D6	2.5	8	6	50		
2 AEC 0303	3	9	4	50		
2 AEC 0303D6	3	9	6	50		
2 AEC 0403	4	12	4	50		
2 AEC 0403D6	4	12	6	50		
2 AEC 0503	5	15	6	50		
2 AEC 0603	6	18	6	50		
2 AEC 0703	7	21	8	60		
2 AEC 0803	8	24	8	60		
2 AEC 0903	9	27	10	75		
2 AEC 1003	10	30	10	75		
2 AEC 1103	11	33	12	75		
2 AEC 1203	12	36	12	75		
2 AEC 1403	14	45	14	100		
2 AEC 1603	16	50	16	100		
2 AEC 2003	20	50	20	100		

備註：其他規格，請來電洽詢。 For other specifications, please call to inquire

適用材質 Work Material :

★最適合 Excellent ●適合 Better ▲佳 Good

碳素鋼 Carbon steels	合金鋼 Alloy steels	預硬鋼材 Pre-hardened steels	高硬度鋼 High-hardened					不銹鋼 Stainless steels	鈦合金 Titanium alloys	鎳基合金 Nickel Based alloys	銅合金 Copper alloys	鋁合金 Aluminum alloys
			~HRC45	~HRC50	~HRC55	~HRC60	~HRC65					
											★	★

2 AELC 鋁合金專用長刃錫鋼立銑刀

AELC (Long Flute Length, For Aluminum Alloy), 3 Flutes



單位：mm (Unit : mm)

產品編號 Model No.	刃徑 D Diameter	刃長 l Flute Length	柄徑 d Shank Diameter	全長 L Overall Length	價格 Price	備註
2 AELC 0103	1	5	6	50		
2 AELC 0153	1.5	8	6	50		
2 AELC 0203	2	10	6	50		
2 AELC 0203S12	2	12	6	50		
2 AELC 0303	3	15	6	50		
2 AELC 0403	4	20	6	75		
2 AELC 0403S25	4	25	6	75		
2 AELC 0503	5	25	6	75		
2 AELC 0603	6	30	6	75		
2 AELC 0603S40	6	40	6	100		
2 AELC 0603S50	6	50	6	100		
2 AELC 0703	7	35	8	100		
2 AELC 0803	8	40	8	100		
2 AELC 0803S50	8	50	8	100		
2 AELC 0903	9	45	10	100		
2 AELC 1003	10	50	10	100		
2 AELC 1003S60	10	60	10	100		
2 AELC 1103	11	50	12	100		
2 AELC 1203S50	12	50	12	100		
2 AELC 1203S60	12	60	12	100		
2 AELC 1603S65	16	65	16	120		
2 AELC 1603S80	16	80	16	150		
2 AELC 2003S65	20	65	20	120		
2 AELC 2003S80	20	80	20	150		

備註：其他規格，請來電洽詢。 For other specifications, please call to inquire


適用材質 Work Material :

★最適合 Excellent ●適合 Better ▲佳 Good

碳素鋼 Carbon steels	合金鋼 Alloy steels	預硬鋼材 Pre-hardened steels	高硬度鋼 High-hardened					不銹鋼 Stainless steels	鈦合金 Titanium alloys	鎳基合金 Nickel Based alloys	銅合金 Copper alloys	鋁合金 Aluminum alloys
			~HRC45	~HRC50	~HRC55	~HRC60	~HRC65					
											★	★

2 AE 龍捲風鋁合金專用三刃鎢鋼立銑刀

AE (For Aluminum Alloy), 3 Flutes



■ 大切深, 高進給, 加工面精細

單位: mm (Unit: mm)

產品編號 Model No.	刃徑 D Diameter	刃長 l Flute Length	柄徑 d Shank Diameter	全長 L Overall Length	價格 Price	備註
2 AE 0103	1	3	4	50		
2 AE 0153	1.5	4.5	4	50		
2 AE 0203	2	6	4	50		
2 AE 0203D6	2	6	6	50		
2 AE 0253	2.5	8	4	50		
2 AE 0253D6	2.5	8	6	50		
2 AE 0303D3	3	10	3	50		
2 AE 0303	3	10	4	50		
2 AE 0303D6	3	10	6	50		
2 AE 0353	3.5	11	4	50		
2 AE 0353D6	3.5	11	6	50		
2 AE 0403	4	12	4	50		
2 AE 0403D6	4	12	6	50		
2 AE 0453	4.5	13	6	50		
2 AE 0503	5	15	6	50		
2 AE 0603	6	18	6	50		
2 AE 0703	7	21	8	60		
2 AE 0803	8	24	8	60		
2 AE 0903	9	27	10	75		
2 AE 1003	10	30	10	75		
2 AE 1103	11	33	12	75		
2 AE 1203	12	36	12	75		
2 AE 1403	14	45	14	100		
2 AE 1403D16	14	45	16	100		
2 AE 1603	16	50	16	100		
2 AE 2003	20	50	20	100		

備註: 其他規格, 請來電洽詢。 For other specifications, please call to inquire

適用材質: ★ 最適合 Excellent ● 適合 Better ▲ 佳 Good

碳素鋼 Carbon steels	合金鋼 Alloy steels	預硬鋼材 Pre-hardened steels ~HRC45	高硬度鋼 High-hardened					不銹鋼 Stainless steels	鈦合金 Titanium alloys	鎳基合金 Nickel Based alloys	銅合金 Copper alloys	鋁合金 Aluminum alloys
			~HRC50	~HRC55	~HRC60	~HRC65						
											★	★

2 SLAE / MLAE 龍捲風鋁合金專用三刃長柄鎢鋼立銑刀

SLAE / MLAE (Long Shank, For Aluminum Alloy), 3 Flutes



單位: mm (Unit: mm)

產品編號 Model No.	刃徑 D Diameter	刃長 l Flute Length	柄徑 d Shank Diameter	全長 L Overall Length	價格 Price	備註
2 SLAE 0403	4	12	4	75		
2 SLAE 0503	5	15	6	75		
2 SLAE 0603	6	18	6	75		
2 MLAE 0603	6	18	6	100		
2 SLAE 0803	8	24	8	75		
2 MLAE 0803	8	24	8	100		
2 MLAE 1003	10	30	10	100		
2 MLAE 1203	12	36	12	100		

備註: 其他規格, 請來電洽詢。 For other specifications, please call to inquire

適用材質 Work Material: ★ 最適合 Excellent ● 適合 Better ▲ 佳 Good

碳素鋼 Carbon steels	合金鋼 Alloy steels	預硬鋼材 Pre-hardened steels ~HRC45	高硬度鋼 High-hardened					不銹鋼 Stainless steels	鈦合金 Titanium alloys	鎳基合金 Nickel Based alloys	銅合金 Copper alloys	鋁合金 Aluminum alloys
			~HRC50	~HRC55	~HRC60	~HRC65						
											★	★

2 AEL 龍捲風鋁合金專用三刃長刃鎢鋼立銑刀  

AEL (Long Flute Length, For Aluminum Alloy), 3 Flutes



單位：mm (Unit : mm)

產品編號 Model No.	刃徑 D Diameter	刃長 l Flute Length	柄徑 d Shank Diameter	全長 L Overall Length	價格 Price	備註
2 AEL 0103D6	1	5	6	50		
2 AEL 0153D6	1.5	8	6	50		
2 AEL 0153S10D6	1.5	10	6	50		
2 AEL 0203D6	2	10	6	50		
2 AEL 0203S12D6	2	12	6	50		
2 AEL 0253D6S13	2.5	13	6	50		
2 AEL 0303D6	3	15	6	75		
2 AEL 0303D6S18	3	18	6	75		
2 AEL 0403D6S16	4	16	6	50		
2 AEL 0403	4	20	4	75		
2 AEL 0403D6	4	20	6	75		
2 AEL 0403D6S25	4	25	6	75		
2 AEL 0503S20	5	20	6	75		
2 AEL 0503	5	25	6	75		
2 AEL 0503S30	5	30	6	75		
2 AEL 0503S40	5	40	6	100		
2 AEL 0603S25L75	6	25	6	75		
2 AEL 0603	6	30	6	75		
2 AEL 0603L100	6	30	6	100		
2 AEL 0603S35L100	6	35	6	100		
2 AEL 0603S40L100	6	40	6	100		
2 AEL 0603S45L100	6	45	6	100		
2 AEL 0603S50L100	6	50	6	100		
2 AEL 0703L100	7	35	8	100		
2 AEL 0803S32	8	32	8	75		
2 AEL 0803L100	8	40	8	100		
2 AEL 0803S50L100	8	50	8	100		
2 AEL 0903	9	45	10	100		

單位：mm (Unit : mm)

產品編號 Model No.	刃徑 D Diameter	刃長 l Flute Length	柄徑 d Shank Diameter	全長 L Overall Length	價格 Price	備註
2 AEL 1003S40	10	40	10	100		
2 AEL 1003	10	50	10	100		
2 AEL 1003S60	10	60	10	100		
2 AEL 1103	11	50	12	100		
2 AEL 1203S50	12	50	12	100		
2 AEL 1203S55	12	55	12	100		
2 AEL 1203S60	12	60	12	100		
2 AEL 1403	14	65	14	120		
2 AEL 1603S55	16	55	16	100		
2 AEL 1603S60	16	60	16	120		
2 AEL 1603S65	16	65	16	120		
2 AEL 1603S80	16	80	16	150		
2 AEL 1603S100	16	100	16	150		
2 AEL 2003S60	20	60	20	100		
2 AEL 2003S65	20	65	20	120		
2 AEL 2003S80	20	80	20	150		
2 AEL 2003S100	20	100	20	150		

備註：其他規格，請來電洽詢。 For other specifications, please call to inquire


適用材質 Work Material :

★ 最適合 Excellent ● 適合 Better ▲ 佳 Good

碳素鋼 Carbon steels	合金鋼 Alloy steels	預硬鋼材	高硬度鋼				不銹鋼 Stainless steels	鈦合金 Titanium alloys	鎳基合金 Nickel Based alloys	銅合金 Copper alloys	鋁合金 Aluminum alloys
		Pre-hardened steels	High-hardened								
		~HRC45	~HRC50	~HRC55	~HRC60	~HRC65				★	★

2 ACB 鋁銅專用二刃鎢鋼球刀

ACB (Ball Nose, Aluminum Alloy), 2 Flutes



單位：mm (Unit : mm)

產品編號 Model No.	球頭半徑 R Radius	刃徑 D Diameter	刃長 l Flute Length	柄徑 d Shank Diameter	全長 L Overall Length	價格 Price	備註
2 ACB 0042	0.2R	0.4	1.2	4	50		
2 ACB 0052	0.25R	0.5	1.5	4	50		
2 ACB 0062	0.3R	0.6	1.8	4	50		
2 ACB 0082	0.4R	0.8	2.4	4	50		
2 ACB 0102	0.5R	1	3	4	50		
2 ACB 0152	0.75R	1.5	5	4	50		
2 ACB 0202	1R	2	6	4	50		
2 ACB 0252	1.25R	2.5	8	4	50		
2 ACB 0302D3	1.5R	3	10	3	50		
2 ACB 0302	1.5R	3	10	4	50		
2 ACB 0302D6	1.5R	3	10	6	50		
2 ACB 0402	2R	4	12	4	50		
2 ACB 0402D6	2R	4	12	6	50		
2 ACB 0502	2.5R	5	15	6	50		
2 ACB 0602	3R	6	18	6	50		
2 SLACB 0802	4R	8	24	8	75		
2 ACB 1002	5R	10	30	10	75		
2 ACB 1202	6R	12	30	12	75		

備註：其他規格，請來電洽詢。 For other specifications, please call to inquire

適用材質 Work Material :

★最適合 Excellent ●適合 Better ▲佳 Good

碳素鋼 Carbon steels	合金鋼 Alloy steels	預硬鋼材	高硬度鋼				不銹鋼 Stainless steels	鈦合金 Titanium alloys	鎳基合金 Nickel Based alloys	銅合金 Copper alloys	鋁合金 Aluminum alloys
		Pre-hardened steels	High-hardened								
		~HRC45	~HRC50	~HRC55	~HRC60	~HRC65				★	★

2 SLACB / MLACB / LLACB 鋁銅專用長柄鎢鋼球刀

SLACB/MLACB/LLACB (Long Shank Ball Nose End Mill for Aluminum Alloy), 2 Flutes



單位：mm (Unit : mm)

產品編號 Model No.	球頭半徑 R Radius	刃徑 D Diameter	刃長 l Flute Length	柄徑 d Shank Diameter	全長 L Overall Length	價格 Price	備註
2 SLACB 0102D6	0.5R	1	3	6	75		
2 MLACB 0102	0.5R	1	3	6	100		
2 SLACB 0152D6	0.75R	1.5	5	6	75		
2 MLACB 0152	0.75R	1.5	5	6	100		
2 SLACB 0202D6	1R	2	6	6	75		
2 MLACB 0202	1R	2	6	6	100		
2 SLACB 0302D6	1.5R	3	10	6	75		
2 MLACB 0302	1.5R	3	10	6	100		
2 SLACB 0402	2R	4	12	4	75		
2 SLACB 0402D6	2R	4	12	6	75		
2 MLACB 0402	2R	4	12	6	100		
2 SLACB 0502	2.5R	5	15	6	75		
2 MLACB 0502	2.5R	5	15	6	100		
2 SLACB 0602	3R	6	18	6	75		
2 MLACB 0602	3R	6	18	6	100		
2 SLACB 0802	4R	8	24	8	75		
2 MLACB 0802	4R	8	24	8	100		
2 LLACB 0802	4R	8	24	8	150		
2 MLACB 1002	5R	10	30	10	100		
2 LLACB 1002	5R	10	30	10	150		
2 MLACB 1202	6R	12	30	12	100		
2 LLACB 1202	6R	12	30	12	150		

備註：其他規格，請來電洽詢。 For other specifications, please call to inquire


適用材質 Work Material :

★最適合 Excellent ●適合 Better ▲佳 Good

碳素鋼 Carbon steels	合金鋼 Alloy steels	預硬鋼材	高硬度鋼				不銹鋼 Stainless steels	鈦合金 Titanium alloys	鎳基合金 Nickel Based alloys	銅合金 Copper alloys	鋁合金 Aluminum alloys
		Pre-hardened steels	High-hardened								
		~HRC45	~HRC50	~HRC55	~HRC60	~HRC65				★	★

2 AR 鋁銅專用三刃鎢鋼R角銑刀

AR (Corner Radius, For Aluminum Alloy), 3 Flutes



產品編號 Model No.	刃徑 D × R角 R Diameter × Corner Radius	刃長 l Flute Length	柄徑 d Shank Diameter	全長 L Overall Length	價格 Price	備註
2 AR 010023	1 × 0.2R	3	4	50		
2 AR 015023	1.5 × 0.2R	5	4	50		
2 AR 015053	1.5 × 0.5R	5	4	50		
2 AR 020023	2 × 0.2R	6	4	50		
2 AR 020053	2 × 0.5R	6	4	50		
2 AR 025023	2.5 × 0.2R	8	4	50		
2 AR 025053	2.5 × 0.5R	8	4	50		
2 AR 030023D3	3 × 0.2R	10	3	50		
2 AR 030023	3 × 0.2R	10	4	50		
2 AR 030053D3	3 × 0.5R	10	3	50		
2 AR 030053	3 × 0.5R	10	4	50		
2 AR 030053D6	3 × 0.5R	10	6	50		
2 AR 030103D3	3 × 1R	10	3	50		
2 AR 030103	3 × 1R	10	4	50		
2 AR 030103D6	3 × 1R	10	6	50		
2 AR 040023	4 × 0.2R	12	4	50		
2 AR 040053	4 × 0.5R	12	4	50		
2 AR 040053D6	4 × 0.5R	12	6	50		
2 AR 040103	4 × 1R	12	4	50		
2 AR 040103D6	4 × 1R	12	6	50		
2 AR 050053	5 × 0.5R	15	6	50		
2 AR 050103	5 × 1R	15	6	50		
2 AR 050153	5 × 1.5R	15	6	50		
2 AR 060023	6 × 0.2R	18	6	50		
2 AR 060053	6 × 0.5R	18	6	50		
2 AR 060103	6 × 1R	18	6	50		
2 AR 060153	6 × 1.5R	18	6	50		
2 AR 060203	6 × 2R	18	6	50		
2 AR 060253	6 × 2.5R	18	6	50		

單位: mm (Unit: mm)

產品編號 Model No.	刃徑 D × R角 R Diameter × Corner Radius	刃長 l Flute Length	柄徑 d Shank Diameter	全長 L Overall Length	價格 Price	備註
2 AR 080053	8 × 0.5R	24	8	60		
2 AR 080103	8 × 1R	24	8	60		
2 AR 080203	8 × 2R	24	8	60		
2 AR 080303	8 × 3R	24	8	60		
2 AR 100053	10 × 0.5R	30	10	75		
2 AR 100103	10 × 1R	30	10	75		
2 AR 100153	10 × 1.5R	30	10	75		
2 AR 100203	10 × 2R	30	10	75		
2 AR 100253	10 × 2.5R	30	10	75		
2 AR 100303	10 × 3R	30	10	75		
2 AR 100403	10 × 4R	30	10	75		
2 AR 120103	12 × 1R	36	12	75		
2 AR 120153	12 × 1.5R	36	12	75		
2 AR 120203	12 × 2R	36	12	75		
2 AR 120253	12 × 2.5R	36	12	75		
2 AR 120303	12 × 3R	36	12	75		
2 AR 120403	12 × 4R	36	12	75		
2 AR 140103	14 × 1R	45	14	100		
2 AR 140203	14 × 2R	45	14	100		
2 AR 140303	14 × 3R	45	14	100		
2 AR 160103	16 × 1R	50	16	100		
2 AR 160203	16 × 2R	50	16	100		
2 AR 160303	16 × 3R	50	16	100		
2 AR 160403	16 × 4R	50	16	100		
2 AR 160503	16 × 5R	50	16	100		
2 AR 200103	20 × 1R	50	20	100		
2 AR 200203	20 × 2R	50	20	100		
2 AR 200303	20 × 3R	50	20	100		
2 AR 200403	20 × 4R	50	20	100		
2 AR 200503	20 × 5R	50	20	100		

備註: 其他規格, 請來電洽詢。 For other specifications, please call to inquire


適用材質 Work Material:

★ 最適合 Excellent ● 適合 Better ▲ 佳 Good

碳素鋼 Carbon steels	合金鋼 Alloy steels	預硬鋼材 Pre-hardened steels	高硬度鋼 High-hardened				不銹鋼 Stainless steels	鈦合金 Titanium alloys	鎳基合金 Nickel Based alloys	銅合金 Copper alloys	鋁合金 Aluminum alloys
		~HRC45	~HRC50	~HRC55	~HRC60	~HRC65					
										★	★

② SLAR / MLAR / LLAR 鋁銅專用長柄鎢鋼R角銑刀

SLAR/MLAR/LLAR (Long Shank Corner Radius, For Aluminum Alloy), 3 Flutes



單位：mm (Unit : mm)

產品編號 Model No.	刃徑 D × R角 R Diameter × Corner Radius	刃長 l Flute Length	柄徑 d Shank Diameter	全長 L Overall Length	價格 Price	備註
2 SLAR 030023	3 × 0.2R	10	4	75		
2 SLAR 040023	4 × 0.2R	12	4	75		
2 SLAR 040053	4 × 0.5R	12	4	75		
2 SLAR 040103	4 × 1R	12	4	75		
2 SLAR 060023	6 × 0.2R	18	6	75		
2 SLAR 060103	6 × 1R	18	6	75		
2 MLAR 060103	6 × 1R	18	6	100		
2 SLAR 060203	6 × 2R	18	6	75		
2 SLAR 080023	8 × 0.2R	24	8	75		
2 SLAR 080053	8 × 0.5R	24	8	75		
2 SLAR 080103	8 × 1R	24	8	75		
2 SLAR 080153	8 × 1.5R	24	8	75		
2 SLAR 080203	8 × 2R	24	8	75		
2 SLAR 080253	8 × 2.5R	24	8	75		
2 SLAR 080303	8 × 3R	24	8	75		
2 MLAR 100103	10 × 1R	30	10	100		
2 LLAR 100303	10 × 3R	30	10	150		
2 MLAR 120153S30	12 × 1.5R	36	12	100		
2 LLAR 120103S30	12 × 1R	36	12	150		

備註：其他規格，請來電洽詢。 For other specifications, please call to inquire

適用材質 Work Material :

★ 最適合 Excellent ● 適合 Better ▲ 佳 Good

碳素鋼 Carbon steels	合金鋼 Alloy steels	預硬鋼材	高硬度鋼					不銹鋼 Stainless steels	鈦合金 Titanium alloys	鎳基合金 Nickel Based alloys	銅合金 Copper alloys	鋁合金 Aluminum alloys
		Pre-hardened steels	High-hardened									
		~HRC45	~HRC50	~HRC55	~HRC60	~HRC65					★	★

Hwe Der Machinery and Hardware Pty Ltd.

專業 刀 具 製 造 廠
Specialized cutting tool factory

www.hdtools.com.tw



【高效率切削刀具】
High Efficiency cutting tools

- 高精度模具專用銑刀 Carbide End Mill For High Accuracy
- 高效率鎢鋼銑刀 Carbide End Mill For High Efficiency
- 成型刀訂製 Customized Cutting Tool
- 三省節能科技刀頭 Energy-saving Technology Endmill Head
- 鎢鋼抗震刀柄 GL Tungsten Carbide Anti-Vibration Tools Holder
- 鎢鋼後拉刀桿 Tungsten Carbide Toolholder-HDC/HUC Collet Chuck
- 鎢鋼小徑搪孔刀桿 Tungsten Carbide Boring System Tool Holder-Micro Diameter
- 鎢鋼搪孔刀柄 GLCK Tungsten Carbide Anti-Vibration Boring System Tool Holder



FACEBOOK



LINE ID:@hdtools



Online Shopping




② 太陽戰士系列 THE SUN SERIES

使用超微粒 0.6u m/m Co10% 鎢鋼製成，搭配TXM 高潤滑性塗層，適用於溼式加工，碳素鋼、合金鋼~HRC52 之鋼材、不鏽鋼、鈦合金廣泛運用。

- 1.所有的產品皆採用高品質的鎢鋼材料
High Quality Tungsten Steels Materials for Production.
- 2.強力溝型設計，可增加排屑空間
The heavy groove type design will increase the chip removal.
- 3.塗層-搭配 "耐磨性" 及 "耐熱裂性" 的塗層，適用於中高硬度溼式加工
Coating-With "High wear resistance" and "High thermal crack resistance", which will suited for wet cutting with high hardness steels.
- 4.廣泛應用於機械加工廠、水五金產業、汽機車產業、自行車產業、緊固件產業
Wide used in Machinery processing factory, Plumbing Hardware Industry, Automobile and motorcycle industry, Bicycles industry, Fastener industry.

② MHD 四刃重切削鎢鋼立銑刀

MHD (Heavy Cutting Operation Type), 4 Flutes



單位：mm (Unit : mm)

產品編號 Model No.	刃徑 D Diameter	刃長 L Flute Length	柄徑 d Shank Diameter	全長 L Overall Length	價格 Price	備註
2 MPE 0104TXM	1	3	4	50		
2 PE 0104TXM	1	3	6	50		
2 MPE 0154TXM	1.5	4	4	50		
2 PE 0154TXM	1.5	4	6	50		
2 MPE 0204TXM	2	6	4	50		
2 PE 0204TXM	2	6	6	50		
2 MPE 0254TXM	2.5	8	4	50		
2 PE 0254TXM	2.5	8	6	50		
2 MHD 0304TXMD3	3	8	3	50		
2 MHD 0304TXM	3	8	4	50		
2 MHD 0304TXMD6	3	8	6	50		
2 MHD 0354TXM	3.5	10	4	50		
2 MHD 0354TXMD6	3.5	10	6	50		
2 MHD 0404TXM	4	11	4	50		
2 MHD 0404TXMD6	4	11	6	50		
2 MHD 0454TXM	4.5	13	6	50		
2 MHD 0504TXM	5	13	6	50		
2 MHD 0554TXM	5.5	15	6	50		
2 MHD 0604TXM	6	16	6	50		
2 MHD 0654TXM	6.5	18	8	60		
2 MHD 0704TXM	7	18	8	60		
2 MHD 0754TXM	7.5	20	8	60		
2 MHD 0804TXM	8	20	8	60		
2 MHD 0854TXM	8.5	24	10	75		
2 MHD 0904TXM	9	23	10	75		
2 MHD 1004TXM	10	30	10	75		
2 MHD 1104TXM	11	28	12	75		
2 MHD 1204TXM	12	30	12	75		
2 MHD 1304TXM	13	40	16	100		
2 MHD 1404TXM	14	40	16	100		
2 MHD 1504TXM	15	40	16	100		
2 MHD 1604TXM	16	50	16	100		
2 MHD 1804TXM	18	50	20	100		
2 MHD 2004TXM	20	50	20	100		


備註：其他規格，請來電洽詢。 For other specifications, please call to inquire

適用材質 Work Material :

★ 最適合 Excellent ● 適合 Better ▲ 佳 Good

碳素鋼 Carbon steels	合金鋼 Alloy steels	預硬鋼材 Pre-hardened steels		高硬度鋼 High-hardened				不銹鋼 Stainless steels	鈦合金 Titanium alloys	鎳基合金 Nickel Based alloys	銅合金 Copper alloys	鋁合金 Aluminum alloys
		~HRC45	~HRC50	~HRC55	~HRC60	~HRC65						
★	★	●	▲					●			●	

2 SLE4 / MLE4 / LLE4 四刃長柄鎢鋼立銑刀 TXM 45 h5 HRC52
SLE4/MLE4/LLE4 (Long Shank, Regular Length), 4 Flutes



單位：mm (Unit : mm)

產品編號 Model No.	刃徑 D Diameter	刃長 l Flute Length	柄徑 d Shank Diameter	全長 L Overall Length	價格 Price	備註
2 SLE 0104TXMD6	1	3	6	75		
2 MLE 0104TXMD6	1	3	6	100		
2 SLE 0154TXMD6	1.5	4	6	75		
2 MLE 0154TXMD6	1.5	4	6	100		
2 SLE 0204TXMD6	2	6	6	75		
2 MLE 0204TXMD6	2	6	6	100		
2 SLE 0254TXMD6	2.5	6	6	75		
2 MLE 0254TXMD6	2.5	6	6	100		
2 SLE 0304TXMD3	3	8	3	75		
2 SLE 0304TXM	3	8	4	75		
2 SLE 0304TXMD6	3	8	6	75		
2 MLE 0304TXMD3	3	8	3	100		
2 MLE 0304TXM	3	8	4	100		
2 MLE 0304TXMD6	3	8	6	100		
2 SLE 0404TXM	4	11	4	75		
2 SLE 0404TXMD6	4	11	6	75		
2 MLE 0404TXM	4	11	4	100		
2 MLE 0404TXMD6	4	11	6	100		
2 SLE 0504TXM	5	13	6	75		
2 MLE 0504TXM	5	13	6	100		
2 SLE 0604TXM	6	16	6	75		
2 MLE 0604TXM	6	16	6	100		

單位：mm (Unit : mm)

產品編號 Model No.	刃徑 D Diameter	刃長 l Flute Length	柄徑 d Shank Diameter	全長 L Overall Length	價格 Price	備註
2 MLE 0704TXM	7	18	8	100		
2 SLE 0804TXM	8	20	8	75		
2 MLE 0804TXM	8	20	8	100		
2 LLE 0804TXM	8	20	8	150		
2 MLE 0904TXM	9	23	10	100		
2 MLE 1004TXM	10	30	10	100		
2 LLE 1004TXM	10	30	10	150		
2 MLE 1204TXM	12	30	12	100		
2 LLE 1204TXM	12	30	12	150		
2 MLE 1604TXM	16	50	16	150		
2 LLE 1604TXM	16	50	16	200		
2 MLE 2004TXM	20	50	20	150		
2 LLE 2004TXM	20	50	20	200		

備註：其他規格，請來電洽詢。 For other specifications, please call to inquire


適用材質 Work Material :

★ 最適合 Excellent ● 適合 Better ▲ 佳 Good

碳素鋼 Carbon steels	合金鋼 Alloy steels	預硬鋼材	高硬度鋼					不銹鋼 Stainless steels	鈦合金 Titanium alloys	鎳基合金 Nickel Based alloys	銅合金 Copper alloys	鋁合金 Aluminum alloys
		Pre-hardened steels ~HRC45	High-hardened ~HRC50 ~HRC55 ~HRC60 ~HRC65									
★	★	●	▲					●			●	

2 LET4 四刃長刃鎢鋼立銑刀

LET4 (Long Flute Length End Mill), 4 Flutes



單位：mm (Unit : mm)

產品編號 Model No.	刃徑 D Diameter	刃長 l Flute Length	柄徑 d Shank Diameter	全長 L Overall Length	價格 Price	備註
2 LET 0104TXM	1	5	4	50		
2 LET 0154TXM	1.5	8	4	50		
2 LET 0204TXM	2	10	4	50		
2 LET 0254TXM	2.5	13	4	50		
2 LET 0304TXM	3	15	6	50		
2 LET 0404TXM	4	20	6	75		
2 LET 0504TXM	5	25	6	75		
2 LET 0604TXM	6	30	6	75		
2 LET 0704TXM	7	35	8	100		
2 LET 0804TXM	8	40	8	100		
2 LET 0904TXM	9	45	10	100		
2 LET 1004TXM	10	50	10	100		
2 LET 1204TXM	12	50	12	100		
2 LET 1604TXM	16	80	16	150		
2 LET 2004TXM	20	80	20	150		

備註：其他規格，請來電洽詢。 For other specifications, please call to inquire


適用材質 Work Material :

★最適合 Excellent ●適合 Better ▲佳 Good

碳素鋼 Carbon steels	合金鋼 Alloy steels	預硬鋼材 Pre-hardened steels ~HRC45	高硬度鋼 High-hardened				不銹鋼 Stainless steels	鈦合金 Titanium alloys	鎳基合金 Nickel Based alloys	銅合金 Copper alloys	鋁合金 Aluminum alloys
			~HRC50	~HRC55	~HRC60	~HRC65					
★	★	●	▲				●		●		

2 SE2 二刃鎢鋼立銑刀

SE2 (Regular Length), 2 Flutes



單位：mm (Unit : mm)

產品編號 Model No.	刃徑 D Diameter	刃長 l Flute Length	柄徑 d Shank Diameter	全長 L Overall Length	價格 Price	備註
2 SE 0102TXM	1	3	6	50		
2 SE 0152TXM	1.5	4	6	50		
2 SE 0202TXM	2	6	6	50		
2 SE 0252TXM	2.5	7	6	50		
2 SE 0302TXM	3	8	6	50		
2 SE 0352TXM	3.5	10	6	50		
2 SE 0402TXM	4	11	6	50		
2 SE 0502TXM	5	13	6	50		
2 SE 0602TXM	6	16	6	50		
2 SE 0702TXM	7	18	8	60		
2 SE 0802TXM	8	20	8	60		
2 SE 0902TXM	9	23	10	75		
2 SE 1002TXM	10	30	10	75		
2 SE 1102TXM	11	30	12	75		
2 SE 1202TXM	12	30	12	75		

備註：其他規格，請來電洽詢。 For other specifications, please call to inquire

適用材質 Work Material :


★最適合 Excellent ●適合 Better ▲佳 Good

碳素鋼 Carbon steels	合金鋼 Alloy steels	預硬鋼材 Pre-hardened steels ~HRC45	高硬度鋼 High-hardened					不銹鋼 Stainless steels	鈦合金 Titanium alloys	鎳基合金 Nickel Based alloys	銅合金 Copper alloys	鋁合金 Aluminum alloys
			~HRC50	~HRC55	~HRC60	~HRC65						
★	★	●	▲					●			●	

2 MSE2 / SE2 二刃點數鎢鋼立銑刀



MSE2/SE2 (Flat End Mill), 2 Flutes-Micro Decimal Diameter



單位 : mm (Unit : mm)

產品編號 Model No.	刃徑 D Diameter	刃長 l Flute Length	柄徑 d Shank Diameter	全長 L Overall Length	價格 Price	備註
2 MSE 0012OL	0.1	0.2	4	50		
2 MSE 0022OL	0.2	0.4	4	50		
2 MSE 0032OL	0.3	0.6	4	50		
2 MSE 0042OL	0.4	0.8	4	50		
2 MSE 0052OL	0.5	1	4	50		
2 MSE 0062OL	0.6	1.2	4	50		
2 MSE 0072OL	0.7	1.4	4	50		
2 MSE 0082OL	0.8	1.6	4	50		
2 MSE 0092OL	0.9	1.8	4	50		
2 MSE 0112TXM	1.1	3	4	50		
2 MSE 0122TXM	1.2	3	4	50		
2 MSE 0132TXM	1.3	3	4	50		
2 MSE 0142TXM	1.4	3	4	50		
2 MSE 0162TXM	1.6	4	4	50		
2 MSE 0172TXM	1.7	4	4	50		
2 MSE 0182TXM	1.8	4	4	50		
2 MSE 0192TXM	1.9	4	4	50		
2 MSE 0212TXM	2.1	6	4	50		
2 MSE 0222TXM	2.2	6	4	50		
2 MSE 0232TXM	2.3	6	4	50		
2 MSE 0242TXM	2.4	6	4	50		
2 MSE 0262TXM	2.6	8	4	50		
2 MSE 0272TXM	2.7	8	4	50		
2 MSE 0282TXM	2.8	8	4	50		
2 MSE 0292TXM	2.9	8	4	50		
2 MSE 0312TXM	3.1	9	4	50		
2 MSE 0322TXM	3.2	9	4	50		
2 MSE 0332TXM	3.3	9	4	50		
2 MSE 0342TXM	3.4	9	4	50		
2 MSE 0362TXM	3.6	10	4	50		
2 MSE 0372TXM	3.7	10	4	50		
2 MSE 0382TXM	3.8	10	4	50		
2 MSE 0392TXM	3.9	10	4	50		
2 SE 0412TXM	4.1	11	6	50		
2 SE 0422TXM	4.2	11	6	50		
2 SE 0432TXM	4.3	11	6	50		
2 SE 0442TXM	4.4	11	6	50		
2 SE 0452TXM	4.5	13	6	50		
2 SE 0462TXM	4.6	13	6	50		
2 SE 0472TXM	4.7	13	6	50		
2 SE 0482TXM	4.8	13	6	50		
2 SE 0492TXM	4.9	13	6	50		

單位 : mm (Unit : mm)

產品編號 Model No.	刃徑 D Diameter	刃長 l Flute Length	柄徑 d Shank Diameter	全長 L Overall Length	價格 Price	備註
2 SE 0512TXM	5.1	14	6	50		
2 SE 0522TXM	5.2	14	6	50		
2 SE 0532TXM	5.3	14	6	50		
2 SE 0542TXM	5.4	14	6	50		
2 SE 0552TXM	5.5	15	6	50		
2 SE 0562TXM	5.6	15	6	50		
2 SE 0572TXM	5.7	15	6	50		
2 SE 0582TXM	5.8	15	6	50		
2 SE 0592TXM	5.9	15	6	50		
2 SE 0612TXM	6.1	17	8	60		
2 SE 0622TXM	6.2	17	8	60		
2 SE 0632TXM	6.3	17	8	60		
2 SE 0642TXM	6.4	17	8	60		
2 SE 0652TXM	6.5	18	8	60		
2 SE 0662TXM	6.6	18	8	60		
2 SE 0672TXM	6.7	18	8	60		
2 SE 0682TXM	6.8	18	8	60		
2 SE 0692TXM	6.9	18	8	60		
2 SE 0712TXM	7.1	19	8	60		
2 SE 0722TXM	7.2	19	8	60		
2 SE 0732TXM	7.3	19	8	60		
2 SE 0742TXM	7.4	19	8	60		
2 SE 0752TXM	7.5	20	8	60		
2 SE 0762TXM	7.6	20	8	60		
2 SE 0772TXM	7.7	20	8	60		
2 SE 0782TXM	7.8	20	8	60		
2 SE 0792TXM	7.9	20	8	60		
2 SE 0812TXM	8.1	21	10	75		
2 SE 0822TXM	8.2	21	10	75		
2 SE 0832TXM	8.3	21	10	75		
2 SE 0842TXM	8.4	21	10	75		
2 SE 0852TXM	8.5	23	10	75		
2 SE 0862TXM	8.6	23	10	75		
2 SE 0872TXM	8.7	23	10	75		
2 SE 0882TXM	8.8	23	10	75		
2 SE 0892TXM	8.9	23	10	75		
2 SE 0912TXM	9.1	25	10	75		
2 SE 0922TXM	9.2	25	10	75		
2 SE 0932TXM	9.3	25	10	75		
2 SE 0942TXM	9.4	25	10	75		
2 SE 0952TXM	9.5	25	10	75		
2 SE 0962TXM	9.6	25	10	75		
2 SE 0972TXM	9.7	25	10	75		
2 SE 0982TXM	9.8	25	10	75		
2 SE 0992TXM	9.9	25	10	75		

編號
Air-6302



轉速/Speed	65,000 rpm
尺寸/Dimension(mm)	Max ϕ 22x140L
重量/Weight	98g
筒夾/Collet Chuck	ϕ 3.0mm、 ϕ 1/8"、 ϕ 2.34" mm

西德軸承/日本葉片/不鏽鋼主軸

編號
Air-6345



轉速/Speed	23,500 rpm
尺寸/Dimension(mm)	Max ϕ 16.5x136L
重量/Weight	200g
筒夾/Collet Chuck	M7 screw shaft

編號
TL-A30
渦輪式



往復行程/Stroke	0.3mm
往復頻率/Frequency	30,000 strokes/min
空氣消耗量/Air Consumption	0.08m ³ /min
輸出壓力/Pressure Recommended	90 psi
尺寸/Dimension(mm)	Max. ϕ 28x185L
重量/Weight	220g



編號
TL-A70
渦輪式



往復行程/Stroke	0.7mm
往復頻率/Frequency	30,000 strokes/min
空氣消耗量/Air Consumption	0.08m ³ /min
輸出壓力/Pressure Recommended	90 psi
尺寸/Dimension(mm)	Max. ϕ 28x205L
重量/Weight	220g

② MSB2 二刃鎢鋼球刀

MSB2 (Ball Nose), 2 Flutes




單位: mm (Unit: mm)

產品編號 Model No.	球頭半徑 R Radius	刃徑 D Diameter	刃長 I Flute Length	柄徑 d Shank Diameter	全長 L Overall Length	價格 Price	備註
2 MSB 0102TXM	0.5R	1	2	4	50		
2 SB 0102TXM	0.5R	1	2	6	50		
2 MSB 0152TXM	0.75R	1.5	3	4	50		
2 SB 0152TXM	0.75R	1.5	3	6	50		
2 MSB 0202TXM	1R	2	4	4	50		
2 SB 0202TXM	1R	2	4	6	50		
2 MSB 0252TXM	1.25R	2.5	5	4	50		
2 SB 0252TXM	1.25R	2.5	5	6	50		
2 SSB 0302TXM	1.5R	3	6	3	50		
2 MSB 0302TXM	1.5R	3	6	4	50		
2 SB 0302TXM	1.5R	3	6	6	50		
2 MSB 0352TXM	1.75R	3.5	7	4	50		
2 MSB 0402TXM	2R	4	8	4	50		
2 SB 0402TXM	2R	4	8	6	50		
2 SB 0452TXM	2.25R	4.5	9	6	50		
2 SB 0502TXM	2.5R	5	10	6	50		
2 SB 0602TXM	3R	6	12	6	50		
2 SB 0702TXM	3.5R	7	14	8	60		
2 SB 0802TXM	4R	8	16	8	60		
2 SB 0902TXM	4.5R	9	18	10	75		
2 SB 1002TXM	5R	10	20	10	75		
2 SB 1102TXM	5.5R	11	22	12	75		
2 SB 1202TXM	6R	12	24	12	75		
2 SB 1402TXM	7R	14	28	16	100		
2 SB 1602TXM	8R	16	32	16	100		
2 SB 2002TXM	10R	20	40	20	100		

備註: 其他規格, 請來電洽詢。 For other specifications, please call to inquire

2 SLB2 / MLB2 / LLB2 二刃長柄鎢鋼球刀

SLB2/MLB2/LLB2 (Ball Nose, Long Shank), 2 Flutes



產品編號 Model No.	球頭半徑 R Radius	刃徑 D Diameter	刃長 l Flute Length	柄徑 d Shank Diameter	全長 L Overall Length	價格 Price	備註
2 SLB 0102TXM	0.5R	1	2	4	75		
2 SLB 0102TXMD6	0.5R	1	2	6	75		
2 MLB 0102TXM	0.5R	1	2	4	100		
2 MLB 0102TXMD6	0.5R	1	2	6	100		
2 SLB 0152TXM	0.75R	1.5	3	4	75		
2 SLB 0152TXMD6	0.75R	1.5	3	6	75		
2 MLB 0152TXM	0.75R	1.5	3	4	100		
2 MLB 0152TXMD6	0.75R	1.5	3	6	100		
2 SLB 0202TXM	1R	2	4	4	75		
2 SLB 0202TXMD6	1R	2	4	6	75		
2 MLB 0202TXM	1R	2	4	4	100		
2 MLB 0202TXMD6	1R	2	4	6	100		
2 SLB 0252TXM	1.25R	2.5	5	4	75		
2 SLB 0252TXMD6	1.25R	2.5	5	6	75		
2 MLB 0252TXM	1.25R	2.5	5	4	100		
2 MLB 0252TXMD6	1.25R	2.5	5	6	100		
2 SLB 0302TXMD3	1.5R	3	6	3	75		
2 SLB 0302TXM	1.5R	3	6	4	75		
2 SLB 0302TXMD6	1.5R	3	6	6	75		
2 MLB 0302TXMD3	1.5R	3	6	3	100		
2 MLB 0302TXM	1.5R	3	6	4	100		
2 MLB 0302TXMD6	1.5R	3	6	6	100		
2 SLB 0402TXM	2R	4	8	4	75		
2 SLB 0402TXMD6	2R	4	8	6	75		
2 MLB 0402TXM	2R	4	8	4	100		
2 MLB 0402TXMD6	2R	4	8	6	100		

產品編號 Model No.	球頭半徑 R Radius	刃徑 D Diameter	刃長 l Flute Length	柄徑 d Shank Diameter	全長 L Overall Length	價格 Price	備註
2 SLB 0502TXM	2.5R	5	10	6	75		
2 MLB 0502TXM	2.5R	5	10	6	100		
2 SLB 0602TXM	3R	6	12	6	75		
2 MLB 0602TXM	3R	6	12	6	100		
2 SLB 0802TXM	4R	8	16	8	75		
2 MLB 0802TXM	4R	8	16	8	100		
2 LLB 0802TXM	4R	8	16	8	150		
2 MLB 1002TXM	5R	10	20	10	100		
2 LLB 1002TXM	5R	10	20	10	150		
2 MLB 1202TXM	6R	12	24	12	100		
2 LLB 1202TXM	6R	12	24	12	150		
2 MLB 1602TXM	8R	16	32	16	150		
2 LLB 1602TXM	8R	16	32	16	200		
2 MLB 2002TXM	10R	20	40	20	150		
2 LLB 2002TXM	10R	20	40	20	200		

備註：其他規格，請來電洽詢。 For other specifications, please call to inquire

適用材質 Work Material :

★最適合 Excellent ●適合 Better ▲佳 Good

碳素鋼 Carbon steels	合金鋼 Alloy steels	預硬鋼材 Pre-hardened steels	高硬度鋼 High-hardened				不銹鋼 Stainless steels	鈦合金 Titanium alloys	鎳基合金 Nickel Based alloys	銅合金 Copper alloys	鋁合金 Aluminum alloys
		~HRC45	~HRC50	~HRC55	~HRC60	~HRC65					
★	★	●	▲				●			●	

2 RTA 四刃鎢鋼R角銑刀

RTA (Corner Radius), 4 Flutes



單位 : mm (Unit : mm)

產品編號 Model No.	刃徑 D Diameter	R角 R Corner Radius	刃長 l Flute Length	柄徑 d Shank Diameter	全長 L Overall Length	價格 Price	備註
2 RTA 010024TXM	1 × 0.2R		2	4	50		
2 RTA 015024TXM	1.5 × 0.2R		3	4	50		
2 RTA 015054TXM	1.5 × 0.5R		3	4	50		
2 RTA 020024TXM	2 × 0.2R		4	4	50		
2 RTA 020054TXM	2 × 0.5R		4	4	50		
2 RTA 025024TXM	2.5 × 0.2R		5	4	50		
2 RTA 025054TXM	2.5 × 0.5R		5	4	50		
2 RTA 030024TXMD3	3 × 0.2R		6	3	50		
2 RTA 030024TXM	3 × 0.2R		6	4	50		
2 RTA 030024TXMD6	3 × 0.2R		6	6	50		
2 RTA 030054TXMD3	3 × 0.5R		6	3	50		
2 RTA 030054TXM	3 × 0.5R		6	4	50		
2 RTA 030054TXMD6	3 × 0.5R		6	6	50		
2 RTA 030104TXMD3	3 × 1R		6	3	50		
2 RTA 030104TXM	3 × 1R		6	4	50		
2 RTA 030104TXMD6	3 × 1R		6	6	50		
2 RTA 040024TXM	4 × 0.2R		8	4	50		
2 RTA 040024TXMD6	4 × 0.2R		8	6	50		
2 RTA 040054TXM	4 × 0.5R		8	4	50		
2 RTA 040054TXMD6	4 × 0.5R		8	6	50		
2 RTA 040104TXM	4 × 1R		8	4	50		
2 RTA 040104TXMD6	4 × 1R		8	6	50		
2 RTA 050054TXM	5 × 0.5R		10	6	50		
2 RTA 050104TXM	5 × 1R		10	6	50		
2 RTA 060024TXM	6 × 0.2R		12	6	50		
2 RTA 060054TXM	6 × 0.5R		12	6	50		
2 RTA 060104TXM	6 × 1R		12	6	50		
2 RTA 060154TXM	6 × 1.5R		12	6	50		

單位 : mm (Unit : mm)

產品編號 Model No.	刃徑 D Diameter	R角 R Corner Radius	刃長 l Flute Length	柄徑 d Shank Diameter	全長 L Overall Length	價格 Price	備註
2 RTA 080024TXM	8 × 0.2R		16	8	60		
2 RTA 080054TXM	8 × 0.5R		16	8	60		
2 RTA 080104TXM	8 × 1R		16	8	60		
2 RTA 080204TXM	8 × 2R		16	8	60		
2 RTA 100054TXM	10 × 0.5R		20	10	75		
2 RTA 100104TXM	10 × 1R		20	10	75		
2 RTA 100204TXM	10 × 2R		20	10	75		
2 RTA 120054TXM	12 × 0.5R		24	12	75		
2 RTA 120104TXM	12 × 1R		24	12	75		
2 RTA 120204TXM	12 × 2R		24	12	75		
2 RTA 120304TXM	12 × 3R		24	12	75		

備註 : 其他規格, 請來電洽詢。 For other specifications, please call to inquire

適用材質 Work Material :

★最適合 Excellent ●適合 Better ▲佳 Good

碳素鋼 Carbon steels	合金鋼 Alloy steels	預硬鋼材 Pre-hardened steels	高硬度鋼 High-hardened					不銹鋼 Stainless steels	鈦合金 Titanium alloys	鎳基合金 Nickel Based alloys	銅合金 Copper alloys	鋁合金 Aluminum alloys
		~HRC45	~HRC50	~HRC55	~HRC60	~HRC65						
★	★	●	▲				●			●		

2 SLR4 / MLR4 四刃長柄鎢鋼R角銑刀

SLR4/MLR4 (Corner Radius, Long Shank), 4 Flutes



單位：mm (Unit : mm)

產品編號 Model No.	刃徑 × R角 Diameter × Corner Radius	刃長 Flute Length	柄徑 Shank Diameter	全長 Overall Length	價格 Price	備註
2 SLR 010024TXM	1 × 0.2R	2	4	75		
2 SLR 010024TXMD6	1 × 0.2R	2	6	75		
2 MLR 010024TXM	1 × 0.2R	2	4	100		
2 MLR 010024TXMD6	1 × 0.2R	2	6	100		
2 SLR 015024TXM	1.5 × 0.2R	3	4	75		
2 SLR 015024TXMD6	1.5 × 0.2R	3	6	75		
2 MLR 015024TXM	1.5 × 0.2R	3	4	100		
2 MLR 015024TXMD6	1.5 × 0.2R	3	6	100		
2 SLR 015054TXM	1.5 × 0.5R	3	4	75		
2 SLR 015054TXMD6	1.5 × 0.5R	3	6	75		
2 MLR 015054TXM	1.5 × 0.5R	3	4	100		
2 MLR 015054TXMD6	1.5 × 0.5R	3	6	100		
2 SLR 020024TXM	2 × 0.2R	4	4	75		
2 SLR 020024TXMD6	2 × 0.2R	4	6	75		
2 MLR 020024TXM	2 × 0.2R	4	4	100		
2 MLR 020024TXMD6	2 × 0.2R	4	6	100		
2 SLR 020054TXM	2 × 0.5R	4	4	75		
2 SLR 020054TXMD6	2 × 0.5R	4	6	75		
2 MLR 020054TXM	2 × 0.5R	4	4	100		
2 MLR 020054TXMD6	2 × 0.5R	4	6	100		
2 SLR 030024TXMD3	3 × 0.2R	6	3	75		
2 SLR 030024TXM	3 × 0.2R	6	4	75		
2 SLR 030024TXMD6	3 × 0.2R	6	6	75		
2 MLR 030024TXMD3	3 × 0.2R	6	3	100		
2 MLR 030024TXM	3 × 0.2R	6	4	100		
2 MLR 030024TXMD6	3 × 0.2R	6	6	100		
2 SLR 030054TXMD3	3 × 0.5R	6	3	75		
2 SLR 030054TXM	3 × 0.5R	6	4	75		
2 SLR 030054TXMD6	3 × 0.5R	6	6	75		
2 MLR 030054TXMD3	3 × 0.5R	6	3	100		
2 MLR 030054TXM	3 × 0.5R	6	4	100		
2 MLR 030054TXMD6	3 × 0.5R	6	6	100		
2 SLR 030104TXMD3	3 × 1 R	6	3	75		
2 SLR 030104TXM	3 × 1 R	6	4	75		
2 SLR 030104TXMD6	3 × 1 R	6	6	75		
2 SLR 030104TXMD3	3 × 1 R	6	3	100		
2 SLR 030104TXM	3 × 1 R	6	4	100		
2 SLR 030104TXMD6	3 × 1 R	6	6	100		

單位：mm (Unit : mm)

產品編號 Model No.	刃徑 × R角 Diameter × Corner Radius	刃長 Flute Length	柄徑 Shank Diameter	全長 Overall Length	價格 Price	備註
2 SLR 040024TXM	4 × 0.2R	8	4	75		
2 SLR 040024TXMD6	4 × 0.2R	8	6	75		
2 MLR 040024TXM	4 × 0.2R	8	4	100		
2 MLR 040024TXMD6	4 × 0.2R	8	6	100		
2 SLR 040054TXM	4 × 0.5R	8	4	75		
2 SLR 040054TXMD6	4 × 0.5R	8	6	75		
2 MLR 040054TXM	4 × 0.5R	8	4	100		
2 MLR 040054TXMD6	4 × 0.5R	8	6	100		
2 SLR 040104TXM	4 × 1R	8	4	75		
2 SLR 040104TXMD6	4 × 1R	8	6	75		
2 MLR 040104TXM	4 × 1R	8	4	100		
2 MLR 040104TXMD6	4 × 1R	8	6	100		
2 SLR 060024TXM	6 × 0.2R	12	6	75		
2 MLR 060024TXM	6 × 0.2R	12	6	100		
2 SLR 060054TXM	6 × 0.5R	12	6	75		
2 MLR 060054TXM	6 × 0.5R	12	6	100		
2 SLR 060104TXM	6 × 1R	12	6	75		
2 MLR 060104TXM	6 × 1R	12	6	100		
2 SLR 080024TXM	8 × 0.2R	16	8	75		
2 MLR 080024TXM	8 × 0.2R	16	8	100		
2 SLR 080054TXM	8 × 0.5R	16	8	75		
2 MLR 080054TXM	8 × 0.5R	16	8	100		
2 SLR 080104TXM	8 × 1R	16	8	75		
2 MLR 080104TXM	8 × 1R	16	8	100		
2 SLR 080204TXM	8 × 2R	16	8	75		
2 MLR 080204TXM	8 × 2R	16	8	100		
2 MLR 100054TXM	10 × 0.5R	20	10	100		
2 MLR 100104TXM	10 × 1R	20	10	100		
2 MLR 100204TXM	10 × 2R	20	10	100		
2 MLR 120054TXM	12 × 0.5R	24	12	100		
2 MLR 120104TXM	12 × 1R	24	12	100		
2 MLR 120204TXM	12 × 2R	24	12	100		
2 MLR 120304TXM	12 × 3R	24	12	100		

備註：其他規格，請來電洽詢。 For other specifications, please call to inquire

適用材質 Work Material :

★最適合 Excellent ●適合 Better ▲佳 Good

碳素鋼 Carbon steels	合金鋼 Alloy steels	預硬鋼材 Pre-hardened steels		高硬度鋼 High-hardened					不銹鋼 Stainless steels	鈦合金 Titanium alloys	鎳基合金 Nickel Based alloys	銅合金 Copper alloys	鋁合金 Aluminum alloys
		~HRC45	~HRC50	~HRC55	~HRC60	~HRC65							
★	★	●	▲						●			●	




5 黃金戰神系列 THE GOLD SERIES

使用極細超微粒 0.3u m/m Co12% 鎢鋼製成，搭配高耐熱及高潤滑性之TX級塗層，特別適用於溼式高速切削、合金鋼、模具鋼~HRC55 之鋼材。

- 所有的產品皆採用高品質的鎢鋼材料
High Quality Tungsten Steels Materials for Production.
- 強力溝型設計，可增加排屑空間
The heavy groove type design will increase the chip removal.
- 塗層-搭配 "耐熱性" 及 "高潤滑" 的塗層，適用於濕式及高速切削
Coating-With "High heat resistant" and "High lubrication" coating, which will suited for wet cutting and high speed processing.
- 廣泛應用於機械加工廠、家電製造產業、模具製造產業、航太零件加工應用、水五金產業、汽機車產業、自行車產業、緊固件產業
Wide used in Machinery processing factory, Domestic Appliances Industry, Mold and Die Manufacturing Industry, Aerospace parts Industry, Plumbing Hardware Industry, Automobile and motorcycle industry, Bicycles industry, Fastener industry.

5 MHD 四刃重切削鎢鋼立銑刀

MHD (Heavy Cutting Operation Type), 4 Flutes



單位：mm (Unit : mm)

產品編號 Model No.	刃徑 D Diameter	刃長 L Flute Length	柄徑 d Shank Diameter	全長 L Overall Length	價格 Price	備註
5 MSE 0104TX	1	3	4	50		
5 SE 0104TX	1	3	6	50		
5 MSE 0154TX	1.5	4	4	50		
5 SE 0154TX	1.5	4	6	50		
5 MSE 0204TX	2	6	4	50		
5 SE 0204TX	2	6	6	50		
5 MSE 0254TX	2.5	8	4	50		
5 SE 0254TX	2.5	8	6	50		
5 MHD 0304TXD3	3	8	3	50		
5 MHD 0304TX	3	8	4	50		
5 MHD 0304TXD6	3	8	6	50		
5 MHD 0354TX	3.5	10	4	50		
5 MHD 0354TXD6	3.5	10	6	50		
5 MHD 0404TX	4	11	4	50		
5 MHD 0404TXD6	4	11	6	50		
5 MHD 0504TX	5	13	6	50		
5 MHD 0604TX	6	16	6	50		
5 MHD 0704TX	7	18	8	60		
5 MHD 0804TX	8	20	8	60		
5 MHD 0904TX	9	25	10	75		
5 MHD 1004TX	10	30	10	75		
5 MHD 1104TX	11	28	12	75		
5 MHD 1204TX	12	30	12	75		
5 MHD 1304TX	13	40	16	100		
5 MHD 1404TX	14	40	16	100		
5 MHD 1504TX	15	45	16	100		
5 MHD 1604TX	16	50	16	100		
5 MHD 1804TX	18	50	20	100		
5 MHD 2004TX	20	50	20	100		

備註：其他規格，請來電洽詢。 For other specifications, please call to inquire


適用材質 Work Material :

★ 最適合 Excellent ● 適合 Better ▲ 佳 Good

碳素鋼 Carbon steels	合金鋼 Alloy steels	預硬鋼材 Pre-hardened steels		高硬度鋼 High-hardened			不銹鋼 Stainless steels	鈦合金 Titanium alloys	鎳基合金 Nickel Based alloys	銅合金 Copper alloys	鋁合金 Aluminum alloys
		~HRC45	~HRC50	~HRC55	~HRC60	~HRC65					
●	★	★	★	●						●	

5 MSE2 小徑鎢鋼立銑刀

MSE2 (Flat End Mill), 2 Flutes Decimal Diameter



單位：mm (Unit : mm)

產品編號 Model No.	刃徑 D Diameter	刃長 l Flute Length	柄徑 d Shank Diameter	全長 L Overall Length	價格 Price	備註
5 MSE 0012OL	0.1	0.2	4	50		
5 MSE 0022OL	0.2	0.4	4	50		
5 MSE 0032OL	0.3	0.6	4	50		
5 MSE 0042OL	0.4	0.8	4	50		
5 MSE 0052OL	0.5	1.0	4	50		
5 MSE 0062OL	0.6	1.2	4	50		
5 MSE 0072OL	0.7	1.4	4	50		
5 MSE 0082OL	0.8	1.6	4	50		
5 MSE 0092OL	0.9	1.8	4	50		

備註：其他規格，請來電洽詢。 For other specifications, please call to inquire

適用材質 Work Material :


★ 最適合 Excellent ● 適合 Better ▲ 佳 Good

碳素鋼 Carbon steels	合金鋼 Alloy steels	預硬鋼材	高硬度鋼					不銹鋼 Stainless steels	鈦合金 Titanium alloys	鎳基合金 Nickel Based alloys	銅合金 Copper alloys	鋁合金 Aluminum alloys
		Pre-hardened steels ~HRC45	~HRC50	~HRC55	~HRC60	~HRC65						
●	★	★	★	●						●	▲	

還在為加工效率煩惱？ 慧德刀具讓你沒煩惱！


HD. 銑刀 2D ERVD1004GRJ
刀桿 SYIC SBT40 PRO-E32-70
加工材料：SUS304

輪廓精修
切削寬度 Ae : 0.1 mm
切削深度 Ap : 20 mm
主軸轉速 S : 3180 rpm/min
進給率 F : 510 mm/min




HD. 銑刀 CHD0604ST
刀桿：SYIC SBT40 PRO-E20-100
加工材料：S50C

開槽銑削
切削寬度 Ae : 6 mm
切削深度 Ap : 6 mm
加工線速度 127米
主軸轉速 S : 6750 rpm/min
進給率 F : 900 mm/min




HD. 銑刀 2AE0603A
6 x 18 x 3T x 50度 x 50L
刀桿 SYIC SBT40 PRO-E20-100
加工材料：T6061

側銑擺線加工
切削寬度 Ae : 1.5 mm
切削深度 Ap : 12 mm
主軸轉速 S : 7960 rpm/min
進給率 F : 3000 mm/min



HD. 銑刀 638 RTA P0600054NB
刀桿：SBT40xPRO-E32-100
加工材質：HSS
硬度：HRC60

曲面粗切挖槽
主軸轉速 S : 4244 rpm/min
切削深度 Ap : 0.2 mm
切削寬度 Ae : 0.5 mm
進給 F : 630 mm/min



不只解決問題，更提供改善方案，
用心服務、客製化價值，您將得到滿意的回饋！

請來電或洽詢業務人員

TEL:886-4-7559458 . 886-4-7567158


Line ID:@hdtools E-mail:hdtools168@gmail.com



模具加工專用

5 SLE4 / MLE4 / LLE4 四刃長柄鎢鋼立銑刀 TX SHANK h5 HRC 55

SLE4/MLE4/LLE4 (Long Shank, Regular Length), 4 Flutes



單位：mm (Unit : mm)

產品編號 Model No.	刃徑 D Diameter	刃長 l Flute Length	柄徑 d Shank Diameter	全長 L Overall Length	價格 Price	備註
5 SLE 0104TXD6	1	2.5	6	75		
5 MLE 0104TXD6	1	2.5	6	100		
5 SLE 0154TXD6	1.5	4	6	75		
5 MLE 0154TXD6	1.5	4	6	100		
5 SLE 0204TXD6	2	6	6	75		
5 MLE 0204TXD6	2	6	6	100		
5 SLE 0254TXD6	2.5	7	6	75		
5 MLE 0254TXD6	2.5	7	6	100		
5 SLE 0304TXD3	3	8	3	75		
5 SLE 0304TX	3	8	4	75		
5 SLE 0304TXD6	3	8	6	75		
5 MLE 0304TXD3	3	8	3	100		
5 MLE 0304TX	3	8	4	100		
5 MLE 0304TXD6	3	8	6	100		
5 SLE 0404TX	4	11	4	75		
5 SLE 0404TXD6	4	11	6	75		
5 MLE 0404TX	4	11	4	100		
5 MLE 0404TXD6	4	11	6	100		
5 SLE 0504TX	5	13	6	75		
5 MLE 0504TX	5	13	6	100		
5 SLE 0604TX	6	16	6	75		
5 MLE 0604TX	6	16	6	100		

單位：mm (Unit : mm)

產品編號 Model No.	刃徑 D Diameter	刃長 l Flute Length	柄徑 d Shank Diameter	全長 L Overall Length	價格 Price	備註
5 MLE 0704TX	7	18	8	100		
5 SLE 0804TX	8	20	8	75		
5 MLE 0804TX	8	20	8	100		
5 LLE 0804TX	8	20	8	150		
5 MLE 0904TX	9	23	10	100		
5 MLE 1004TX	10	30	10	100		
5 LLE 1004TX	10	30	10	150		
5 MLE 1204TX	12	30	12	100		
5 LLE 1204TX	12	30	12	150		
5 MLE 1604TX	16	50	16	150		
5 LLE 1604TX	16	50	16	200		
5 MLE 2004TX	20	50	20	150		
5 LLE 2004TX	20	50	20	200		

備註：其他規格，請來電洽詢。 For other specifications, please call to inquire


適用材質 Work Material :

★ 最適合 Excellent ● 適合 Better ▲ 佳 Good

碳素鋼 Carbon steels	合金鋼 Alloy steels	預硬鋼材 Pre-hardened steels	高硬度鋼 High-hardened					不銹鋼 Stainless steels	鈦合金 Titanium alloys	鎳基合金 Nickel Based alloys	銅合金 Copper alloys	鋁合金 Aluminum alloys
		~HRC45	~HRC50	~HRC55	~HRC60	~HRC65						
●	★	★	★	●							●	

5 LET4 四刃長刃鎢鋼立銑刀

LET4 (Long Flute Length End Mill), 4 Flutes



單位：mm (Unit : mm)

產品編號 Model No.	刃徑 Diameter D	刃長 Flute Length l	柄徑 Shank Diameter d	全長 Overall Length L	價格 Price	備註
5 LET 0104TX	1	5	4	50		
5 LET 0154TX	1.5	8	4	50		
5 LET 0204TX	2	10	4	50		
5 LET 0254TX	2.5	13	4	50		
5 LET 0304TX	3	15	6	75		
5 LET 0404TX	4	20	6	75		
5 LET 0504TX	5	25	6	75		
5 LET 0604TX	6	30	6	75		
5 LET 0704TX	7	35	8	100		
5 LET 0804TX	8	40	8	100		
5 LET 0904TX	9	45	10	100		
5 LET 1004TX	10	50	10	100		
5 LET 1204TX	12	50	12	100		
5 LET 1604TX	16	80	16	150		
5 LET 2004TX	20	80	20	150		

備註：其他規格，請來電洽詢。 For other specifications, please call to inquire

適用材質 Work Material :

★ 最適合 Excellent ● 適合 Better ▲ 佳 Good

碳素鋼 Carbon steels	合金鋼 Alloy steels	預硬鋼材 Pre-hardened steels	高硬度鋼 High-hardened				不銹鋼 Stainless steels	鈦合金 Titanium alloys	鎳基合金 Nickel Based alloys	銅合金 Copper alloys	鋁合金 Aluminum alloys
		~HRC45	~HRC50	~HRC55	~HRC60	~HRC65					
●	★	★	★	●					●		

鋁用銑刀

垂直度極佳 大切深、高進給
加工面精細 銅鋁合金專用



高效率 加工用刀具

High Performance Cutting Tools



成型刀訂製

1. 提供圖面、樣品或手稿皆可訂製專屬刀具
2. 依客戶加工材質，客製最適合的塗層


We can customize exclusive Cutter based on provided drawings, samples, or sketches.

We'll apply the most suitable coating based on the material you provide for processing.



5 MSB2 / SB2 二刃鎢鋼球刀

MSB2 (Ball Nose), 2 Flutes



單位：mm (Unit : mm)

產品編號 Model No.	球頭半徑 R Radius	刃徑 D Diameter	刃長 l Flute Length	柄徑 d Shank Diameter	全長 L Overall Length	價格 Price	備註
5 MSB 0102TX	0.5R	1	2	4	50		
5 SB 0102TX	0.5R	1	2	6	50		
5 MSB 0152TX	0.75R	1.5	3	4	50		
5 SB 0152TX	0.75R	1.5	3	6	50		
5 MSB 0202TX	1R	2	4	4	50		
5 SB 0202TX	1R	2	4	6	50		
5 MSB 0252TX	1.25R	2.5	5	4	50		
5 SB 0252TX	1.25R	2.5	5	6	50		
5 SSB 0302TX	1.5R	3	6	3	50		
5 MSB 0302TX	1.5R	3	6	4	50		
5 SB 0302TX	1.5R	3	6	6	50		
5 MSB 0352TX	1.75R	3.5	7	4	50		
5 MSB 0402TX	2R	4	8	4	50		
5 SB 0402TX	2R	4	8	6	50		
5 SB 0452TX	2.25R	4.5	9	6	50		
5 SB 0502TX	2.5R	5	10	6	50		
5 SB 0602TX	3R	6	12	6	50		
5 SB 0702TX	3.5R	7	14	8	60		
5 SB 0802TX	4R	8	16	8	60		
5 SB 0902TX	4.5R	9	18	10	75		
5 SB 1002TX	5R	10	20	10	75		
5 SB 1102TX	5.5R	11	22	12	75		
5 SB 1202TX	6R	12	24	12	75		
5 SB 1602TX	8R	16	32	16	100		
5 SB 2002TX	10R	20	40	20	100		

備註：其他規格，請來電洽詢。 For other specifications, please call to inquire


適用材質 Work Material :

★ 最適合 Excellent ● 適合 Better ▲ 佳 Good

碳素鋼 Carbon steels	合金鋼 Alloy steels	預硬鋼材 Pre-hardened steels		高硬度鋼 High-hardened					不銹鋼 Stainless steels	鈦合金 Titanium alloys	鎳基合金 Nickel Based alloys	銅合金 Copper alloys	鋁合金 Aluminum alloys
		~HRC45	~HRC50	~HRC55	~HRC60	~HRC65							
●	★	★	★	●								●	

5 MSB 小徑鎢鋼球刀

MSB (Ball Nose), 2 Flutes-Decimal Diameter



單位：mm (Unit : mm)

產品編號 Model No.	球頭半徑 R Radius	刃徑 D Diameter	刃長 l Flute Length	柄徑 d Shank Diameter	全長 L Overall Length	價格 Price	備註
5 MSB 0022OL	0.1R	0.2	0.4	4	50		
5 MSB 0032OL	0.15R	0.3	0.6	4	50		
5 MSB 0042OL	0.2R	0.4	0.8	4	50		
5 MSB 0052OL	0.25R	0.5	1	4	50		
5 MSB 0062OL	0.3R	0.6	1.2	4	50		
5 MSB 0072OL	0.35R	0.7	1.4	4	50		
5 MSB 0082OL	0.4R	0.8	1.6	4	50		
5 MSB 0092OL	0.45R	0.9	1.8	4	50		
5 MSB 0112TX	0.55R	1.1	2.2	4	50		
5 MSB 0122TX	0.6R	1.2	2.4	4	50		
5 MSB 0132TX	0.65R	1.3	2.6	4	50		
5 MSB 0142TX	0.7R	1.4	2.8	4	50		
5 MSB 0162TX	0.8R	1.6	3.2	4	50		
5 MSB 0172TX	0.85R	1.7	3.4	4	50		
5 MSB 0182TX	0.9R	1.8	3.6	4	50		
5 MSB 0192TX	0.95R	1.9	3.8	4	50		
5 MSB 0212TX	1.05R	2.1	4.2	4	50		
5 MSB 0222TX	1.1R	2.2	4.4	4	50		
5 MSB 0232TX	1.15R	2.3	4.6	4	50		
5 MSB 0242TX	1.2R	2.4	4.8	4	50		
5 MSB 0262TX	1.3R	2.6	5.2	4	50		
5 MSB 0272TX	1.35R	2.7	5.4	4	50		
5 MSB 0282TX	1.4R	2.8	5.5	4	50		
5 MSB 0292TX	1.45R	2.9	5.8	4	50		

備註：其他規格，請來電洽詢。 For other specifications, please call to inquire

適用材質 Work Material :

★ 最適合 Excellent ● 適合 Better ▲ 佳 Good

碳素鋼 Carbon steels	合金鋼 Alloy steels	預硬鋼材 Pre-hardened steels		高硬度鋼 High-hardened					不銹鋼 Stainless steels	鈦合金 Titanium alloys	鎳基合金 Nickel Based alloys	銅合金 Copper alloys	鋁合金 Aluminum alloys
		~HRC45	~HRC50	~HRC55	~HRC60	~HRC65							
●	★	★	★	●								●	

5 SLB2 / MLB2 / LLB2 二刃長柄鎢鋼球刀



SLB2/MLB2/LLB2 (Ball Nose, Long Shank), 2 Flutes



單位 : mm (Unit : mm)

產品編號 Model No.	球頭半徑 R Radius	刃徑 D Diameter	刃長 l Flute Length	柄徑 d Shank Diameter	全長 L Overall Length	價格 Price	備註
5 SLB 0102TX	0.5R	1	2	4	75		
5 SLB 0102TXD6	0.5R	1	2	6	75		
5 MLB 0102TX	0.5R	1	2	4	100		
5 MLB 0102TXD6	0.5R	1	2	6	100		
5 SLB 0152TX	0.75R	1.5	3	4	75		
5 SLB 0152TXD6	0.75R	1.5	3	6	75		
5 MLB 0152TX	0.75R	1.5	3	4	100		
5 MLB 0152TXD6	0.75R	1.5	3	6	100		
5 SLB 0202TX	1R	2	4	4	75		
5 SLB 0202TXD6	1R	2	4	6	75		
5 MLB 0202TX	1R	2	4	4	100		
5 MLB 0202TXD6	1R	2	4	6	100		
5 SLB 0252TX	1.25R	2.5	5	4	75		
5 SLB 0252TXD6	1.25R	2.5	5	6	75		
5 MLB 0252TX	1.25R	2.5	5	4	100		
5 MLB 0252TXD6	1.25R	2.5	5	6	100		
5 SLB 0302TXD3	1.5R	3	6	3	75		
5 SLB 0302TX	1.5R	3	6	4	75		
5 SLB 0302TXD6	1.5R	3	6	6	75		
5 MLB 0302TXD3	1.5R	3	6	3	100		
5 MLB 0302TX	1.5R	3	6	4	100		
5 MLB 0302TXD6	1.5R	3	6	6	100		
5 SLB 0402TX	2R	4	8	4	75		
5 SLB 0402TXD6	2R	4	8	6	75		
5 MLB 0402TX	2R	4	8	4	100		
5 MLB 0402TXD6	2R	4	8	6	100		

單位 : mm (Unit : mm)

產品編號 Model No.	球頭半徑 R Radius	刃徑 D Diameter	刃長 l Flute Length	柄徑 d Shank Diameter	全長 L Overall Length	價格 Price	備註
5 SLB 0502TX	2.5R	5	10	6	75		
5 MLB 0502TX	2.5R	5	10	6	100		
5 SLB 0602TX	3R	6	12	6	75		
5 MLB 0602TX	3R	6	12	6	100		
5 SLB 0802TX	4R	8	16	8	75		
5 MLB 0802TX	4R	8	16	8	100		
5 LLB 0802TX	4R	8	16	8	150		
5 MLB 1002TX	5R	10	20	10	100		
5 LLB 1002TX	5R	10	20	10	150		
5 MLB 1202TX	6R	12	24	12	100		
5 LLB 1202TX	6R	12	24	12	150		
5 MLB 1602TX	8R	16	32	16	150		
5 LLB 1602TX	8R	16	32	16	200		
5 MLB 2002TX	10R	20	40	20	150		
5 LLB 2002TX	10R	20	40	20	200		

備註 : 其他規格 , 請來電洽詢。 For other specifications, please call to inquire


適用材質 Work Material :

★ 最適合 Excellent ● 適合 Better ▲ 佳 Good

碳素鋼 Carbon steels	合金鋼 Alloy steels	預硬鋼材	高硬度鋼				不銹鋼 Stainless steels	鈦合金 Titanium alloys	鎳基合金 Nickel Based alloys	銅合金 Copper alloys	鋁合金 Aluminum alloys
		Pre-hardened steels	High-hardened								
		~HRC45	~HRC50	~HRC55	~HRC60	~HRC65					
●	★	★	★	●						●	

5 RTA 四刃鎢鋼R角銑刀

RTA (Corner Radius), 4 Flutes



單位：mm (Unit : mm)

產品編號 Model No.	刃徑 × R角 Diameter × Corner Radius	刃長 Flute Length	柄徑 Shank Diameter	全長 Overall Length	價格 Price	備註
5 RTA 010014TX	1 × 0.1R	2	4	50		
5 RTA 010024TX	1 × 0.2R	2	4	50		
5 RTA 015024TX	1.5 × 0.2R	3	4	50		
5 RTA 015054TX	1.5 × 0.5R	3	4	50		
5 RTA 020014TX	2 × 0.1R	4	4	50		
5 RTA 020024TX	2 × 0.2R	4	4	50		
5 RTA 020054TX	2 × 0.5R	4	4	50		
5 RTA 025024TX	2.5 × 0.2R	5	4	50		
5 RTA 025054TX	2.5 × 0.5R	5	4	50		
5 RTA 030014TX	3 × 0.1R	6	4	50		
5 RTA 030024TXD3	3 × 0.2R	6	3	50		
5 RTA 030024TX	3 × 0.2R	6	4	50		
5 RTA 030024TXD6	3 × 0.2R	6	6	50		
5 RTA 030054TXD3	3 × 0.5R	6	3	50		
5 RTA 030054TX	3 × 0.5R	6	4	50		
5 RTA 030054TXD6	3 × 0.5R	6	6	50		
5 RTA 030104TXD3	3 × 1R	6	3	50		
5 RTA 030104TX	3 × 1R	6	4	50		
5 RTA 030104TXD6	3 × 1R	6	6	50		
5 RTA 040014TX	4 × 0.1R	8	4	50		
5 RTA 040024TX	4 × 0.2R	8	4	50		
5 RTA 040024TXD6	4 × 0.2R	8	6	50		
5 RTA 040054TX	4 × 0.5R	8	4	50		
5 RTA 040054TXD6	4 × 0.5R	8	6	50		
5 RTA 040104TX	4 × 1R	8	4	50		
5 RTA 040104TXD6	4 × 1R	8	6	50		
5 RTA 050054TX	5 × 0.5R	10	6	50		
5 RTA 050104TX	5 × 1R	10	6	50		
5 RTA 060024TX	6 × 0.2R	12	6	50		
5 RTA 060054TX	6 × 0.5R	12	6	50		
5 RTA 060104TX	6 × 1R	12	6	50		
5 RTA 060154TX	6 × 1.5R	12	6	50		

單位：mm (Unit : mm)

產品編號 Model No.	刃徑 × R角 Diameter × Corner Radius	刃長 Flute Length	柄徑 Shank Diameter	全長 Overall Length	價格 Price	備註
5 RTA 080024TX	8 × 0.2R	16	8	60		
5 RTA 080054TX	8 × 0.5R	16	8	60		
5 RTA 080104TX	8 × 1R	16	8	60		
5 RTA 080204TX	8 × 2R	16	8	60		
5 RTA 100054TX	10 × 0.5R	20	10	75		
5 RTA 100104TX	10 × 1R	20	10	75		
5 RTA 100204TX	10 × 2R	20	10	75		
5 RTA 120054TX	12 × 0.5R	24	12	75		
5 RTA 120104TX	12 × 1R	24	12	75		
5 RTA 120204TX	12 × 2R	24	12	75		
5 RTA 120304TX	12 × 3R	24	12	75		

備註：其他規格，請來電洽詢。 For other specifications, please call to inquire

適用材質 Work Material :

★最適合 Excellent ●適合 Better ▲佳 Good

碳素鋼 Carbon steels	合金鋼 Alloy steels	預硬鋼材 Pre-hardened steels		高硬度鋼 High-hardened			不銹鋼 Stainless steels	鈦合金 Titanium alloys	鎳基合金 Nickel Based alloys	銅合金 Copper alloys	鋁合金 Aluminum alloys
		~HRC45	~HRC50	~HRC55	~HRC60	~HRC65					
●	★	★	★	●						●	

5 SLR4 / MLR4 四刃長柄鎢鋼R角銑刀



SLR4/MLR4 (Corner Radius, Long Shank), 4 Flutes



單位：mm (Unit : mm)

產品編號 Model No.	刃徑 D Diameter	R角 R Corner Radius	刃長 l Flute Length	柄徑 d Shank Diameter	全長 L Overall Length	價格 Price	備註
5 SLR 010024TX	1 × 0.2R		2	4	75		
5 SLR 010024TXD6	1 × 0.2R		2	6	75		
5 MLR 010024TX	1 × 0.2R		2	4	100		
5 MLR 010024TXD6	1 × 0.2R		2	6	100		
5 SLR 015024TX	1.5 × 0.2R		3	4	75		
5 SLR 015024TXD6	1.5 × 0.2R		3	6	75		
5 MLR 015024TX	1.5 × 0.2R		3	4	100		
5 MLR 015024TXD6	1.5 × 0.2R		3	6	100		
5 SLR 015054TX	1.5 × 0.5R		3	4	75		
5 SLR 015054TXD6	1.5 × 0.5R		3	6	75		
5 MLR 015054TX	1.5 × 0.5R		3	4	100		
5 MLR 015054TXD6	1.5 × 0.5R		3	6	100		
5 SLR 020024TX	2 × 0.2R		4	4	75		
5 SLR 020024TXD6	2 × 0.2R		4	6	75		
5 MLR 020024TX	2 × 0.2R		4	4	100		
5 MLR 020024TXD6	2 × 0.2R		4	6	100		
5 SLR 020054TX	2 × 0.5R		4	4	75		
5 SLR 020054TXD6	2 × 0.5R		4	6	75		
5 MLR 020054TX	2 × 0.5R		4	4	100		
5 MLR 020054TXD6	2 × 0.5R		4	6	100		
5 SLR 030024TXD3	3 × 0.2R		6	3	75		
5 SLR 030024TX	3 × 0.2R		6	4	75		
5 SLR 030024TXD6	3 × 0.2R		6	6	75		
5 MLR 030024TXD3	3 × 0.2R		6	3	100		
5 MLR 030024TX	3 × 0.2R		6	4	100		
5 MLR 030024TXD6	3 × 0.2R		6	6	100		
5 SLR 030054TXD3	3 × 0.5R		6	3	75		
5 SLR 030054TX	3 × 0.5R		6	4	75		
5 SLR 030054TXD6	3 × 0.5R		6	6	75		
5 MLR 030054TXD3	3 × 0.5R		6	3	100		
5 MLR 030054TX	3 × 0.5R		6	4	100		
5 MLR 030054TXD6	3 × 0.5R		6	6	100		
5 SLR 030104TXD3	3 × 1R		6	3	75		
5 SLR 030104TX	3 × 1R		6	4	75		
5 SLR 030104TXD6	3 × 1R		6	6	75		
5 SLR 030104TXD3	3 × 1R		6	3	100		
5 SLR 030104TX	3 × 1R		6	4	100		
5 SLR 030104TXD6	3 × 1R		6	6	100		

單位：mm (Unit : mm)

產品編號 Model No.	刃徑 D × R角 R Diameter × Corner Radius	刃長 l Flute Length	柄徑 d Shank Diameter	全長 L Overall Length	價格 Price	備註
5 SLR 040024TX	4 × 0.2R	8	4	75		
5 SLR 040024TXD6	4 × 0.2R	8	6	75		
5 MLR 040024TX	4 × 0.2R	8	4	100		
5 MLR 040024TXD6	4 × 0.2R	8	6	100		
5 SLR 040054TX	4 × 0.5R	8	4	75		
5 SLR 040054TXD6	4 × 0.5R	8	6	75		
5 MLR 040054TX	4 × 0.5R	8	4	100		
5 MLR 040054TXD6	4 × 0.5R	8	6	100		
5 SLR 040104TX	4 × 1R	8	4	75		
5 SLR 040104TXD6	4 × 1R	8	6	75		
5 MLR 040104TX	4 × 1R	8	4	100		
5 MLR 040104TXD6	4 × 1R	8	6	100		
5 SLR 060024TX	6 × 0.2R	12	6	75		
5 MLR 060024TX	6 × 0.2R	12	6	100		
5 SLR 060054TX	6 × 0.5R	12	6	75		
5 MLR 060054TX	6 × 0.5R	12	6	100		
5 SLR 060104TX	6 × 1R	12	6	75		
5 MLR 060104TX	6 × 1R	12	6	100		
5 SLR 080024TX	8 × 0.2R	16	8	75		
5 MLR 080024TX	8 × 0.2R	16	8	100		
5 SLR 080054TX	8 × 0.5R	16	8	75		
5 MLR 080054TX	8 × 0.5R	16	8	100		
5 SLR 080104TX	8 × 1R	16	8	75		
5 MLR 080104TX	8 × 1R	16	8	100		
5 SLR 080204TX	8 × 2R	16	8	75		
5 MLR 080204TX	8 × 2R	16	8	100		
5 MLR 100054TX	10 × 0.5R	20	10	100		
5 MLR 100104TX	10 × 1R	20	10	100		
5 MLR 100204TX	10 × 2R	20	10	100		
5 MLR 120054TX	12 × 0.5R	24	12	100		
5 MLR 120104TX	12 × 1R	24	12	100		
5 MLR 120204TX	12 × 2R	24	12	100		
5 MLR 120304TX	12 × 3R	24	12	100		

備註：其他規格，請來電洽詢。 For other specifications, please call to inquire


適用材質 Work Material :

★ 最適合 Excellent ● 適合 Better ▲ 佳 Good

碳素鋼 Carbon steels	合金鋼 Alloy steels	預硬鋼材 Pre-hardened steels		高硬度鋼 High-hardened			不銹鋼 Stainless steels	鈦合金 Titanium alloys	鎳基合金 Nickel Based alloys	銅合金 Copper alloys	鋁合金 Aluminum alloys
		~HRC45	~HRC50	~HRC55	~HRC60	~HRC65					
●	★	★	★	●						●	

5 LNT 二刃深溝加工用鎢鋼立銑刀

LNT (For Deep Processing, Long Neck), 2 Flutes




單位 : mm (Unit : mm)

產品編號 Model No.	刃徑 Diameter D	刃長 Flute Length l	有效長 Effective Length L1	頸徑 Neck dia dh	柄徑 Shank Diameter d	全長 Overall Length L	價格 Price	備註
5 LNT 020102OL	0.2	0.2	1	0.17	4	50		
5 LNT 020152OL	0.2	0.2	1.5	0.17	4	50		
5 LNT 020202OL	0.2	0.2	2	0.17	4	50		
5 LNT 030152OL	0.3	0.3	1.5	0.26	4	50		
5 LNT 030202OL	0.3	0.3	2	0.26	4	50		
5 LNT 030302OL	0.3	0.3	3	0.26	4	50		
5 LNT 040202OL	0.4	0.4	2	0.35	4	50		
5 LNT 040302OL	0.4	0.4	3	0.35	4	50		
5 LNT 040402OL	0.4	0.4	4	0.35	4	50		
5 LNT 040502OL	0.4	0.4	5	0.35	4	50		
5 LNT 050302OL	0.5	0.5	3	0.45	4	50		
5 LNT 050402OL	0.5	0.5	4	0.45	4	50		
5 LNT 050602OL	0.5	0.5	6	0.45	4	50		
5 LNT 060302OL	0.6	0.6	3	0.55	4	50		
5 LNT 060402OL	0.6	0.6	4	0.55	4	50		
5 LNT 060602OL	0.6	0.6	6	0.55	4	50		
5 LNT 060802OL	0.6	0.6	8	0.55	4	50		
5 LNT 080402OL	0.8	0.8	4	0.75	4	50		
5 LNT 080602OL	0.8	0.8	6	0.75	4	50		
5 LNT 080802OL	0.8	0.8	8	0.75	4	50		
5 LNT 081002OL	0.8	0.8	10	0.75	4	50		
5 LNT 100602TX	1	1	6	0.95	4	50		
5 LNT 100802TX	1	1	8	0.95	4	50		
5 LNT 101002TX	1	1	10	0.95	4	50		
5 LNT 101202TX	1	1	12	0.95	4	50		
5 LNT 120602TX	1.2	1.2	6	1.15	4	50		
5 LNT 120802TX	1.2	1.2	8	1.15	4	50		
5 LNT 121002TX	1.2	1.2	10	1.15	4	50		
5 LNT 121202TX	1.2	1.2	12	1.15	4	50		
5 LNT 121602TX	1.2	1.2	16	1.15	4	50		
5 LNT 150802TX	1.5	1.5	8	1.45	4	50		
5 LNT 151002TX	1.5	1.5	10	1.45	4	50		
5 LNT 151202TX	1.5	1.5	12	1.45	4	50		
5 LNT 151602TX	1.5	1.5	16	1.45	4	50		
5 LNT 201002TX	2	2	10	1.95	4	50		
5 LNT 201202TX	2	2	12	1.95	4	50		
5 LNT 201602TX	2	2	16	1.95	4	50		
5 LNT 202002TX	2	2	20	1.95	4	50		

5 LNB 二刃深溝加工用鎢鋼球刀

LNB (Ball Nose For Deep Processing, Long Neck), 2 Flutes




單位 : mm (Unit : mm)

產品編號 Model No.	球頭半徑 Radius R	刃徑 Diameter D	刃長 Flute Length l	有效長 Effective Length L1	頸徑 Neck dia dh	柄徑 Shank Diameter d	全長 Overall Length L	價格 Price	備註
5 LNB 020102OL	0.1R	0.2	0.2	1	0.17	4	50		
5 LNB 020152OL	0.1R	0.2	0.2	1.5	0.17	4	50		
5 LNB 020202OL	0.1R	0.2	0.2	2	0.17	4	50		
5 LNB 030152OL	0.15R	0.3	0.3	1.5	0.26	4	50		
5 LNB 030202OL	0.15R	0.3	0.3	2	0.26	4	50		
5 LNB 030302OL	0.15R	0.3	0.3	3	0.26	4	50		
5 LNB 040202OL	0.2R	0.4	0.4	2	0.35	4	50		
5 LNB 040302OL	0.2R	0.4	0.4	3	0.35	4	50		
5 LNB 040402OL	0.2R	0.4	0.4	4	0.35	4	50		
5 LNB 040502OL	0.2R	0.4	0.4	5	0.35	4	50		
5 LNB 050302OL	0.25R	0.5	0.5	3	0.45	4	50		
5 LNB 050402OL	0.25R	0.5	0.5	4	0.45	4	50		
5 LNB 050602OL	0.25R	0.5	0.5	6	0.45	4	50		
5 LNB 060302OL	0.3R	0.6	0.6	3	0.55	4	50		
5 LNB 060402OL	0.3R	0.6	0.6	4	0.55	4	50		
5 LNB 060602OL	0.3R	0.6	0.6	6	0.55	4	50		
5 LNB 060802OL	0.3R	0.6	0.6	8	0.55	4	50		
5 LNB 080402OL	0.4R	0.8	0.8	4	0.75	4	50		
5 LNB 080602OL	0.4R	0.8	0.8	6	0.75	4	50		
5 LNB 080802OL	0.4R	0.8	0.8	8	0.75	4	50		
5 LNB 081002OL	0.4R	0.8	0.8	10	0.75	4	50		
5 LNB 100602TX	0.5R	1	1	6	0.95	4	50		
5 LNB 100802TX	0.5R	1	1	8	0.95	4	50		
5 LNB 101002TX	0.5R	1	1	10	0.95	4	50		
5 LNB 101202TX	0.5R	1	1	12	0.95	4	50		
5 LNB 150602TX	0.75R	1.5	1.5	6	1.45	4	50		
5 LNB 150802TX	0.75R	1.5	1.5	8	1.45	4	50		
5 LNB 151002TX	0.75R	1.5	1.5	10	1.45	4	50		
5 LNB 151202TX	0.75R	1.5	1.5	12	1.45	4	50		
5 LNB 151602TX	0.75R	1.5	1.5	16	1.45	4	50		
5 LNB 200802TX	1R	2	2	8	1.95	4	50		
5 LNB 201002TX	1R	2	2	10	1.95	4	50		
5 LNB 201202TX	1R	2	2	12	1.95	4	50		
5 LNB 201402TX	1R	2	2	14	1.95	4	50		
5 LNB 201602TX	1R	2	2	16	1.95	4	50		
5 LNB 202002TX	1R	2	2	20	1.95	4	50		

5 LNR 四刃深溝加工用鎢鋼R角銑刀

LNR (Corner Radius For Deep Processing, Long Neck), 4 Flutes



單位：mm (Unit : mm)

產品編號 Model No.	刃徑 D Diameter	R角 R Corner Radius	刃長 L Flute Length	有效長 L1 Effective Length	頸徑 dh Neck dia	柄徑 d Shank Diameter	全長 L Overall Length	價格 Price	備註
5 LNR 0601032TX	0.6 x 0.1R	0.6	3	0.55	4	50			
5 LNR 0601042TX	0.6 x 0.1R	0.6	4	0.55	4	50			
5 LNR 0601052TX	0.6 x 0.1R	0.6	5	0.55	4	50			
5 LNR 0801042TX	0.8 x 0.1R	0.8	4	0.75	4	50			
5 LNR 0801062TX	0.8 x 0.1R	0.8	6	0.75	4	50			
5 LNR 1002044TX	1 x 0.2R	1	4	0.95	4	50			
5 LNR 1002064TX	1 x 0.2R	1	6	0.95	4	50			
5 LNR 1002084TX	1 x 0.2R	1	8	0.95	4	50			
5 LNR 1002104TX	1 x 0.2R	1	10	0.95	4	50			
5 LNR 1502064TX	1.5 x 0.2R	1.5	6	1.45	4	50			
5 LNR 1502084TX	1.5 x 0.2R	1.5	8	1.45	4	50			
5 LNR 1502104TX	1.5 x 0.2R	1.5	10	1.45	4	50			
5 LNR 1502124TX	1.5 x 0.2R	1.5	12	1.45	4	50			
5 LNR 1505064TX	1.5 x 0.5R	1.5	6	1.45	4	50			
5 LNR 1505084TX	1.5 x 0.5R	1.5	8	1.45	4	50			
5 LNR 1505104TX	1.5 x 0.5R	1.5	10	1.45	4	50			
5 LNR 1505124TX	1.5 x 0.5R	1.5	12	1.45	4	50			
5 LNR 2002084TX	2 x 0.2R	2	8	1.95	4	50			
5 LNR 2002104TX	2 x 0.2R	2	10	1.95	4	50			
5 LNR 2002124TX	2 x 0.2R	2	12	1.95	4	50			
5 LNR 2002164TX	2 x 0.2R	2	16	1.95	4	50			
5 LNR 2005084TX	2 x 0.5R	2	8	1.95	4	50			
5 LNR 2005104TX	2 x 0.5R	2	10	1.95	4	50			
5 LNR 2005124TX	2 x 0.5R	2	12	1.95	4	50			
5 LNR 2005164TX	2 x 0.5R	2	16	1.95	4	50			

備註：其他規格，請來電洽詢。 For other specifications, please call to inquire

適用材質 Work Material :

★最適合 Excellent ●適合 Better ▲佳 Good

碳素鋼 Carbon steels	合金鋼 Alloy steels	預硬鋼材 Pre-hardened steels		高硬度鋼 High-hardened			不銹鋼 Stainless steels	鈦合金 Titanium alloys	鎳基合金 Nickel Based alloys	銅合金 Copper alloys	鋁合金 Aluminum alloys
		~HRC45	~HRC50	~HRC55	~HRC60	~HRC65					
★	★	★	★	●			●			●	

638 熱處理乾式專用銑刀

Tungsten Carbide End Mills for Heat Treatment and Dry Processing



高耐熱 · 高耐磨
High heat resistance High wear resistance

高 速 · 高硬度
High speed processing High hardness

加工最佳選擇
The best choice for processing



應用材質：合金鋼 Alloy steel · 模具鋼 Die Steel HRC45-HRC68

效率加乘 → 極大的提升工具機生產效率，降低工件加工成本

綠色切削 → 乾式加工，利於保護環境，節約自然資源




【高耐熱】和【高耐磨】塗層，再難的加工，也能輕鬆完成，適用於高速、高硬度的乾式加工



HD. 慧德刀具五金有限公司 / 和東五金商行
Hwe Der Machinery and Hardware Pty Ltd. Ho Dung Hardware Co., Ltd.
TEL: 886-4-7559458 Email: hdttools168@gmail.com

638 SE4 高速・高硬度專用四刃鎢鋼立銑刀    

SE4 (Regular Length, For High Hardness Material), 4 Flutes





單位：mm (Unit : mm)

產品編號 Model No.	刃徑 D Diameter	刃長 l Flute Length	柄徑 d Shank Diameter	全長 L Overall Length	價格 Price	備註
638 MSE 0104NB	1	3	4	50		
638 MSE 0154NB	1.5	4	4	50		
638 MSE 0204NB	2	6	4	50		
638 MSE 0254NB	2.5	7	4	50		
638 MSE 0304NB	3	8	4	50		
638 MSE 0354NB	3.5	10	4	50		
638 MSE 0404NB	4	11	4	50		
638 SE 0404NB	4	11	6	50		
638 SE 0454NB	4.5	11	6	50		
638 SE 0504NB	5	13	6	50		
638 SE 0604NB	6	16	6	50		
638 SE 0704NB	7	18	8	60		
638 SE 0804NB	8	20	8	60		
638 SE 0904NB	9	23	10	75		
638 SE 1004NB	10	30	10	75		
638 SE 1104NB	11	30	12	75		
638 SE 1204NB	12	30	12	75		
638 SE 1404NB	14	40	16	100		
638 SE 1604NB	16	50	16	100		
638 SE 2004NB	20	50	20	100		


備註：其他規格，請來電洽詢。 For other specifications, please call to inquire

適用材質 Work Material : ★最適合 Excellent ●適合 Better ▲佳 Good

碳素鋼 Carbon steels	合金鋼 Alloy steels	預硬鋼材 Pre-hardened steels ~HRC45	高硬度鋼 High-hardened				不銹鋼 Stainless steels	鈦合金 Titanium alloys	鎳基合金 Nickel Based alloys	銅合金 Copper alloys	鋁合金 Aluminum alloys
			~HRC50	~HRC55	~HRC60	~HRC68					
●	●	●	★	★	★	▲					

638 MSE2 高速・高硬度專用小徑鎢鋼立銑刀    

MSE2 (Flat End Mill, For High Hardness Material), 2 Flutes-Micro Decimal Diameter



單位：mm (Unit : mm)

產品編號 Model No.	刃徑 D Diameter	刃長 l Flute Length	柄徑 d Shank Diameter	全長 L Overall Length	價格 Price	備註
638 MSE 0012OS	0.1	0.2	4	50		
638 MSE 0022OS	0.2	0.4	4	50		
638 MSE 0032OS	0.3	0.6	4	50		
638 MSE 0042OS	0.4	0.8	4	50		
638 MSE 0052OS	0.5	1.0	4	50		
638 MSE 0062OS	0.6	1.2	4	50		
638 MSE 0072OS	0.7	1.4	4	50		
638 MSE 0082OS	0.8	1.6	4	50		
638 MSE 0092OS	0.9	1.8	4	50		

備註：其他規格，請來電洽詢。 For other specifications, please call to inquire

適用材質 Work Material : ★最適合 Excellent ●適合 Better ▲佳 Good


碳素鋼 Carbon steels	合金鋼 Alloy steels	預硬鋼材 Pre-hardened steels ~HRC45	高硬度鋼 High-hardened				不銹鋼 Stainless steels	鈦合金 Titanium alloys	鎳基合金 Nickel Based alloys	銅合金 Copper alloys	鋁合金 Aluminum alloys
			~HRC50	~HRC55	~HRC60	~HRC68					
●	●	●	★	★	★	▲					

熱處理乾式專用

熱處理乾式專用

638 MSE2 / SE2 高速・高硬度二刃鎢鋼立銑刀    

MSE2/SE2 (Regular Length, For High Hardness Material), 2 Flutes



產品編號 Model No.	刃徑 D Diameter	刃長 l Flute Length	柄徑 d Shank Diameter	全長 L Overall Length	價格 Price	備註
638 MSE 0102NB	1	3	4	50		
638 MSE 0152NB	1.5	4	4	50		
638 MSE 0202NB	2	6	4	50		
638 MSE 0252NB	2.5	7	4	50		
638 MSE 0302NB	3	8	4	50		
638 SE 0302NB	3	8	6	50		
638 SE 0352NB	3.5	10	6	50		
638 MSE 0402NB	4	11	4	50		
638 SE 0402NB	4	11	6	50		
638 SE 0502NB	5	13	6	50		
638 SE 0602NB	6	16	6	50		

備註：其他規格，請來電洽詢。 For other specifications, please call to inquire


適用材質 Work Material :

★最適合 Excellent ●適合 Better ▲佳 Good

碳素鋼 Carbon steels	合金鋼 Alloy steels	預硬鋼材	高硬度鋼					不銹鋼 Stainless steels	鈦合金 Titanium alloys	鎳基合金 Nickel Based alloys	銅合金 Copper alloys	鋁合金 Aluminum alloys
		~HRC45	~HRC50	~HRC55	~HRC60	~HRC68						
●	●	●	★	★	★	▲						




638 MSP6 高速・高硬度專用六刃鎢鋼立銑刀    

MSP6 (High Hardness Material), 6 Flutes




產品編號 Model No.	刃徑 D Diameter	刃長 l Flute Length	柄徑 d Shank Diameter	全長 L Overall Length	價格 Price	備註
638 MSP 0306NB	3	8	6	50		
638 MSP 0406NB	4	11	6	50		
638 MSP 0506NB	5	13	6	50		
638 MSP 0606NB	6	15	6	50		
638 MSP 0806NB	8	20	8	60		
638 MSP 1006NB	10	30	10	75		
638 MSP 1206NB	12	30	12	75		
638 MSP 1606NB	16	50	16	100		
638 MSP 2006NB	20	50	20	100		

備註：其他規格，請來電洽詢。 For other specifications, please call to inquire

638 MLP6 高速・高硬度專用六刃長刃鎢鋼立銑刀    

MLP6 (High Hardness Material, Long Flute Length), 6 Flutes



產品編號 Model No.	刃徑 D Diameter	刃長 l Flute Length	柄徑 d Shank Diameter	全長 L Overall Length	價格 Price	備註
638 MLP 0606NB	6	30	6	75		
638 MLP 0806NB	8	40	8	100		
638 MLP 1006NB	10	50	10	100		
638 MLP 1206NB	12	50	12	100		
638 MLP 1606NB	16	80	16	150		
638 MLP 2006NB	20	80	20	150		

備註：其他規格，請來電洽詢。 For other specifications, please call to inquire

適用材質 Work Material :

★最適合 Excellent ●適合 Better ▲佳 Good

碳素鋼 Carbon steels	合金鋼 Alloy steels	預硬鋼材	高硬度鋼					不銹鋼 Stainless steels	鈦合金 Titanium alloys	鎳基合金 Nickel Based alloys	銅合金 Copper alloys	鋁合金 Aluminum alloys
		~HRC45	~HRC50	~HRC55	~HRC60	~HRC68						
●	●	●	★	★	★	▲						

638 MSB2 / SB2 二刃鎢鋼球刀

MSB2 (Ball Nose), 2 Flutes




單位：mm (Unit : mm)

產品編號 Model No.	球頭半徑 R Radius	刃徑 D Diameter	刃長 l Flute Length	柄徑 d Shank Diameter	全長 L Overall Length	價格 Price	備註
638 MSB 0102NB	0.5R	1	2	4	50		
638 SB 0102NB	0.5R	1	2	6	50		
638 MSB 0152NB	0.75R	1.5	3	4	50		
638 SB 0152NB	0.75R	1.5	3	6	50		
638 MSB 0202NB	1R	2	4	4	50		
638 SB 0202NB	1R	2	4	6	50		
638 MSB 0252NB	1.25R	2.5	5	4	50		
638 SB 0252NB	1.25R	2.5	5	6	50		
638 SSB 0302NB	1.5R	3	6	3	50		
638 MSB 0302NB	1.5R	3	6	4	50		
638 SB 0302NB	1.5R	3	6	6	50		
638 MSB 0352NB	1.75R	3.5	7	4	50		
638 MSB 0402NB	2R	4	8	4	50		
638 SB 0402NB	2R	4	8	6	50		
638 SB 0452NB	2.25R	4.5	9	6	50		
638 SB 0502NB	2.5R	5	10	6	50		
638 SB 0602NB	3R	6	12	6	50		
638 SB 0702NB	3.5R	7	14	8	60		
638 SB 0802NB	4R	8	16	8	60		
638 SB 0902NB	4.5R	9	18	10	75		
638 SB 1002NB	5R	10	20	10	75		
638 SB 1102NB	5.5R	11	22	12	75		
638 SB 1202NB	6R	12	24	12	75		
638 SB 1402NB	7R	14	28	16	75		
638 SB 1602NB	8R	16	32	16	100		
638 SB 2002NB	10R	20	40	20	100		

638 MSB 高速·高硬度用小徑鎢鋼球刀

MSB (Ball Nose, For High Hardness Material), 2 Flutes-Micro Diameter



單位：mm (Unit : mm)

產品編號 Model No.	球頭半徑 R Radius	刃徑 D Diameter	刃長 l Flute Length	柄徑 d Shank Diameter	全長 L Overall Length	價格 Price	備註
638 MSB 0022OS	0.1R	0.2	0.4	4	50		
638 MSB 0032OS	0.15R	0.3	0.6	4	50		
638 MSB 0042OS	0.2R	0.4	0.8	4	50		
638 MSB 0052OS	0.25R	0.5	1	4	50		
638 MSB 0062OS	0.3R	0.6	1.2	4	50		
638 MSB 0082OS	0.4R	0.8	1.6	4	50		

備註：其他規格，請來電洽詢。 For other specifications, please call to inquire

適用材質 Work Material :

★最適合 Excellent ●適合 Better ▲佳 Good

碳素鋼 Carbon steels	合金鋼 Alloy steels	預硬鋼材 Pre-hardened steels ~HRC45	高硬度鋼 High-hardened				不銹鋼 Stainless steels	鈦合金 Titanium alloys	鎳基合金 Nickel Based alloys	銅合金 Copper alloys	鋁合金 Aluminum alloys
			~HRC50	~HRC55	~HRC60	~HRC68					
●	●	●	★	★	★	▲					

638 SLB2 / MLB2 / LLB2 二刃長柄鎢鋼球刀



SLB2/MLB2/LLB2 (Ball Nose, Long Shank), 2 Flutes



單位 : mm (Unit : mm)

產品編號 Model No.	球頭半徑 R Radius	刃徑 D Diameter	刃長 l Flute Length	柄徑 d Shank Diameter	全長 L Overall Length	價格 Price	備註
638 SLB 0102NB	0.5R	1	2	4	75		
638 SLB 0102NBD6	0.5R	1	2	6	75		
638 MLB 0102NB	0.5R	1	2	4	100		
638 MLB 0102NBD6	0.5R	1	2	6	100		
638 SLB 0152NB	0.75R	1.5	3	4	75		
638 SLB 0152NBD6	0.75R	1.5	3	6	75		
638 MLB 0152NB	0.75R	1.5	3	4	100		
638 MLB 0152NBD6	0.75R	1.5	3	6	100		
638 SLB 0202NB	1R	2	4	4	75		
638 SLB 0202NBD6	1R	2	4	6	75		
638 MLB 0202NB	1R	2	4	4	100		
638 MLB 0202NBD6	1R	2	4	6	100		
638 SLB 0252NB	1.25R	2.5	5	4	75		
638 SLB 0252NBD6	1.25R	2.5	5	6	75		
638 MLB 0252NB	1.25R	2.5	5	4	100		
638 MLB 0252NBD6	1.25R	2.5	5	6	100		
638 SLB 0302NBD3	1.5R	3	6	3	75		
638 SLB 0302NB	1.5R	3	6	4	75		
638 SLB 0302NBD6	1.5R	3	6	6	75		
638 MLB 0302NBD3	1.5R	3	6	3	100		
638 MLB 0302NB	1.5R	3	6	4	100		
638 MLB 0302NBD6	1.5R	3	6	6	100		
638 SLB 0402NB	2R	4	8	4	75		
638 SLB 0402NBD6	2R	4	8	6	75		
638 MLB 0402NB	2R	4	8	4	100		
638 MLB 0402NBD6	2R	4	8	6	100		

單位 : mm (Unit : mm)

產品編號 Model No.	球頭半徑 R Radius	刃徑 D Diameter	刃長 l Flute Length	柄徑 d Shank Diameter	全長 L Overall Length	價格 Price	備註
638 SLB 0502NB	2.5R	5	10	6	75		
638 MLB 0502NB	2.5R	5	10	6	100		
638 SLB 0602NB	3R	6	12	6	75		
638 MLB 0602NB	3R	6	12	6	100		
638 SLB 0802NB	4R	8	16	8	75		
638 MLB 0802NB	4R	8	16	8	100		
638 LLB 0802NB	4R	8	16	8	150		
638 MLB 1002NB	5R	10	20	10	100		
638 LLB 1002NB	5R	10	20	10	150		
638 MLB 1202NB	6R	12	24	12	100		
638 LLB 1202NB	6R	12	24	12	150		
638 MLB 1602NB	8R	16	32	16	150		
638 LLB 1602NB	8R	16	32	16	200		
638 MLB 2002NB	10R	20	40	20	150		
638 LLB 2002NB	10R	20	40	20	200		

備註 : 其他規格, 請來電洽詢。 For other specifications, please call to inquire

適用材質 Work Material :

★ 最適合 Excellent ● 適合 Better ▲ 佳 Good



碳素鋼 Carbon steels	合金鋼 Alloy steels	預硬鋼材	高硬度鋼				不銹鋼 Stainless steels	鈦合金 Titanium alloys	鎳基合金 Nickel Based alloys	銅合金 Copper alloys	鋁合金 Aluminum alloys
		Pre-hardened steels	High-hardened								
		~HRC45	~HRC50	~HRC55	~HRC60	~HRC68					
●	●	●	★	★	★	▲					

熱處理乾式專用

熱處理乾式專用

638 RTA 四刃鎢鋼R角銑刀

RTA (Corner Radius), 4 Flutes



單位：mm (Unit : mm)

產品編號 Model No.	刃徑 D × R角 R Diameter × Corner Radius	刃長 I Flute Length	有效長 DL Effective Length	柄徑 d Shank Diameter	全長 L Overall Length	價格 Price	備註
638 RTA 0040012OS	0.4 × 0.1R	0.4		4	50		
638 RTA 0050012OS	0.5 × 0.1R	0.5		4	50		
638 RTA 0060012OS	0.6 × 0.1R	0.6	2	4	50		
638 RTA 0080014OS	0.8 × 0.1R	0.8	2.5	4	50		
638 RTA 010014NB	1 × 0.1R	1	3	4	50		
638 RTA 010024NB	1 × 0.2R	1	3	4	50		
638 RTA 015014NB	1.5 × 0.1R	1.5	5	4	50		
638 RTA 015024NB	1.5 × 0.2R	1.5	5	4	50		
638 RTA 015054NB	1.5 × 0.5R	1.5	5	4	50		
638 RTA 020014NB	2 × 0.1R	2	6	4	50		
638 RTA 020024NB	2 × 0.2R	2	6	4	50		
638 RTA 020054NB	2 × 0.5R	2	6	4	50		
638 RTA 025024NB	2.5 × 0.2R	2.5	8	4	50		
638 RTA 025054NB	2.5 × 0.5R	2.5	8	4	50		
638 RTA 030014NB	3 × 0.1R	3	10	4	50		
638 RTA 030024NBD3	3 × 0.2R	3	10	3	50		
638 RTA 030024NB	3 × 0.2R	3	10	4	50		
638 RTA 030024NBD6	3 × 0.2R	3	10	6	50		
638 RTA 030054NBD3	3 × 0.5R	3	10	3	50		
638 RTA 030054NB	3 × 0.5R	3	10	4	50		
638 RTA 030054NBD6	3 × 0.5R	3	10	6	50		
638 RTA 030104NBD3	3 × 1R	3	10	3	50		
638 RTA 030104NB	3 × 1R	3	10	4	50		
638 RTA 030104NBD6	3 × 1R	3	10	6	50		
638 RTA 040014NB	4 × 0.1R	4	12	4	50		
638 RTA 040024NB	4 × 0.2R	4	12	4	50		
638 RTA 040024NBD6	4 × 0.2R	4	12	6	50		
638 RTA 040054NB	4 × 0.5R	4	12	4	50		
638 RTA 040054NBD6	4 × 0.5R	4	12	6	50		
638 RTA 040104NB	4 × 1R	4	12	4	50		
638 RTA 040104NBD6	4 × 1R	4	12	6	50		

單位：mm (Unit : mm)

產品編號 Model No.	刃徑 D × R角 R Diameter × Corner Radius	刃長 I Flute Length	有效長 DL Effective Length	柄徑 d Shank Diameter	全長 L Overall Length	價格 Price	備註
638 RTA 050054NB	5 × 0.5R	5	15	6	50		
638 RTA 050104NB	5 × 1R	5	15	6	50		
638 RTA 060024NB	6 × 0.2R	6	18	6	50		
638 RTA 060054NB	6 × 0.5R	6	18	6	50		
638 RTA 060104NB	6 × 1R	6	18	6	50		
638 RTA 060154NB	6 × 1.5R	6	18	6	50		
638 RTA 080024NB	8 × 0.2R	8	24	8	60		
638 RTA 080054NB	8 × 0.5R	8	24	8	60		
638 RTA 080104NB	8 × 1R	8	24	8	60		
638 RTA 080204NB	8 × 2R	8	24	8	60		
638 RTA 100054NB	10 × 0.5R	10	30	10	75		
638 RTA 100104NB	10 × 1R	10	30	10	75		
638 RTA 100204NB	10 × 2R	10	30	10	75		
638 RTA 120054NB	12 × 0.5R	12	36	12	75		
638 RTA 120104NB	12 × 1R	12	36	12	75		
638 RTA 120204NB	12 × 2R	12	36	12	75		
638 RTA 120304NB	12 × 3R	12	36	12	75		

備註：其他規格，請來電洽詢。 For other specifications, please call to inquire

適用材質 Work Material :

★ 最適合 Excellent ● 適合 Better ▲ 佳 Good

碳素鋼 Carbon steels	合金鋼 Alloy steels	預硬鋼材	高硬度鋼				不銹鋼 Stainless steels	鈦合金 Titanium alloys	鎳基合金 Nickel Based alloys	銅合金 Copper alloys	鋁合金 Aluminum alloys
		Pre-hardened steels	High-hardened								
		~HRC45	~HRC50	~HRC55	~HRC60	~HRC68					
●	●	●	★	★	★	▲					


熱處理乾式專用

熱處理乾式專用

638 SLR4 / MLR4 四刃長柄鎢鋼R角銑刀



SLR4/MLR4 (Corner Radius, Long Shank), 4 Flutes



單位：mm (Unit : mm)

產品編號 Model No.	刃徑 D × R角 R Diameter Corner Radius	刃長 I Flute Length	有效長 DL Effective Length	柄徑 d Shank Diameter	全長 L Overall Length	價格 Price	備註
638 SLR 010024NB	1 × 0.2R	1	3	4	75		
638 SLR 010024NBD6	1 × 0.2R	1	3	6	75		
638 MLR 010024NB	1 × 0.2R	1	3	4	100		
638 MLR 010024NBD6	1 × 0.2R	1	3	6	100		
638 SLR 015024NB	1.5 × 0.2R	1.5	5	4	75		
638 SLR 015024NBD6	1.5 × 0.2R	1.5	5	6	75		
638 MLR 015024NB	1.5 × 0.2R	1.5	5	4	100		
638 MLR 015024NBD6	1.5 × 0.2R	1.5	5	6	100		
638 SLR 020024NB	2 × 0.2R	2	6	4	75		
638 SLR 020024NBD6	2 × 0.2R	2	6	6	75		
638 MLR 020024NB	2 × 0.2R	2	6	4	100		
638 MLR 020024NBD6	2 × 0.2R	2	6	6	100		
638 SLR 020054NB	2 × 0.5R	2	6	4	75		
638 SLR 020054NBD6	2 × 0.5R	2	6	6	75		
638 MLR 020054NB	2 × 0.5R	2	6	4	100		
638 MLR 020054NBD6	2 × 0.5R	2	6	6	100		
638 SLR 030024NBD3	3 × 0.2R	3	10	3	75		
638 SLR 030024NB	3 × 0.2R	3	10	4	75		
638 SLR 030024NBD6	3 × 0.2R	3	10	6	75		
638 MLR 030024NBD3	3 × 0.2R	3	10	3	100		
638 MLR 030024NB	3 × 0.2R	3	10	4	100		
638 MLR 030024NBD6	3 × 0.2R	3	10	6	100		
638 SLR 030054NBD3	3 × 0.5R	3	10	3	75		
638 SLR 030054NB	3 × 0.5R	3	10	4	75		
638 SLR 030054NBD6	3 × 0.5R	3	10	6	75		
638 MLR 030054NBD3	3 × 0.5R	3	10	3	100		
638 MLR 030054NB	3 × 0.5R	3	10	4	100		
638 MLR 030054NBD6	3 × 0.5R	3	10	6	100		
638 SLR 040024NB	4 × 0.2R	4	12	4	75		
638 SLR 040024NBD6	4 × 0.2R	4	12	6	75		
638 MLR 040024NB	4 × 0.2R	4	12	4	100		
638 MLR 040024NBD6	4 × 0.2R	4	12	6	100		
638 SLR 040054NB	4 × 0.5R	4	12	4	75		
638 SLR 040054NBD6	4 × 0.5R	4	12	6	75		
638 MLR 040054NB	4 × 0.5R	4	12	4	100		
638 MLR 040054NBD6	4 × 0.5R	4	12	6	100		

單位：mm (Unit : mm)

產品編號 Model No.	刃徑 D × R角 R Diameter Corner Radius	刃長 I Flute Length	有效長 DL Effective Length	柄徑 d Shank Diameter	全長 L Overall Length	價格 Price	備註
638 SLR 040104NB	4 × 1R	4	12	4	75		
638 SLR 040104NBD6	4 × 1R	4	12	6	75		
638 MLR 040104NB	4 × 1R	4	12	4	100		
638 MLR 040104NBD6	4 × 1R	4	12	6	100		
638 SLR 060024NB	6 × 0.2R	6	18	6	75		
638 MLR 060024NB	6 × 0.2R	6	18	6	100		
638 SLR 060054NB	6 × 0.5R	6	18	6	75		
638 MLR 060054NB	6 × 0.5R	6	18	6	100		
638 SLR 060104NB	6 × 1R	6	18	6	75		
638 MLR 060104NB	6 × 1R	6	18	6	100		
638 SLR 080024NB	8 × 0.2R	8	24	6	75		
638 MLR 080024NB	8 × 0.2R	8	24	6	100		
638 SLR 080054NB	8 × 0.5R	8	24	8	75		
638 MLR 080054NB	8 × 0.5R	8	24	8	100		
638 SLR 080104NB	8 × 1R	8	24	8	75		
638 MLR 080104NB	8 × 1R	8	24	8	100		
638 SLR 080204NB	8 × 2R	8	24	8	75		
638 MLR 080204NB	8 × 2R	8	24	8	100		
638 MLR 100054NB	10 × 0.5R	10	30	10	100		
638 MLR 100104NB	10 × 1R	10	30	10	100		
638 MLR 100204NB	10 × 2R	10	30	10	100		
638 MLR 120054NB	12 × 0.5R	12	36	12	100		
638 MLR 120104NB	12 × 1R	12	36	12	100		
638 MLR 120204NB	12 × 2R	12	36	12	100		
638 MLR 120304NB	12 × 3R	12	36	12	100		

備註：其他規格，請來電洽詢。 For other specifications, please call to inquire

適用材質 Work Material :


★ 最適合 Excellent ● 適合 Better ▲ 佳 Good

碳素鋼 Carbon steels	合金鋼 Alloy steels	預硬鋼材 Pre-hardened steels	高硬度鋼 High-hardened				不銹鋼 Stainless steels	鈦合金 Titanium alloys	鎳基合金 Nickel Based alloys	銅合金 Copper alloys	鋁合金 Aluminum alloys
		~HRC45	~HRC50	~HRC55	~HRC60	~HRC68					
●	●	●	★	★	★	▲					

2D HIDO TMAE 車銑複合機專用鋁用立銑刀 

TMAE (Compound Lathe End Mill for Aluminum Alloy), 3 Flutes

單位：mm (Unit : mm)




產品編號 Model No.	刃徑 D Diameter	刃長 I Flute Length	柄徑 d Shank Diameter	全長 L Overall Length	價格 Price	備註
2D TMAE 0103	1	1.5	6	50		
2D TMAE 0153	1.5	2.5	6	50		
2D TMAE 0203	2	3	6	50		
2D TMAE 0253	2.5	4	6	50		
2D TMAE 0303	3	4.5	6	50		
2D TMAE 0403	4	6	6	50		
2D TMAE 0503	5	8	6	50		
2D TMAE 0603	6	9	6	50		
2D TMAE 0803	8	12	8	50		
2D TMAE 1003	10	15	10	50		
2D TMAE 1203	12	18	12	60		
2D TMAE 1603	16	24	12	60		

備註：其他規格，請來電洽詢。 For other specifications, please call to inquire

2D HIDO TMTAE 車銑複合機專用小柄鋁用立銑刀 

TMTAE (Compound Lathe End Mill for Aluminum Alloy-Small handle), 3 Flutes

單位：mm (Unit : mm)



產品編號 Model No.	刃徑 D Diameter	刃長 I Flute Length	柄徑 d Shank Diameter	全長 L Overall Length	價格 Price	備註
2D TMTAE 0803	8	8	6	30		
2D TMTAE 1003	10	10	6	35		
2D TMTAE 1203	12	12	6	40		

備註：其他規格，請來電洽詢。 For other specifications, please call to inquire

適用材質 Work Material :

★ 最適合 Excellent ● 適合 Better ▲ 佳 Good

碳素鋼 Carbon steels	合金鋼 Alloy steels	預硬鋼材 Pre-hardened steels ~HRC45	高硬度鋼 High-hardened				不銹鋼 Stainless steels	鈦合金 Titanium alloys	鎳基合金 Nickel Based alloys	銅合金 Copper alloys	鋁合金 Aluminum alloys
			~HRC50	~HRC55	~HRC60	~HRC65					
									★	★	

2D HIDO TMSB 車銑複合機專用鎢鋼球型銑刀 

TMSB (Compound Lathe Ball Nose End Mill), 2 Flutes

單位：mm (Unit : mm)




產品編號 Model No.	球頭半徑 R Radius	刃徑 D Diameter	刃長 I Flute Length	柄徑 d Shank Diameter	全長 L Overall Length	價格 Price	備註
2D TMSB 0102R7	0.5R	1	1.5	6	50		
2D TMSB 0152R7	0.75R	1.5	2.5	6	50		
2D TMSB 0202R7	1R	2	3	6	50		
2D TMSB 0302R7	1.5R	3	4.5	6	50		
2D TMSB 0402R7	2R	4	6	6	50		
2D TMSB 0502R7	2.5R	5	8	6	50		
2D TMSB 0602R7	3R	6	9	6	50		
2D TMSB 0802R7	4R	8	12	8	50		
2D TMSB 1002R7	5R	10	15	10	50		
2D TMSB 1202R7	6R	12	18	12	60		
2D TMSB 1602R7	8R	16	24	12	60		

備註：其他規格，請來電洽詢。 For other specifications, please call to inquire

2D HIDO TMTSB 車銑複合機專用小柄球銑刀 

TMTSB (Compound Lathe Ball Nose End Mill-Small handle), 2 Flutes

單位：mm (Unit : mm)



產品編號 Model No.	球頭半徑 R Radius	刃徑 D Diameter	刃長 I Flute Length	柄徑 d Shank Diameter	全長 L Overall Length	價格 Price	備註
2D TMTSB 0802R7	4R	8	8	6	30		
2D TMTSB 1002R7	5R	10	10	6	35		
2D TMTSB 1202R7	6R	12	12	6	40		

備註：其他規格，請來電洽詢。 For other specifications, please call to inquire

適用材質 Work Material :

★ 最適合 Excellent ● 適合 Better ▲ 佳 Good

碳素鋼 Carbon steels	合金鋼 Alloy steels	預硬鋼材 Pre-hardened steels ~HRC45	高硬度鋼 High-hardened				不銹鋼 Stainless steels	鈦合金 Titanium alloys	鎳基合金 Nickel Based alloys	銅合金 Copper alloys	鋁合金 Aluminum alloys
			~HRC50	~HRC55	~HRC60	~HRC65					
★	★	★					★	●	●	●	


車銑複合機專用

車銑複合機專用

2D HIDO TMPE 車銑複合機專用三刃立銑刀 (R7) (45°) (SHANK h5)


TMPE (For Compound Lathe End Mill), 3 Flutes

單位: mm (Unit: mm)



產品編號 Model No.	刃徑 D Diameter	刃長 I Flute Length	柄徑 d Shank Diameter	全長 L Overall Length	價格 Price	備註
2D TMPE 0103R7D4	1	1.5	4	50		
2D TMPE 0103R7	1	1.5	6	50		
2D TMPE 0153R7	1.5	2.5	6	50		
2D TMPE 0203R7	2	3	6	50		
2D TMPE 0253R7	2.5	4	6	50		
2D TMPE 0303R7	3	4.5	6	50		
2D TMPE 0403R7D4	4	6	4	50		
2D TMPE 0403R7	4	6	6	50		
2D TMPE 0503R7	5	8	6	50		
2D TMPE 0603R7	6	9	6	50		
2D TMPE 0703R7	7	11	8	50		
2D TMPE 0803R7	8	12	8	50		
2D TMPE 1003R7	10	15	10	60		
2D TMPE 1203R7	12	18	12	60		
2D TMPE 1603R7	16	24	12	60		

備註: 其他規格, 請來電洽詢。 For other specifications, please call to inquire



2D HIDO TMTPE 車銑複合機專用小柄立銑刀 (R7) (45°) (SHANK h5)

TMTPE (For Compound Lathe End Mill-Small handle mill), 3 Flutes

單位: mm (Unit: mm)

產品編號 Model No.	刃徑 D Diameter	刃長 I Flute Length	柄徑 d Shank Diameter	全長 L Overall Length	價格 Price	備註
2D TMTPE 0803R7	8	8	6	30		
2D TMTPE 1003R7	10	10	6	35		
2D TMTPE 1203R7	12	12	6	40		

備註: 其他規格, 請來電洽詢。 For other specifications, please call to inquire


適用材質 Work Material:

★ 最適合 Excellent ● 適合 Better ▲ 佳 Good

碳素鋼 Carbon steels	合金鋼 Alloy steels	預硬鋼材 Pre-hardened steels ~HRC45	高硬度鋼 High-hardened				不銹鋼 Stainless steels	鈦合金 Titanium alloys	鎳基合金 Nickel Based alloys	銅合金 Copper alloys	鋁合金 Aluminum alloys
			~HRC50	~HRC55	~HRC60	~HRC65					
★	★	★					★	●	●	●	●


VUA 鎢鋼螺旋銑牙刀- ISO規格 (三峰)

VUA (Thread Milling Tools-Helical Flutes-ISO Metric) Three teeth



Defined by: R262 (DIN 13)
Tolerance class: 6H

單位: mm (Unit: mm)




產品編號 Model No.	外徑 D Diameter	牙距 MM Pitch	牙尺寸 Thread	有效長 DL Effective Length	刃數 T Flute	柄徑 d Shank Diameter	全長 L Overall Length	價格 Price	備註
5 VUA 01050303TX	1.05	0.3	M1.4 × 0.3	2.8	3T	4	50		
5 VUA 01200353TX	1.2	0.35	M1.6 × 0.35	3.2	3T	4	50		
5 VUA 01550403TX	1.55	0.4	M2 × 0.4	4	3T	4	50		
5 VUA 01950453TX	1.95	0.45	M2.5 × 0.45	5	3T	4	50		
5 VUA 02300503TX	2.3	0.5	M3 × 0.5	6	3T	4	50		
5 VUA 03200703TX	3.2	0.7	M4 × 0.7	8	3T	6	60		
5 VUA 04000803TX	4	0.8	M5 × 0.8	10	3T	6	60		
5 VUA 04801003TX	4.8	1.0	M6 × 1.0	12	3T	6	75		

備註: 其他規格, 請來電洽詢。 For other specifications, please call to inquire

VUB 鎢鋼螺旋銑牙刀- ISO規格 (全齒)

VUB (Thread Milling Tools-Helical Flutes-ISO Metric)-Full teeth



單位: mm (Unit: mm)

產品編號 Model No.	外徑 D Diameter	牙距 MM Pitch	牙尺寸 Thread	刃長 I Flute Length	刃數 T Flute	柄徑 d Shank Diameter	全長 L Overall Length	價格 Price	備註
5 VUB 02300503TX	2.3	0.5	M3 × 0.5	6	3T	6	50		
5 VUB 03100703TX	3.1	0.7	M4 × 0.7	10	3T	6	50		
5 VUB 04000803TX	4	0.8	M5 × 0.8	13	3T	6	60		
5 VUB 04801003TX	4.8	1.0	M6 × 1.0	15	3T	6	60		
5 VUB 06001253TX	6	1.25	M8 × 1.25	20	3T	6	60		
5 VUB 08001503TX	8	1.5	M10 × 1.5	20	3T	8	75		
5 VUB 10001754TX	10	1.75	M12 × 1.75	30	4T	10	75		
5 VUB 10002004TX	10	2.0	M14 × 2.0	36	4T	10	75		
5 VUB 12002004TX	12	2.0	M16 × 2.0	36	4T	12	100		

備註: 其他規格, 請來電洽詢。 For other specifications, please call to inquire

適用材質 Work Material:

★ 最適合 Excellent ● 適合 Better ▲ 佳 Good

碳素鋼 Carbon steels	合金鋼 Alloy steels	預硬鋼材 Pre-hardened steels ~HRC45	高硬度鋼 High-hardened				不銹鋼 Stainless steels	鈦合金 Titanium alloys	鎳基合金 Nickel Based alloys	銅合金 Copper alloys	鋁合金 Aluminum alloys
			~HRC50	~HRC55	~HRC60	~HRC65					
★	★	★	★	●	●	▲	★	●		●	●

VUA 鎢鋼銑牙刀-三峰-UN (內牙/外牙)

VUA(Tungsten Carbide Thread Milling Tools-American-UN (Internal/External))



單位：mm (Unit : mm)

產品編號 Model No.	外徑 D Diameter	牙尺寸 Thread Size		螺距 MM Pitch	有效長 DL Effective Length	刃數 T Flute	柄徑 d Shank Diameter	全長 L Overall Length	價格 Price	備註
		粗牙 UNC	細牙 UNF							
5 VUA 014UN72TX	1.4		1-72UNF	72	3.8	3	4	50		
5 VUA 014UN64TX	1.4	1-64UNC	2-64UNF	64	3.9	3	4	50		
5 VUA 016UN56TX	1.6	2-56UNC	3-56UNF	56	4.6	3	4	50		
5 VUA 019UN48TX	1.9	3-48UNC	4-48UNF	48	5.4	3	4	50		
5 VUA 021UN40TX	2.1	4-40UNC		40	6.2	3	4	50		
5 VUA 024UN40TX	2.4	5-40UNC	6-40UNF	40	7.1	3	4	50		
5 VUA 033UN36TX	3.3		8-36UNF	36	8.8	3	4	50		
5 VUA 026UN32TX	2.6	6-32UNC		32	7.3	3	4	50		
5 VUA 032UN32TX	3.2	8-32UNC	10-32UNF	32	10.1	3	6	60		
5 VUA 052UN28TX	5.2		1/4-28UNF	28	14	3	6	60		
5 VUA 036UN24TX	3.6	10-24UNC		24	10.4	3	6	60		
5 VUA 048UN20TX	4.8	1/4-20UNC	7/16-20UNF	20	13.7	3	6	60		
5 VUA 060UN18TX	6.0	5/16-18UNC		18	16.5	3	6	60		

備註：其他規格，請來電洽詢。 For other specifications, please call to inquire



適用材質 Work Material :

★最適合 Excellent ●適合 Better ▲佳 Good

碳素鋼 Carbon steels	合金鋼 Alloy steels	預硬鋼材	高硬度鋼				不銹鋼 Stainless steels	鈦合金 Titanium alloys	鎳基合金 Nickel Based alloys	銅合金 Copper alloys	鋁合金 Aluminum alloys
		Pre-hardened steels	High-hardened								
		~HRC45	~HRC50	~HRC55	~HRC60	~HRC65					
★	★	★	★	●	●	▲	★	●		●	●

VUB 鎢鋼銑牙刀- UN (內牙)

VUB Tungsten Carbide Thread Milling Tools-American-UN (Internal)



單位：mm (Unit : mm)

產品編號 Model No.	外徑 D Diameter	粗牙 UNC	細牙 UNF	極細牙 UNEF	螺距 P Pitch	牙長 I Flute Length	刃數 T Number of Flute	柄徑 d Shank Diameter	全長 L Overall Length	價格 Price	備註
5 VUB 06032UN	6.0			5/16	32	15	3	6	60		
5 VUB 08032UN	8.0			3/8	32	20	3	8	60		
5 VUB 05128UN	5.1		1/4		28	15	3	6	60		
5 VUB 08028UN	8.0			7/16-1/2	28	20	3	8	60		
5 VUB 06024UN	6.0		5/16		24	15	3	6	60		
5 VUB 08024UN	8.0		3/8		24	20	3	8	60		
5 VUB 12024UN	12.0		9/16-5/8		24	30	4	12	75		
5 VUB 04820UN	4.8	1/4			20	12	3	6	60		
5 VUB 08020UN	8.0		7/16		20	20	3	8	60		
5 VUB 10020UN	10.0		1/2		20	25	4	10	75		
5 VUB 12020UN	12.0			3/4-1	20	30	4	12	75		
5 VUB 06018UN	6.0	5/16			18	15	3	6	60		
5 VUB 10018UN	10.0		9/16-5/8		18	25	4	10	75		
5 VUB 07516UN	7.5	3/8			16	18.2	3	8	60		
5 VUB 12016UN	12.0		3/4		16	30	4	12	75		
5 VUB 08014UN	8.0	7/16			14	20	3	8	60		
5 VUB 12014UN	12.0		7/8		14	30	4	12	75		
5 VUB 10013UN	10.0	1/2			13	25	4	10	75		
5 VUB 11512UN	11.5	9/16			12	30	4	12	75		
5 VUB 16012UN	16.0		1		12	40	4	16	100		
5 VUB 12011UN	12.0	5/8			11	30	4	12	75		
5 VUB 16010UN	16.0	3/4			10	40	4	16	100		
5 VUB 16009UN	16.0	7/8			9	40	4	16	100		
5 VUB 20008UN	20.0	1			8	50	4	20	100		

備註：其他規格，請來電洽詢。 For other specifications, please call to inquire

適用材質 Work Material :

★最適合 Excellent ●適合 Better ▲佳 Good



碳素鋼 Carbon steels	合金鋼 Alloy steels	預硬鋼材	高硬度鋼				不銹鋼 Stainless steels	鈦合金 Titanium alloys	鎳基合金 Nickel Based alloys	銅合金 Copper alloys	鋁合金 Aluminum alloys
		Pre-hardened steels	High-hardened								
		~HRC45	~HRC50	~HRC55	~HRC60	~HRC65					
★	★	★	★	●	●	▲	★	●		●	●

螺紋加工

螺紋加工

VUC 鎢鋼銑牙刀- NPT/NPTF (內牙/外牙)

VUC Tungsten Carbide Thread Milling Tools-NPT/NPTF(Internal/External)



單位：mm (Unit : mm)

產品編號 Model No.	前端外徑 D1 Top Diameter	牙尺寸 Thread Size	牙距 Pitch	牙長 Flute Length	刃數 Flute T	柄徑 d Shank Diameter	全長 L Overall Length	齒數 Zt teeth	底孔尺寸 mm	價格 Price	備註 Note
5 VUC 0513NPT27TX	5.13	1/16"-27	0.941	11.3	3	6	60	12	6.3		
5 VUC 0720NPT27TX	7.20	1/8"-27	0.941	11.3	4	8	60	12	8.5		
5 VUC 0880NPT18TX	8.80	1/4"-18	1.411	16.9	4	10	75	12	11.1		
5 VUC 1090NPT18TX	10.90	3/8"-18	1.411	16.9	4	12	75	12	14.5		
5 VUC 1040NPT14TX	10.40	1/2	1.814	21.8	4	12	75	12	17.7		
5 VUC 1398NPT14TX	13.98	1/2",3/4"-14	1.814	25.4	4	16	100	14	17.7/23.0		
5 VUC 1790NPT115TX	17.90	1-2"-11.5	2.209	33.1	4	20	100	15	29.0/56.0		

備註：其他規格，請來電洽詢。 For other specifications, please call to inquire



適用材質 Work Material :

★最適合 Excellent ●適合 Better ▲佳 Good

碳素鋼 Carbon steels	合金鋼 Alloy steel	預硬鋼材 Pre-hardened steels	高硬度鋼 High-hardened				不銹鋼 Stainless steels	鈦合金 Titanium alloys	鎳基合金 Nickel Based alloys	銅合金 Copper alloys	鋁合金 Aluminum alloys
		~HRC45	~HRC50	~HRC55	~HRC60	~HRC65					
★	★	★	★	●	●	▲	★	●		●	●

VUC 鎢鋼螺旋斜度銑牙刀

VUC (Taper Thread Milling Cutter)



單位：mm (Unit : mm)

產品編號 Model No.	先端徑 D Top Diameter	牙距 MM Pitch	角度 a Taper	刃長 Flute Length I	刃數 Teeth T	柄徑 d Shank Diameter	全長 L Overall Length	價格 Price	備註 備註
5 VUC 0120300103GR	1.2	0.3	10°	7.90	3T	4	50		
5 VUC 0150300103GR	1.5	0.3	10°	7.04	3T	4	50		
5 VUC 0150375103GR	1.5	0.375	10°	7.04	3T	4	50		
5 VUC 0150330103GR	1.5	0.33	10°	7.04	3T	4	50		
5 VUC 0180430103GR	1.8	0.43	10°	11.90	3T	6	50		
5 VUC 0230400103GR	2.3	0.4	10°	10.46	3T	6	50		
5 VUC 0260400103GR	2.6	0.4	10°	9.60	3T	6	50		
5 VUC 0300333083GR	3	0.333	8°	10.65	3T	6	50		
5 VUC 03004167083GR	3	0.4167	8°	10.65	3T	6	50		

備註：其他規格，請來電洽詢。 For other specifications, please call to inquire

適用材質 Work Material :

★最適合 Excellent ●適合 Better ▲佳 Good

碳素鋼 Carbon steels	合金鋼 Alloy steels	預硬鋼材 Pre-hardened steels	高硬度鋼 High-hardened				不銹鋼 Stainless steels	鈦合金 Titanium alloys	鎳基合金 Nickel Based alloys	銅合金 Copper alloys	鋁合金 Aluminum alloys
		~HRC45	~HRC50	~HRC55	~HRC60	~HRC65					
★	★	★	★	●	●	▲	★	●	▲	●	●

2 鎢鋼倒角刀 - 2T

Tungsten Carbide Chamfering End Mill, 2 Flutes



單位 : mm (Unit : mm)

產品編號 Model No.	角度 a Top Angle	外徑 D Outside Diameter	刃數 T Flute	柄徑 d Shank Diameter	全長 L Overall Length	價格 Price	備註
2 2R2WC0400902	90°	4	2	4	50		
2 2R2WC0600902	90°	6	2	6	50		
2 2R2WC0800902	90°	8	2	8	60		
2 2R2WC1000902	90°	10	2	10	75		
2 2R2WC1200902	90°	12	2	12	75		
2 2R2WC0401202	120°	4	2	4	50		
2 2R2WC0601202	120°	6	2	6	50		
2 2R2WC0801202	120°	8	2	8	60		
2 2R2WC1001202	120°	10	2	10	75		
2 2R2WC1201202	120°	12	2	12	75		

備註：其他規格，請來電洽詢。 For other specifications, please call to inquire

2 鎢鋼倒角刀 - 4T

Tungsten Carbide Chamfering End Mill, 4 Flutes



單位 : mm (Unit : mm)

產品編號 Model No.	角度 a Top Angle	外徑 D Outside Diameter	小平面 D1 Top Diameter	刃數 T Flute	柄徑 d Shank Diameter	全長 L Overall Length	價格 Price	備註
2 2R2WC0400904	90°	4	0.5	4	4	50		
2 2R2WC0600904	90°	6	0.5	4	6	50		
2 2R2WC0800904	90°	8	0.5	4	8	60		
2 2R2WC1000904	90°	10	1	4	10	75		
2 2R2WC1200904	90°	12	1	4	12	75		


備註：其他規格，請來電洽詢。 For other specifications, please call to inquire

適用材質 Work Material : ★ 最適合 Excellent ● 適合 Better ▲ 佳 Good

碳素鋼 Carbon steels	合金鋼 Alloy steels	預硬鋼材 Pre-hardened steels		高硬度鋼 High-hardened					不銹鋼 Stainless steels	鈦合金 Titanium alloys	鎳基合金 Nickel Based alloys	銅合金 Copper alloys	鋁合金 Aluminum alloys
		~HRC45	~HRC50	~HRC55	~HRC60	~HRC65							
★	★	★	●	●					★	★	▲	★	★

2 鎢鋼上下倒角刀

Tungsten Carbide Back and Front Chamfering Cutter



單位 : mm (Unit : mm)

產品編號 Model No.	角度 a Top Angle	外徑 D Outside Diameter	頸徑 dh Neck dia	頸長 L1	刃數 T Flute	柄徑 d Shank Diameter	全長 L Overall Length	價格 Price	備註
2 2R2UD0400904D6	90°	4	2	4	4	6	75		
2 2R2UD0600904	90°	6	3	6	4	6	75		
2 2R2UD0800904	90°	8	4	8	4	8	75		
2 2R2UD1000904	90°	10	5	10	4	10	75		
2 2R2UD1200904	90°	12	6	12	4	12	75		

備註：其他規格，請來電洽詢。 For other specifications, please call to inquire


適用材質 Work Material :

★ 最適合 Excellent ● 適合 Better ▲ 佳 Good

碳素鋼 Carbon steels	合金鋼 Alloy steels	預硬鋼材 Pre-hardened steels		高硬度鋼 High-hardened					不銹鋼 Stainless steels	鈦合金 Titanium alloys	鎳基合金 Nickel Based alloys	銅合金 Copper alloys	鋁合金 Aluminum alloys
		~HRC45	~HRC50	~HRC55	~HRC60	~HRC65							
★	★	●	●	●					★	●	▲	★	★

2 V2SD 鎢鋼鑽銑刀

Tungsten Carbide V-Pointed End Mill (Drilling and Milling)



單位：mm (Unit : mm)

產品編號 Model No.	刀徑 D Diameter	角度 a Top Angle	刃長 l Flute Length	柄徑 d Shank Diameter	全長 L Overall Length	價格 Price	備註
V2 2 SD 0300902TXM	3	× 90°	8	3	50		
V2 2 SD 0400902TXM	4	× 90°	11	4	50		
V2 2 SD 0600902TXM	6	× 90°	15	6	50		
V2 2 SD 0800902TXM	8	× 90°	20	8	60		
V2 2 SD 1000902TXM	10	× 90°	25	10	75		
V2 2 SD 1200902TXM	12	× 90°	30	12	75		
V2 2 SD 1600902TXM	16	× 90°	45	16	100		


產品編號 Model No.	刀徑 D Diameter	角度 a Top Angle	刃長 l Flute Length	柄徑 d Shank Diameter	全長 L Overall Length	價格 Price	備註
V2 2 SLSD 0300902TXM	3	× 90°	8	3	75		
V2 2 SLSD 0400902TXM	4	× 90°	11	4	75		
V2 2 MLSD 0600902TXM	6	× 90°	15	6	100		
V2 2 MLSD 0800902TXM	8	× 90°	20	8	100		
V2 2 MLSD 1000902TXM	10	× 90°	25	10	100		
V2 2 MLSD 1200902TXM	12	× 90°	30	12	100		
V2 2 LLSLSD 1600902TXM	16	× 90°	45	16	150		

備註：其他規格，請來電洽詢。 For other specifications, please call to inquire

適用材質 Work Material :

★ 最適合 Excellent ● 適合 Better ▲ 佳 Good

碳素鋼 Carbon steels	合金鋼 Alloy steels	高硬度鋼 High-hardened					不銹鋼 Stainless steels	鈦合金 Titanium alloys	鎳基合金 Nickel Based alloys	銅合金 Copper alloys	鋁合金 Aluminum alloys
		預硬鋼材 Pre-hardened steels	~HRC45	~HRC50	~HRC55	~HRC60					
★	★	●					●	●		★	★



2 鎢鋼定位鑽 - 2T

Tungsten Carbide Spot Drills.



單位：mm (Unit : mm)

產品編號 Model No.	角度 a Top Angle	刀徑 D Diameter	刃長 l Flute Length	柄徑 d Shank Diameter	全長 L Overall Length	價格 Price	備註
SDNCWC 090030	90°	3	10	3	50		
SDNCWC 090040	90°	4	12	4	50		
SDNCWC 090050	90°	5	15	5	50		
SDNCWC 090060	90°	6	20	6	50		
SDNCWC 090080	90°	8	25	8	60		
SDNCWC 090100	90°	10	25	10	75		
SDNCWC 090120	90°	12	30	12	75		
SDNCWC 090160	90°	16	35	16	100		
SDNCWC 120030	120°	3	10	3	50		
SDNCWC 120040	120°	4	12	4	50		
SDNCWC 120050	120°	5	15	5	50		
SDNCWC 120060	120°	6	20	6	50		
SDNCWC 120080	120°	8	25	8	60		
SDNCWC 120100	120°	10	25	10	75		
SDNCWC 120120	120°	12	30	12	75		
SDNCWC 120160	120°	16	35	16	100		

備註：其他規格，請來電洽詢。 For other specifications, please call to inquire

適用材質 Work Material :

★ 最適合 Excellent ● 適合 Better ▲ 佳 Good

碳素鋼 Carbon steels	合金鋼 Alloy steel	高硬度鋼 High-hardened					不銹鋼 Stainless steels	鈦合金 Titanium alloys	鎳基合金 Nickel Based alloys	銅合金 Copper alloys	鋁合金 Aluminum alloys
		預硬鋼材 Pre-hardened steels	~HRC45	~HRC50	~HRC55	~HRC60					
★	★	●	●				★	★	▲	★	

5 TTA 鎢鋼雕刻銑刀

Tungsten Carbide Engraving End Mill.



1. 刀尖提供 0.1、0.2、0.3、0.4、0.5 寬度，讓使用者有更多的選擇。
2. 適合加工一般鋼材、鋁合金、銅合金。
3. 適合中加工、精加工。

單位：mm (Unit : mm)

產品編號 Model No.	外徑 D Outside Diameter	錐度 a Taper Angle	刃數 T Flute	柄徑 d Shank Diameter	全長 L Overall Length	價格 Price	備註
5 TTA 0011501	0.1	15°	1	4	50		
5 TTA 0021501	0.2	15°	1	4	50		
5 TTA 0031501	0.3	15°	1	4	50		
5 TTA 0041501	0.4	15°	1	4	50		
5 TTA 0051501	0.5	15°	1	4	50		

備註：其他規格，請來電洽詢。 For other specifications, please call to inquire



適用材質 Work Material :

★ 最適合 Excellent ● 適合 Better ▲ 佳 Good

碳素鋼 Carbon steels	合金鋼 Alloy steels	高硬度鋼 High-hardened					不銹鋼 Stainless steels	鈦合金 Titanium alloys	鎳基合金 Nickel Based alloys	銅合金 Copper alloys	鋁合金 Aluminum alloys
		預硬鋼材 Pre-hardened steels	~HRC45	~HRC50	~HRC55	~HRC60					
★	★	●	●	●			●	●	▲	★	

2 RC 鎢鋼外R角銑刀

Tungsten Carbide Outer Radius End Mill



單位: mm (Unit: mm)

產品編號 Model No.	外R角 R Radius	先端徑 d1 Top Diameter	外徑 D Outside Diameter	刃數 T Flute	柄徑 d Shank Diameter	全長 L Overall Length	價格 Price	備註
2 RC 0104	0.5R	1.5	2.7	4	4	50		
2 RC 1504	0.75R	1.5	3.2	4	4	50		
2 RC 0204	1R	1.5	3.7	4	4	50		
2 RC 0254D6	1.25R	1.5	4.2	4	6	50		
2 RC 0304D6	1.5R	1.5	4.7	4	6	50		
2 RC 0354D6	1.75R	1.5	5.2	4	6	50		
2 RC 0404D6	2R	1.5	5.7	4	6	50		
2 RC 0504D8	2.5R	1.5	6.7	4	8	60		
2 RC 0604D8	3R	1.5	7.7	4	8	60		
2 RC 0704D10	3.5R	2	9.2	4	10	75		
2 RC 0804D12	4R	2	10.2	4	12	75		
2 RC 1004D14	5R	3	13.2	4	14	100		
2 RC 1204D16	6R	3	15.2	4	16	100		

備註: 其他規格, 請來電洽詢。 For other specifications, please call to inquire

適用材質 Work Material:

★ 最適合 Excellent ● 適合 Better ▲ 佳 Good

碳素鋼 Carbon steels	合金鋼 Alloy steel	預硬鋼材 Pre-hardened steels ~HRC45	高硬度鋼 High-hardened ~HRC50 ~HRC55 ~HRC60 ~HRC65				不銹鋼 Stainless steels	鈦合金 Titanium alloys	鎳基合金 Nickel Based alloys	銅合金 Copper alloys	鋁合金 Aluminum alloys
★	★	●	●	▲			★	●	▲	★	★

5 280° 鎢鋼棒棒糖球刀

280° Lollipop tungsten Carbide Ball Nose milling cutter.



單位: mm (Unit: mm)

產品編號 Model No.	球頭半徑 R Radius	外徑 D Outside Diameter	頸徑 dh Neck dia	頸長 L1	刃數 T Flute	柄徑 d Shank Diameter	全長 L Overall Length	價格 Price	備註
5 MTB 0102	0.5R	1	0.65	3	2	4	50		
5 MTB 0152	0.75R	1.5	0.98	5	2	4	50		
5 MTB 0202	1R	2	1.3	6	2	4	50		
5 MTB 0302	1.5R	3	1.95	9	2	4	50		
5 MTB 0402	2R	4	2.6	12	2	4	50		
5 TB 0502	2.5R	5	3.25	15	2	6	50		
5 TB 0602	3R	6	3.9	18	2	6	50		
5 TB 0802	4R	8	5.2	24	2	8	75		
5 TB 1002	5R	10	6.5	30	2	10	75		
5 TB 1202	6R	12	7.8	36	2	12	75		

備註: 其他規格, 請來電洽詢。 For other specifications, please call to inquire


適用材質 Work Material:

★ 最適合 Excellent ● 適合 Better ▲ 佳 Good

碳素鋼 Carbon steels	合金鋼 Alloy steels	預硬鋼材 Pre-hardened steels ~HRC45	高硬度鋼 High-hardened ~HRC50 ~HRC55 ~HRC60 ~HRC65				不銹鋼 Stainless steels	鈦合金 Titanium alloys	鎳基合金 Nickel Based alloys	銅合金 Copper alloys	鋁合金 Aluminum alloys
★	★	●	●	●	▲		★	●	▲	★	★

638 複合材料、碳纖維專用鎢鋼立銑刀

For Composite Materials, Carbon Fiber tungsten Carbide milling cutter



單位: mm (Unit: mm)

產品編號 Model No.	刃徑 D Diameter	刃長 l Flute Length	柄徑 d Shank Diameter	全長 L Overall Length	價格 price	備註
638 XXE 010N	1	4	4	50		
638 XXE 015N	1.5	6	4	50		
638 XXE 020N	2	8	4	50		
638 XXE 030N	3	12	4	50		
638 XXE 040N	4	16	4	50		
638 XXE 060N	6	24	6	60		
638 XXE 080N	8	32	8	75		
638 XXE 100NS30	10	30	10	75		
638 XXE 100NS50L100	10	50	10	100		
638 XXE 120NS50L100	12	50	12	100		

備註: 其他規格, 請來電洽詢。 For other specifications, please call to inquire

適用材質 Work Material:

★ 最適合 Excellent ● 適合 Better ▲ 佳 Good

碳素鋼 Carbon steels	合金鋼 Alloy steel	預硬鋼材 Pre-hardened steels ~HRC45	高硬度鋼 High-hardened ~HRC50 ~HRC55 ~HRC60 ~HRC65				碳纖維複材 CFRP	玻璃纖維複材 GFRP	銅合金 Copper alloys	鋁合金 Aluminum alloys
							★	★		

638 YY 銑刀

YYE For Composite Materials Tungsten Carbide Milling Cutter



單位: mm (Unit: mm)

產品編號 Model No.	刃徑 D Diameter	刃長 l Flute Length	柄徑 d Shank Diameter	全長 L Overall Length	價格 price	備註
638 YYE 0104N	1	4	4	50		
638 YYE 015N	1.5	6	4	50		
638 YYE 020N	2	8	4	50		
638 YYE 030N	3	12	4	50		
638 YYE 040NS16	4	16	4	50		
638 YYE 060NL60	6	24	6	60		
638 YYE 080NL75	8	32	8	75		
638 YYE 100N	10	30	10	75		
638 YYE 100NS50L100	10	50	10	100		
638 YYE 120NS50	12	50	12	100		

備註: 其他規格, 請來電洽詢。 For other specifications, please call to inquire

適用材質 Work Material:

★ 最適合 Excellent ● 適合 Better ▲ 佳 Good


碳素鋼 Carbon steels	合金鋼 Alloy steels	預硬鋼材 Pre-hardened steels ~HRC45	高硬度鋼 High-hardened ~HRC50 ~HRC55 ~HRC60 ~HRC65				碳纖維複材 CFRP	玻璃纖維複材 GFRP	銅合金 Copper alloys	鋁合金 Aluminum alloys
							★	★	●	●

特殊加工用刀

特殊加工用刀

2 鎢鋼T型銑刀

Tungsten Carbide, T-Shape End Mill, 4 Flutes / 6 Flutes



1. 高硬度和耐磨性
2. 採用全鎢鋼一體成型
3. 增強剛性與抗震

單位：mm (Unit : mm)

產品編號 Model No.	刃徑 D	厚度 x H	頸徑 dh	頸長 NL	刃數 T	柄徑 d	全長 L	價格 price	備註
2 TE03000504	3	x 0.5	1.5	3	4	4	50		
2 TE03000604	3	x 0.6	1.5	3	4	4	50		
2 TE03000704	3	x 0.7	1.5	3	4	4	50		
2 TE03000804	3	x 0.8	1.5	3	4	4	50		
2 TE03000904	3	x 0.9	1.5	3	4	4	50		
2 TE03001004	3	x 1	1.5	3	4	4	50		
2 TE03001504	3	x 1.5	1.5	3	4	4	50		
2 TE03002004	3	x 2	1.5	3	4	4	50		
2 TE04000504	4	x 0.5	2	3.5	6	4	50		
2 TE04000604	4	x 0.6	2	3.5	6	4	50		
2 TE04000704	4	x 0.7	2	3.5	6	4	50		
2 TE04000804	4	x 0.8	2	3.5	6	4	50		
2 TE04000904	4	x 0.9	2	3.5	6	4	50		
2 TE04001004	4	x 1	2	3.5	6	4	50		
2 TE04001504	4	x 1.5	2	3.5	6	4	50		
2 TE04002004	4	x 2	2	3.5	6	4	50		
2 TE05000506	5	x 0.5	2.5	4	6	6	50		
2 TE05000606	5	x 0.6	2.5	4	6	6	50		
2 TE05000706	5	x 0.7	2.5	4	6	6	50		
2 TE05000806	5	x 0.8	2.5	4	6	6	50		
2 TE05000906	5	x 0.9	2.5	4	6	6	50		
2 TE05001006	5	x 1	2.5	4	6	6	50		
2 TE05001506	5	x 1.5	2.5	4	6	6	50		
2 TE05002006	5	x 2	2.5	4	6	6	50		
2 TE06000506	6	x 0.5	3	4	6	6	50		
2 TE06000606	6	x 0.6	3	4	6	6	50		
2 TE06000706	6	x 0.7	3	4	6	6	50		
2 TE06000806	6	x 0.8	3	4	6	6	50		
2 TE06000906	6	x 0.9	3	4	6	6	50		
2 TE06001006	6	x 1	3	4	6	6	50		
2 TE06001506	6	x 1.5	3	4	6	6	50		
2 TE06002006	6	x 2	3	4	6	6	50		
2 TE08001006	8	x 1	4	4	6	8	60		
2 TE08001506	8	x 1.5	4	4	6	8	60		
2 TE08002006	8	x 2	4	4	6	8	60		
2 TE08002506	8	x 2.5	4	4	6	8	60		

單位：mm (Unit : mm)

產品編號 Model No.	刃徑 D	厚度 x H	頸徑 dh	頸長 NL	刃數 T	柄徑 d	全長 L	價格 price	備註
2 TE10001006	10	x 1	5	6	6	10	75		
2 TE10001506	10	x 1.5	5	6	6	10	75		
2 TE10002006	10	x 2	5	6	6	10	75		
2 TE10003006	10	x 3	5	6	6	10	75		
2 TE12001006	12	x 1	6	7	6	12	75		
2 TE12001506	12	x 1.5	6	7	6	12	75		
2 TE12002006	12	x 2	6	7	6	12	75		
2 TE12003006	12	x 3	6	7	6	12	75		
2 TE16001008	16	x 1	7.5	8.5	8	16	75		
2 TE16001508	16	x 1.5	7.5	8.5	8	16	75		
2 TE16002008	16	x 2	7.5	8.5	8	16	75		
2 TE16002508	16	x 2.5	7.5	8.5	8	16	75		
2 TE16003008	16	x 3	7.5	8.5	8	16	75		
2 TE16004008	16	x 4	7.5	8.5	8	16	75		

備註：其他規格，請來電洽詢。 For other specifications, please call to inquire


適用材質 Work Material :

★ 最適合 Excellent ● 適合 Better ▲ 佳 Good

碳素鋼 Carbon steels	合金鋼 Alloy steels	預硬鋼材 Pre-hardened steels	高硬度鋼 High-hardened					不銹鋼 Stainless steels	鈦合金 Titanium alloys	鎳基合金 Nickel Based alloys	銅合金 Copper alloys	鋁合金 Aluminum alloys
		~HRC45	~HRC50	~HRC55	~HRC60	~HRC65						
★	★	●	●					★	●	▲	★	★

焊刃鎢鋼T型槽銑刀(直刃)

Brazed Carbide T-Slot Cutter (Straight Flute)



單位: mm (Unit: mm)

產品編號 Model No.	刃徑 D	厚度 H	刃數 T	柄徑 d	全長 L	價格 price	備註
CBTE 1600204	16	2 ~ 8 mm	4	12	100		
CBTE 2000206	20	2 ~ 10mm	4	12	100		
CBTE 2500206	25	2 ~ 10mm	6	16	100		
CBTE 3000206	30	2 ~ 10mm	6	16	100		
CBTE 3500206	35	2 ~ 10mm	6	16	100		
CBTE 4000206	40	2 ~ 10mm	6	16	100		
CBTE 4500206	45	2 ~ 10mm	6	20	100		
CBTE 5000208	50	2 ~ 10mm	8	20	100		
CBTE 6000210	60	2 ~ 5 mm	10	20	120		
CBTE 7500212	75	2 ~ 5 mm	12	25	120		

備註: 其他規格, 請來電洽詢。 For other specifications, please call to inquire


適用材質 Work Material:

★最適合 Excellent ●適合 Better ▲佳 Good

碳素鋼 Carbon steels	合金鋼 Alloy steels	預硬鋼材	高硬度鋼					不銹鋼 Stainless steels	鈦合金 Titanium alloys	鎳基合金 Nickel Based alloys	銅合金 Copper alloys	鋁合金 Aluminum alloys
		~HRC45	~HRC50	~HRC55	~HRC60	~HRC65						
★	★	●	●							★	★	

鎢鋼鳩尾銑刀 45°/60°

Carbide Dove-Tail End Mills



單位: mm (Unit: mm)

產品編號 Model No.	刃徑 D	角度 a	刃長 l	頸徑 dh	頸長 NL	刃數 T	柄徑 d	全長 L	價格 price	備註
2 RJ 030454D6	3	45°	0.8	1.4	3	4	6	60		
2 RJ 040454	4	45°	1	2	3	4	4	50		
2 RJ 040454D6	4	45°	1	2	3	4	6	60		
2 RJ 050454	5	45°	1.2	2.5	4	4	6	60		
2 RJ 060454	6	45°	1.4	3	4	4	6	60		
2 RJ 080454	8	45°	1.9	4	5	4	8	60		
2 RJ 100454	10	45°	2.4	5	6	4	10	75		
2 RJ 120454	12	45°	2.9	6	7	4	12	75		

單位: mm (Unit: mm)

產品編號 Model No.	刃徑 D	角度 a	刃長 l	頸徑 dh	頸長 NL	刃數 T	柄徑 d	全長 L	價格 price	備註
2 RJ 030604D6	3	60°	1.2	1.5	3	4	6	60		
2 RJ 040604D6	4	60°	1.6	2	3.5	4	6	60		
2 RJ 050604	5	60°	2.2	2.3	4	4	6	60		
2 RJ 060604	6	60°	2.7	2.7	4	4	6	60		
2 RJ 080604	8	60°	3.7	3.6	5	4	8	60		
2 RJ 100604	10	60°	4.6	4.5	6	4	10	75		
2 RJ 120604	12	60°	5.6	5.4	7	4	12	75		

備註: 其他規格, 請來電洽詢。 For other specifications, please call to inquire

適用材質 Work Material:


★最適合 Excellent ●適合 Better ▲佳 Good

碳素鋼 Carbon steels	合金鋼 Alloy steels	預硬鋼材	高硬度鋼					不銹鋼 Stainless steels	鈦合金 Titanium alloys	鎳基合金 Nickel Based alloys	銅合金 Copper alloys	鋁合金 Aluminum alloys
		~HRC45	~HRC50	~HRC55	~HRC60	~HRC65						
★	★	●	▲					★	●		★	★

5 TTA 鎢鋼斜度銑刀

Tungsten Carbide Taper End Mills-2 / 4 Flutes

1. 排屑順暢，刀具壽命佳，精度佳。
Chip removal fluency, Great tool life, Excellent precision.
2. 成型工件一次加工完成，減少加工時間及成本。
Formed workpiece-finish in one time, reduce the processing time and cost.
3. 適合加工一般鋼材、不銹鋼、模具鋼。
Suitable: Alloy Steel, Stainless Steel, Die Steel.



單位：mm (Unit : mm)

產品編號 Model No.	外徑 D Outside Diameter	角度 a Taper Angle	刃長 l Flute Length	刃數 T Flute	柄徑 d Shank Diameter	全長 L Overall Length	價格 price	備註
5 TTA 0050102OL	0.5	1°	2	2	4	50		
5 TTA 0050252OL	0.5	2.5°	2	2	4	50		
5 TTA 0050702OL	0.5	7°	2	2	4	50		
5 TTA 0051002OL	0.5	10°	2	2	4	50		
5 TTA 0080052OL	0.8	0.5°	3	2	4	50		
5 TTA 0080102OL	0.8	1°	3	2	4	50		
5 TTA 0080152OL	0.8	1.5°	3	2	4	50		
5 TTA 0080202OL	0.8	2°	3	2	4	50		
5 TTA 0080252OL	0.8	2.5°	3	2	4	50		
5 TTA 0080302OL	0.8	3°	3	2	4	50		
5 TTA 0080502OL	0.8	5°	3	2	4	50		
5 TTA 0080702OL	0.8	7°	3	2	4	50		
5 TTA 0081002OL	0.8	10°	3	2	4	50		
5 TTA 0100052TX	1	0.5°	4	2	4	50		
5 TTA 0100102TX	1	1°	4	2	4	50		
5 TTA 0100152TX	1	1.5°	4	2	4	50		
5 TTA 0100202TX	1	2°	4	2	4	50		
5 TTA 0100302TX	1	3°	4	2	4	50		
5 TTA 0100502TX	1	5°	4	2	4	50		
5 TTA 0100702TX	1	7°	4	2	4	50		
5 TTA 0101402TX	1	14°	4	2	4	50		
5 TTA 0101502TX	1	15°	4	2	4	50		
5 TTA 0150052TX	1.5	0.5°	5	2	4	50		
5 TTA 0150102TX	1.5	1°	5	2	4	50		
5 TTA 0150152TX	1.5	1.5°	5	2	4	50		
5 TTA 0150202TX	1.5	2°	5	2	4	50		
5 TTA 0150302TX	1.5	3°	5	2	4	50		
5 TTA 0150502TX	1.5	5°	5	2	4	50		
5 TTA 0150702TX	1.5	7°	5	2	4	50		
5 TTA 0151002TX	1.5	10°	5	2	4	50		
5 TTA 0152002TXD6	1.5	20°	6.18	2	6	50		
5 TTA 0200052TX	2	0.5°	6	2	4	50		
5 TTA 0200102TX	2	1°	6	2	4	50		
5 TTA 0200152TX	2	1.5°	6	2	4	50		
5 TTA 0200202TX	2	2°	6	2	4	50		
5 TTA 0200302TX	2	3°	6	2	4	50		
5 TTA 0200502TX	2	5°	6	2	4	50		
5 TTA 0200702TX	2	7°	6	2	4	50		
5 TTA 0201002TX	2	10°	6	2	4	50		
5 TTA 0201502TXD6	2	15°	6	2	6	50		

單位：mm (Unit : mm)


產品編號 Model No.	外徑 D Outside Diameter	角度 a Taper Angle	刃長 l Flute Length	刃數 T Flute	柄徑 d Shank Diameter	全長 L Overall Length	價格 price	備註
5 TTA 0250052TX	2.5	0.5°	8	2	4	50		
5 TTA 0250102TX	2.5	1°	8	2	4	50		
5 TTA 0250152TX	2.5	1.5°	8	2	4	50		
5 TTA 0250202TX	2.5	2°	8	2	4	50		
5 TTA 0250252TX	2.5	2.5°	8	2	4	50		
5 TTA 0250302TX	2.5	3°	8	2	4	50		
5 TTA 0250502TXD6	2.5	5°	8	2	6	50		
5 TTA 0250702TXD6	2.5	7°	8	2	6	50		
5 TTA 0251002TXD6	2.5	10°	8	2	6	50		
5 TTA 0300054TX	3	0.5°	10	4	6	50		
5 TTA 0300104TX	3	1°	10	4	6	50		
5 TTA 0300154TX	3	1.5°	10	4	6	50		
5 TTA 0300204TX	3	2°	10	4	6	50		
5 TTA 0300254TX	3	2.5°	10	4	6	50		
5 TTA 0300304TX	3	3°	10	4	6	50		
5 TTA 0300504TX	3	5°	10	4	6	50		
5 TTA 0300704TX	3	7°	10	4	6	50		
5 TTA 0400054TX	4	0.5°	15	4	6	50		
5 TTA 0400104TX	4	1°	15	4	6	50		
5 TTA 0400154TX	4	1.5°	15	4	6	50		
5 TTA 0400204TX	4	2°	15	4	6	50		
5 TTA 0400254TX	4	2.5°	15	4	6	50		
5 TTA 0400304TX	4	3°	15	4	6	50		
5 TTA 0400504TXD8	4	5°	15	4	8	60		
5 TTA 0400504TX	4	5°	15	4	8	50		
5 TTA 0400604TX	4	6°	15	4	8	50		
5 TTA 0400704TXD8	4	7°	15	4	8	60		
5 TTA 0500104TX	5	1°	20	4	6	60		
5 TTA 0500154TX	5	1.5°	20	4	8	60		
5 TTA 0500204TX	5	2°	20	4	8	60		
5 TTA 0500254TX	5	2.5°	20	4	8	60		
5 TTA 0500304TX	5	3°	20	4	8	60		
5 TTA 0500504TX	5	5°	20	4	8	60		
5 TTA 0600054TX	6	0.5°	20	4	8	60		
5 TTA 0600154TX	6	1.5°	20	4	8	60		
5 TTA 0600204TX	6	2°	20	4	8	60		
5 TTA 0600254TX	6	2.5°	20	4	8	60		
5 TTA 0600304TX	6	3°	20	4	8	60		
5 TTA 0600504TX	6	5°	20	4	10	75		

備註：其他規格，請來電洽詢。 For other specifications, please call to inquire

適用材質 Work Material :

★ 最適合 Excellent ● 適合 Better ▲ 佳 Good


碳素鋼 Carbon steels	合金鋼 Alloy steels	預硬鋼材 Pre-hardened steels		高硬度鋼 High-hardened				不銹鋼 Stainless steels	鈦合金 Titanium alloys	鎳基合金 Nickel Based alloys	銅合金 Copper alloys	鋁合金 Aluminum alloys
		~HRC45	~HRC50	~HRC55	~HRC60	~HRC65						
★	★	★	●	●				●	●	▲	★	★



單位：mm (Unit : mm)

產品編號 Model No.	D 直徑 Diameter	L1 刃長 Flute-Length	L 刀頭全長 Overall Length	D1 支撐位頸徑 Neck Diameter	M 連接螺紋 Tread Size	價格 Price	備註
HESD 0804TX	8	8	17	5.5	M05		
HESD 1004TX	10	10	21	5.5	M05		
HESD 1204TX	12	12	25.5	6.5	M06		
HESD 1604TX	16	16	30	8.5	M08		
HESD 2004TX	20	20	38	10.5	M10		
HESD 2504TX	25	25	42	12.5	M12		


備註：其他規格，請來電洽詢。 For other specifications, please call to inquire



單位：mm (Unit : mm)

產品編號 Model No.	R 球頭半徑 Radius	L1 刃長 Flute-Length	L 刀頭全長 Overall Length	D1 支撐位頸徑 Neck Diameter	M 連接螺紋 Tread Size	價格 Price	備註
HSB 0802TX	4R	8	17	5.5	M05		
HSB 1002TX	5R	10	21	5.5	M05		
HSB 1202TX	6R	12	25.5	6.5	M06		
HSB 1602TX	8R	16	30	8.5	M08		
HSB 2002TX	10R	20	38	10.5	M10		
HSB 2502TX	12.5R	25	42	12.5	M12		

備註：其他規格，請來電洽詢。 For other specifications, please call to inquire



單位：mm (Unit : mm)

產品編號 Model No.	D 直徑 × R 角 Diameter × Corner Radius	L1 刃長 Flute-Length	L 刀頭全長 Overall Length	D1 支撐位頸徑 Neck Diameter	M 連接螺紋 Tread Size	價格 Price	備註
HESR 080054TX	8 × 0.5R	8	17	5.5	M05		
HESR 080104TX	8 × 1R	8	17	5.5	M05		
HESR 100054TX	10 × 0.5R	10	21	5.5	M05		
HESR 100104TX	10 × 1R	10	21	5.5	M05		
HESR 100204TX	10 × 2R	10	21	5.5	M05		
HESR 120054TX	12 × 0.5R	12	25.5	6.5	M06		
HESR 120104TX	12 × 1R	12	25.5	6.5	M06		
HESR 120204TX	12 × 2R	12	25.5	6.5	M06		
HESR 160054TX	16 × 0.5R	16	30	8.5	M08		
HESR 160104TX	16 × 1R	16	30	8.5	M08		
HESR 160204TX	16 × 2R	16	30	8.5	M08		
HESR 200104TX	20 × 1R	20	38	10.5	M10		
HESR 200204TX	20 × 2R	20	38	10.5	M10		
HESR 200304TX	20 × 3R	20	38	10.5	M10		
HESR 250104TX	25 × 1R	25	42	12.5	M12		
HESR 250204TX	25 × 2R	25	42	12.5	M12		
HESR 250304TX	25 × 3R	25	42	12.5	M12		

備註：其他規格，請來電洽詢。 For other specifications, please call to inquire

適用材質 Work Material :

★ 最適合 Excellent ● 適合 Better ▲ 佳 Good


碳素鋼 Carbon steels	合金鋼 Alloy steels	預硬鋼材 Pre-hardened steels ~HRC45	高硬度鋼 High-hardened					不銹鋼 Stainless steels	鈦合金 Titanium alloys	鎳基合金 Nickel Based alloys	銅合金 Copper alloys	鋁合金 Aluminum alloys
			~HRC50	~HRC55	~HRC60	~HRC65						
●	●	★	★	★	★	▲	▲	▲			●	★



單位：mm (Unit : mm)

產品編號 Model No.	D 直徑 Diameter	L1 刃長 Flute-Length	L 刀頭全長 Overall Length	D1 支撐位頸徑 Neck Diameter	M 連接螺紋 Tread Size	價格 Price	備註
HAE 0803	8	8	17	5.5	M05		
HAE 1003	10	10	21	5.5	M05		
HAE 1203	12	12	25.5	6.5	M06		
HAE 1603	16	16	30	8.5	M08		
HAE 2003	20	20	38	10.5	M10		
HAE 2503	25	25	42	12.5	M12		

備註：其他規格，請來電洽詢。 For other specifications, please call to inquire



單位：mm (Unit : mm)

產品編號 Model No.	R 球頭半徑 Radius	L1 刃長 Flute-Length	L 刀頭全長 Overall Length	D1 支撐位頸徑 Neck Diameter	M 連接螺紋 Tread Size	價格 Price	備註
HACB 0802	4R	8	17	5.5	M05		
HACB 1002	5R	10	21	5.5	M05		
HACB 1202	6R	12	25.5	6.5	M06		
HACB 1602	8R	16	30	8.5	M08		
HACB 2002	10R	20	38	10.5	M10		
HACB 2502	12.5R	25	42	12.5	M12		

備註：其他規格，請來電洽詢。 For other specifications, please call to inquire



單位：mm (Unit : mm)

產品編號 Model No.	D 直徑 × R 角 Diameter × Corner Radius	L1 刃長 Flute-Length	L 刀頭全長 Overall Length	D1 支撐位頸徑 Neck Diameter	M 連接螺紋 Tread Size	價格 Price	備註
HAR 100103	10 × 1R	10	21	5.5	M05		
HAR 100203	10 × 2R	10	21	5.5	M05		
HAR 100303	10 × 3R	10	21	5.5	M05		
HAR 120103	12 × 1R	12	25.5	6.5	M06		
HAR 120153	12 × 1.5R	12	25.5	6.5	M06		
HAR 120203	12 × 2R	12	25.5	6.5	M06		
HAR 120303	12 × 3R	12	25.5	6.5	M06		
HAR 160103	16 × 1R	16	30	8.5	M08		
HAR 160153	16 × 1.5R	16	30	8.5	M08		
HAR 160203	16 × 2R	16	30	8.5	M08		
HAR 160303	16 × 3R	16	30	8.5	M08		
HAR 200203	20 × 2R	20	38	10.5	M10		
HAR 200303	20 × 3R	20	38	10.5	M10		
HAR 200503	20 × 5R	20	38	10.5	M10		
HAR 250203	25 × 2R	25	42	12.5	M12		
HAR 250303	25 × 3R	25	42	12.5	M12		
HAR 250503	25 × 5R	25	42	12.5	M12		

備註：其他規格，請來電洽詢。 For other specifications, please call to inquire

適用材質 Work Material :

★ 最適合 Excellent ● 適合 Better ▲ 佳 Good

碳素鋼 Carbon steels	合金鋼 Alloy steels	預硬鋼材 Pre-hardened steels ~HRC45	高硬度鋼 High-hardened					不銹鋼 Stainless steels	鈦合金 Titanium alloys	鎳基合金 Nickel Based alloys	銅合金 Copper alloys	鋁合金 Aluminum alloys
			~HRC50	~HRC55	~HRC60	~HRC65						
											●	★

GL 鎢鋼抗震刀柄

GL Tungsten Carbide Anti-Vibration Tools Holder


1. 使用全碳化鎢材質製成，剛性優異、吸震性佳、不會因橫向靖力過大，而扭曲變形。
One piece formed design of the Tungsten Carbide Tools holder, have excellent Stiffness and great Anti-Vibration, will not be twisted and deformed due to excessive lateral force.
2. 延長加工深度，提升加工面精度，實現超長、超深、超高精度加工之可行性。
Stretch the depth processing, improve the precision of the surface. Achieve the ultra-long, ultra-deep, and ultra-high-precision machining.
3. 沒有焊接斷裂之虞慮，強調刀頭之多變化性。縱使刀頭損壞，立即更換即上線。
Have no issue of the welding breakage. Emphasize the variability of the exchangeable endmill heads, even the exchangeable endmill head damaged, it can be replaced immediately.

產品編號 Model No.	Fig	L	M	D2	D	D1	L1	a°	價格	備註
GL06-06-060-M03	1	60	M3*0.5	3.5	6	6				
GL06-06-120-M03	1	120	M3*0.5	3.5	6	6				
GL08-08-060-M04	1	60	M4*0.7	4.5	8	8				
GL08-08-100-M04	1	100	M4*0.7	4.5	8	8				
GL08-08-120-M04	1	120	M4*0.7	4.5	8	8				
GL08-10-150-M04-DT60	2	150	M4*0.7	4.5	10	7.8	60	1°		
GL08-08-075-M05	1	75	M5*0.8	5.5	8	8				
GL08-08-100-M05	1	100	M5*0.8	5.5	8	8				
GL08-08-120-M05	1	120	M5*0.8	5.5	8	8				
GL10-10-075-M05	1	75	M5*0.8	5.5	10	10				
GL10-10-100-M05	1	100	M5*0.8	5.5	10	10				
GL10-10-150-M05	1	150	M5*0.8	5.5	10	10				
GL10-12-150-M05-DT60	2	150	M5*0.8	5.5	12	9.8	60	1°		
GL10-20-300-M05-DT135	2	300	M5*0.8	5.5	20	9.8	135	2.15°		
GL12-12-075-M06	1	75	M6*1.0	6.5	12	12				
GL12-12-100-M06	1	100	M6*1.0	6.5	12	12				
GL12-12-150-M06	1	150	M6*1.0	6.5	12	12				
GL12-12-200-M06	1	200	M6*1.0	6.5	12	12				
GL12-16-150-M06-DT70	2	150	M6*1.0	6.5	16	11.8	70	1.65°		
GL12-16-200-M06-DT90	2	200	M6*1.0	6.5	16	11.8	90	1.3°		
GL12-16-250-M06-DT115	2	250	M6*1.0	6.5	16	11.8	115	1°		
GL12-20-300-M06-DT135	2	300	M6*1.0	6.5	20	11.8	135	1.7°		
GL16-16-100-M08	1	100	M8*1.25	8.5	16	16				
GL16-16-150-M08	1	150	M8*1.25	8.5	16	16				
GL16-16-200-M08	1	200	M8*1.25	8.5	16	16				
GL16-16-250-M08	1	250	M8*1.25	8.5	16	16				
GL16-20-200-M08-DT90	2	200	M8*1.25	8.5	20	15.5	90	1.3°		
GL16-20-250-M08-DT115	2	250	M8*1.25	8.5	20	15.5	115	1°		
GL16-20-300-M08-DT135	2	300	M8*1.25	8.5	20	15.5	135	0.85°		
GL20-20-100-M10	1	100	M10*1.5	10.5	20	20				
GL20-20-150-M10	1	150	M10*1.5	10.5	20	20				
GL20-20-200-M10	1	200	M10*1.5	10.5	20	20				
GL20-20-250-M10	1	250	M10*1.5	10.5	20	20				
GL20-20-300-M10	1	300	M10*1.5	10.5	20	20				
GL20-20-400-M10	1	400	M10*1.5	10.5	20	20				
GL20-25-200-M10-DT90	2	200	M10*1.5	10.5	25	19.8	90	1.6°		
GL20-25-250-M10-DT115	2	250	M10*1.5	10.5	25	19.8	115	1.25°		
GL20-25-300-M10-DT135	2	300	M10*1.5	10.5	25	19.8	135	1.1°		

備註：其他規格，請來電洽詢。 For other specifications, please call to inquire

產品編號 Model No.	Fig	L	M	D2	D	D1	L1	a°	價格	備註
GL25-25-100-M12	1	100	M12*1.75	12.5	25	25				
GL25-25-150-M12	1	150	M12*1.75	12.5	25	25				
GL25-25-200-M12	1	200	M12*1.75	12.5	25	25				
GL25-25-250-M12	1	250	M12*1.75	12.5	25	25				
GL25-25-300-M12	1	300	M12*1.75	12.5	25	25				
GL25-25-350-M12	1	350	M12*1.75	12.5	25	25				
GL25-32-200-M12-DT90	2	200	M12*1.75	12.5	32	24.5	90	2.3°		
GL25-32-250-M12-DT115	2	250	M12*1.75	12.5	32	24.5	115	1.75°		
GL25-32-300-M12-DT135	2	300	M12*1.75	12.5	32	24.5	135	1.5°		
GL32-32-150-M16	1	150	M16*2.0	17	32	32				
GL32-32-200-M16	1	200	M16*2.0	17	32	32				
GL32-32-250-M16	1	250	M16*2.0	17	32	32				
GL32-32-300-M16	1	300	M16*2.0	17	32	32				
GL32-32-400-M16	1	400	M16*2.0	17	32	32				
GL42-42-250-M20	1	250	M20*2.5	21	42	42				
GL42-42-300-M20	1	300	M20*2.5	21	42	42				
GL42-42-400-M20	1	400	M20*2.5	21	42	42				
GL42-42-500-M20	1	500	M20*2.5	21	42	42				

備註：其他規格，請來電洽詢。 For other specifications, please call to inquire



HDC/HUC 鎢鋼後拉刀桿

Tungsten Carbide Tools Holder-HDC/HUC Collect Chuck

1. 使用高級碳化鎢材質製成，剛性優異、吸震性佳。
Made of high quality Tungsten Carbide, have excellent Stiffness and great Anti-Vibration.
2. 延長加工深度，提升加工面精度，實現超長、超深、超高精度加工之可行性。
Stretch the depth processing, improve the precision of the surface. Achieve the ultra-long, ultra-deep, and ultra-high-precision machining.
3. 降低刀具成本，延長刀具壽命。
Keep the cost down of the cutting tools, reducing production costs.

產品編號 Model No.	L	L1	D	D1	a°	Fig	價格	備註
HDC4-08-C08-100L	100		8	8		1		
HDC4-10-C10-100L	100		10	10		1		
HDC4-10-C10-150L	150		10	10		1		
HDC4-10-C12-150L-DT60	150	60	12	10	1°	2		
HDC4-10-C16-200L-DT100	200	100	16	10	1.8°	2		
HDC6-12-C12-100L	100		12	12		1		
HDC6-12-C12-150L	150		12	12		1		
HDC6-12.8-C16-150L-DT60	150	60	16	12.8	1.7°	2		
HDC6-12.8-C16-200L-DT90	200	90	16	12.8	1.2°	2		
HDC6-12.8-C20-250L-DT110	250	110	20	12.8	1.9°	2		
HDC6L-12-C12-100L	100		12	12		1		
HDC6L-12-C12-150L	150		12	12		1		
HDC6L-12.8-C16-150L-DT60	150	60	16	12.8	1.7°	2		
HDC6L-12.8-C16-200L-DT90	200	90	16	12.8	1.2°	2		
HDC6L-12.8-C20-250L-DT110	250	110	20	12.8	1.9°	2		
HUC8-16-C16-120L	120		16	16		1		
HUC8-16-C16-150L	150		16	16		1		
HUC8-16-C16-200L	200		16	16		1		
HUC8-16-C20-200L-DT80	200	80	20	16	1.5°	2		
HUC8-16-C20-250L-DT100	250	100	20	16	1.2°	2		
HUC10-20-C20-150L	150		20	20		1		
HUC10-20-C20-200L	200		20	20		1		
HUC10-20-C20-250L	250		20	20		1		
HUC10-23-C25-250L-DT120	250	120	25	23	0.5°	2		
HUC10-23-C25-300L-DT120	300	120	25	23	0.5°	2		

備註：其他規格，請來電洽詢。 For other specifications, please call to inquire

剛性優異
吸震性佳




Fig 1




Fig 2

HDC/HUC 後拉筒夾

HDC/HUC Collet Chuck

產品編號 Model No.	Collet	L	D	∅d	Fig	價格	備註
HDC4-3	HDC4	31	7	3	1		
HDC4-4	HDC4	31	7	4	1		
HDC6-3	HDC6	36	9.6	3	1		
HDC6-3.175	HDC6	36	9.6	3.175	1		
HDC6-4	HDC6	36	9.6	4	1		
HDC6-5	HDC6	36	9.6	5	1		
HDC6-6	HDC6	36	9.6	6	1		
HDCL6-3	HDCL6	60	9.6	3	2		
HDCL6-4	HDCL6	60	9.6	4	2		
HDCL6-5	HDCL6	60	9.6	5	2		
HDCL6-6	HDCL6	60	9.6	6	2		
HUC8-3	HUC8	46.2	12	3	3		
HUC8-4	HUC8	46.2	12	4	3		
HUC8-6	HUC8	46.2	12	6	3		
HUC8-8	HUC8	46.2	12	8	3		
HUC10-3	HUC10	56.5	15	3	3		
HUC10-4	HUC10	56.5	15	4	3		
HUC10-6	HUC10	56.5	15	6	3		
HUC10-8	HUC10	56.5	15	8	3		
HUC10-10	HUC10	56.5	15	10	3		

備註：其他規格，請來電洽詢。 For other specifications, please call to inquire



HDC Collet




Fig 1

HUC Collet




Fig 3

HDC6L Collet





Fig 2


GLCK 鎢鋼抗震搪刀柄

GLCK Tungsten Carbide Anti-Vibration Boring System Tool Holder

1. 使用全碳化鎢材質製成，沒有焊接斷裂之虞，剛性優異、吸震性佳。
One piece formed design of the Tungsten Carbide Tools holder, will have no issue of the welding breakage, also have excellent Stiffness and great Anti-Vibration.
2. 延長加工深度，提升搪孔加工面精度，實現超長、超深、超高精度加工之可行性。
Stretch the depth processing, improve the precision of the surface.
Achieve the ultra-long, ultra-deep, and ultra-high-precision machining.



※可搭配BIG系列搪孔頭使用※
Boring head suggest brand: BIG




鎢鋼抗震搪刀柄
GLCK TOOLHOLDER

產品編號 Model No.	L	D	GLCK	M	價格	備註
GLCK1-19-150L	150	19	GLCK1	4		
GLCK1-19-200L	200	19	GLCK1	4		
GLCK1-19-250L	250	19	GLCK1	4		
GLCK1-20-150L	150	20	GLCK1	4		
GLCK1-20-200L	200	20	GLCK1	4		
GLCK1-20-250L	250	20	GLCK1	4		
GLCK2-24-200L	200	24	GLCK2	5		
GLCK2-24-250L	250	24	GLCK2	5		
GLCK2-24-300L	300	24	GLCK2	5		
GLCK2-25-200L	200	25	GLCK2	5		
GLCK2-25-250L	250	25	GLCK2	5		
GLCK2-25-300L	300	25	GLCK2	5		
GLCK3-31-250L	250	31	GLCK3	6		
GLCK3-31-300L	300	31	GLCK3	6		
GLCK3-31-350L	350	31	GLCK3	6		
GLCK3-31-400L	400	31	GLCK3	6		
GLCK3-32-250L	250	32	GLCK3	6		
GLCK3-32-300L	300	32	GLCK3	6		
GLCK3-32-350L	350	32	GLCK3	6		
GLCK3-32-400L	400	32	GLCK3	6		
GLCK4-42-250L	250	42	GLCK4	8		★
GLCK4-42-300L	300	42	GLCK4	8		★
GLCK4-42-400L	400	42	GLCK4	8		★
GLCK4-42-500L	500	42	GLCK4	8		★


備註：不是常備庫存品，訂購前請來電洽詢。

BORING HEAD & PART
搪孔刀頭
配件


產品編號 Model No.	Dimensions.mm					Shape	Insert	Screw	Wrench	Price
	D	H	L	M	Range					
BE09A	9	7	18	M05	9~10.5	搪孔頭 BORING CUTTER HEAD	TP..0802..	MS2205A	ETF07	
BE10.5A	10.5	7	18	M05	10.5~12			MS2205A		
BE12A	12	8	23	M06	12~14			MS2205A		
BE14A	14	10	23	M06	14~16			MS2206A		
BE16A	16	10	23	M06	16~18					
BE18A	18	14	27	M10	18~20					
BE20A	20	14	27	M10	20~22					
BE22A	22	14	27	M10	22~24					
BE24A	24	14	27	M10	24~26					
BE26A	26	14	27	M10	26~28					
BE28A	28	14	27	M10	28~30					
BE30A	30	14	27	M10	30~32					
BE32A	32	14	27	M10	32~34					
BE34A	34	14	27	M10	34~36					
BE36A	36	14	27	M10	36~38					
BE38A	38	14	27	M10	38~40					
BE40A	40	14	27	M10	40~42					
BE42A	42	14	27	M10	42~44					
BE44A	44	14	27	M10	44~46					
BE46A	46	14	27	M10	46~48					
BE48A	48	14	27	M10	48~50					
BE50A	50	14	27	M10	50~52					




產品編號 Model No.	Dimensions.mm		Shape	適用鎢鋼柄 Suitable Adapters	價格 Price
	D	D1			
EC1605	16	5	套筒 COLLET ADAPTERS	SC05H-SWUBR-06	
EC1606	16	6		SC06J-SWUBR-06	
EC1608	16	8		SC08-M5-..	
EC1610	16	10		SC10-M6-..	
EC1612	16	12		SC12-M6-..	
EC1614	16	14		SC14-M6-..	




產品編號 Model No.	Dimensions.mm			Shape	適用搪刀頭 Suitable Boring Cutter Head	適用套筒 Suitable Collet	價格 Price
	D	M	L				
SC08H-M5-115	8	M5	115	鎢鋼柄搪刀桿 CARBIDE	BE09A、BE10.5A	EC1608	
SC10H-M6-115	10	M6	115		BE12A、BE14A BE16A	EC1610	
SC10H-M6-135	10	M6	135			EC1610	
SC10H-M6-160	10	M6	160			EC1610	
SC12H-M6-135	12	M6	135			EC1612	
SC12H-M6-165	12	M6	165			EC1612	
SC14H-M6-160	14	M6	160			BE14A、BE16A	EC1614
SC16H-M10-105	16	M10	105		BE18A~BE50A	—	
SC16H-M10-140	16	M10	140		BE18A~BE50A		
SC16H-M10-180	16	M10	180		BE18A~BE50A		





MPR 微型車刀 Micro Turning Cutter


Model No.	D	L	L1	R	H	F	最小孔徑 Min Aperture	刀柄	價格	備註
MPR 1.5 R0.1 L6	3.0	50	6	0.10	0.3	0.7	1.5	SIM 0020 H3		
MPR 2 R0.1 L10	3.0	50	10	0.10	0.5	0.8	2.1	SIM 0020 H3		
MPR 3 R0.1 L15	3.0	50	15	0.10	0.7	1.3	3.1	SIM 0020 H3		
MPR 4 R0.1 L22	4.0	50	22	0.10	0.8	1.7	4.1	SIM 0020 H4		
MPR 6 R0.2 L22	6.0	50	22	0.20	1.4	2.8	6.1	SIM 0020 H6		
MPR 8 R0.2 L22	8.0	60	22	0.20	1.6	3.8	8.1	SIM 0020 H8		
MPR 10 R0.2 L35	10.0	75	35	0.20	2.0	4.8	10.1	SIM 0020 H10		



MIR 微型車刀 (60° 螺紋加工)

Micro Turning Cutter(60° Thread Processing)

Model No.	D	L	L1	α	螺距		F	最小孔徑 Min Aperture	刀柄	價格	備註
					mm	牙數/英寸 Teeth / inch					
MIR 3 L15 A60	3.0	50	15	60	0.8-1.0	32-24	1.4	3.2	SIM 0020 H3		
MIR 4 L15 A60	4.0	50	15	60	0.8-1.0	32-24	1.8	4.1	SIM 0020 H4		
MIR 6 L15 A60	6.0	50	15	60	1.0-1.5	24-16	2.6	6.0	SIM 0020 H6		
MIR 8 L22 A60	8.0	60	22	60	1.0-2.0	24-13	3.6	8.0	SIM 0020 H8		



MGR 微型車刀(切槽) Micro Turning Cutter (Recessed)

Model No.	D	L	L1	R	B	H	F	最小孔徑	刀柄	價格	備註
MGR 4 B1.0 L10	4.0	50	10	0.1	1.0	1.0	1.7	4.1	SIM 0020 H4		
MGR 4 B1.5 L10	4.0	50	10	0.1	1.5	1.0	1.7	4.1	SIM 0020 H4		
MGR 6 B1.0 L15	6.0	50	15	0.1	1.0	1.4	2.8	6.1	SIM 0020 H6		
MGR 6 B1.5 L15	6.0	50	15	0.1	1.5	1.4	2.8	6.1	SIM 0020 H6		
MGR 6 B2.0 L15	6.0	50	15	0.1	2.0	1.4	2.8	6.1	SIM 0020 H6		

備註：其他規格，請來電洽詢。 For other specifications, please call to inquire


模具三寶

THREE TREASURES FOR MOLD



2 鎢鋼平底鑽頭

Tungsten Carbide Flat-Bottom Drill



單位: mm (Unit: mm)

產品編號 Model No.	刃徑 D Diameter	刃長 l Flute Length	全長 L Overall Length	柄徑 d Shank Diameter	價格 price
HQDEXZ 0100	1.0	3.3	50	6	
HQDEXZ 0110	1.1	3.5	50	6	
HQDEXZ 0120	1.2	3.9	50	6	
HQDEXZ 0130	1.3	4.2	50	6	
HQDEXZ 0140	1.4	4.6	50	6	
HQDEXZ 0150	1.5	4.9	50	6	
HQDEXZ 0160	1.6	5.2	50	6	
HQDEXZ 0170	1.7	5.5	50	6	
HQDEXZ 0180	1.8	5.8	50	6	
HQDEXZ 0190	1.9	6.2	50	6	
HQDEXZ 0200	2.0	9	50	6	
HQDEXZ 0210	2.1	11	50	6	
HQDEXZ 0220	2.2	11	50	6	
HQDEXZ 0230	2.3	11	50	6	
HQDEXZ 0240	2.4	12	50	6	
HQDEXZ 0250	2.5	12	50	6	
HQDEXZ 0260	2.6	12	50	6	
HQDEXZ 0270	2.7	14	50	6	
HQDEXZ 0280	2.8	14	50	6	
HQDEXZ 0290	2.9	14	50	6	
HQDEXZ 0300	3.0	14	60	6	
HQDEXZ 0310	3.1	15	60	6	
HQDEXZ 0320	3.2	15	60	6	
HQDEXZ 0330	3.3	15	60	6	
HQDEXZ 0340	3.4	16	60	6	
HQDEXZ 0350	3.5	16	60	6	
HQDEXZ 0360	3.6	16	60	6	
HQDEXZ 0370	3.7	18	60	6	
HQDEXZ 0380	3.8	18	60	6	
HQDEXZ 0390	3.9	18	60	6	
HQDEXZ 0400	4.0	18	60	6	
HQDEXZ 0410	4.1	19	60	6	
HQDEXZ 0420	4.2	19	60	6	
HQDEXZ 0430	4.3	19	60	6	
HQDEXZ 0440	4.4	21	60	6	
HQDEXZ 0450	4.5	21	60	6	
HQDEXZ 0460	4.6	21	60	6	
HQDEXZ 0470	4.7	22	60	6	
HQDEXZ 0480	4.8	22	60	6	
HQDEXZ 0490	4.9	22	60	6	
HQDEXZ 0500	5.0	23	75	6	
HQDEXZ 0510	5.1	24	75	6	
HQDEXZ 0520	5.2	24	75	6	
HQDEXZ 0530	5.3	24	75	6	
HQDEXZ 0540	5.4	25	75	6	
HQDEXZ 0550	5.5	25	75	6	
HQDEXZ 0560	5.6	25	75	6	
HQDEXZ 0570	5.7	27	75	6	
HQDEXZ 0580	5.8	27	75	6	
HQDEXZ 0590	5.9	27	75	6	
HQDEXZ 0600	6.0	27	75	6	
HQDEXZ 0610	6.1	28	75	8	
HQDEXZ 0620	6.2	28	75	8	
HQDEXZ 0630	6.3	28	75	8	
HQDEXZ 0640	6.4	30	75	8	
HQDEXZ 0650	6.5	30	75	8	

產品編號 Model No.	刃徑 D Diameter	刃長 l Flute Length	全長 L Overall Length	柄徑 d Shank Diameter	價格 price
HQDEXZ 0660	6.6	30	75	8	
HQDEXZ 0670	6.7	31	75	8	
HQDEXZ 0680	6.8	31	75	8	
HQDEXZ 0690	6.9	31	75	8	
HQDEXZ 0700	7.0	32	75	8	
HQDEXZ 0710	7.1	33	75	8	
HQDEXZ 0720	7.2	33	75	8	
HQDEXZ 0730	7.3	33	75	8	
HQDEXZ 0740	7.4	34	75	8	
HQDEXZ 0750	7.5	34	75	8	
HQDEXZ 0760	7.6	34	75	8	
HQDEXZ 0770	7.7	36	75	8	
HQDEXZ 0780	7.8	36	75	8	
HQDEXZ 0790	7.9	36	75	8	
HQDEXZ 0800	8.0	36	75	8	
HQDEXZ 0810	8.1	37	80	10	
HQDEXZ 0820	8.2	37	80	10	
HQDEXZ 0830	8.3	37	80	10	
HQDEXZ 0840	8.4	39	80	10	
HQDEXZ 0850	8.5	39	80	10	
HQDEXZ 0860	8.6	39	80	10	
HQDEXZ 0870	8.7	40	80	10	
HQDEXZ 0880	8.8	40	80	10	
HQDEXZ 0890	8.9	40	80	10	
HQDEXZ 0900	9.0	41	80	10	
HQDEXZ 0910	9.1	42	80	10	
HQDEXZ 0920	9.2	42	80	10	
HQDEXZ 0930	9.3	42	80	10	
HQDEXZ 0940	9.4	43	80	10	
HQDEXZ 0950	9.5	43	80	10	
HQDEXZ 0960	9.6	43	80	10	
HQDEXZ 0970	9.7	45	80	10	
HQDEXZ 0980	9.8	45	80	10	
HQDEXZ 0990	9.9	45	80	10	
HQDEXZ 1000	10.0	45	80	10	
HQDEXZ 1010	10.1	46	100	12	
HQDEXZ 1020	10.2	46	100	12	
HQDEXZ 1030	10.3	46	100	12	
HQDEXZ 1040	10.4	48	100	12	
HQDEXZ 1050	10.5	48	100	12	
HQDEXZ 1060	10.6	48	100	12	
HQDEXZ 1070	10.7	49	100	12	
HQDEXZ 1080	10.8	49	100	12	
HQDEXZ 1090	10.9	49	100	12	
HQDEXZ 1100	11.0	50	100	12	
HQDEXZ 1110	11.1	51	100	12	
HQDEXZ 1120	11.2	51	100	12	
HQDEXZ 1130	11.3	51	100	12	
HQDEXZ 1140	11.4	52	100	12	
HQDEXZ 1150	11.5	52	100	12	
HQDEXZ 1160	11.6	52	100	12	
HQDEXZ 1170	11.7	54	100	12	
HQDEXZ 1180	11.8	54	100	12	
HQDEXZ 1190	11.9	54	100	12	
HQDEXZ 1200	12.0	54	100	12	

備註: 其他規格, 請來電洽詢。 For other specifications, please call to inquire

適用材質 Work Material:

★ 最適合 Excellent ● 適合 Better ▲ 佳 Good

碳素鋼 Carbon steels	合金鋼 Alloy steel	預硬鋼材 Pre-hardened steels					高硬度鋼 High-hardened					不銹鋼 Stainless steels	鈦合金 Titanium alloys	鎳基合金 Nickel Based alloys	銅合金 Copper alloys	鋁合金 Aluminum alloys
		~HRC45	~HRC50	~HRC55	~HRC60	~HRC65										
★	★	●	●								★	●			★	★

硬質合金塗層鑽頭 Carbide Coating Drills

工業用途廣泛, 高韌性、高耐磨
High thermal crack resistance、High wear resistance

- 適用於高碳鋼、模具鋼、不鏽鋼各種加工。
- 高平滑性的鑽尖處理 & 溝槽設計對切屑分斷與排屑流暢達到鑽孔的高穩定性、長壽命。
- 單刃帶設計在鑽孔加工中取得高精度孔徑, 良好加工面。

www.hdtools.com.tw



● 水孔內冷鎢鋼鑽頭
Coolant Hole High Performance
Tungsten Carbide Drill
3D / 5D / 8D

● 泛用型加工外冷鎢鋼鑽頭
High Performance
Tungsten Carbide Drill
3D / 5D / 7D


HD.



慧德刀具五金有限公司
Hwe Der Machinery and Hardware Pty Ltd.

泛用型加工外冷鎢鋼鑽頭3D.5D.7D (SDWC R Series)

High Performance Tungsten Carbide Drill Bit-3D.5D.7D (SDWC R Series)



單位：mm (Unit : mm)

產品編號 Model No.	直徑 D	溝長 LU	柄徑 d	全長 L	價格 Price
SDWC R 3D 0200	2.0	12	3	50	
SDWC R 5D 0200	2.0	16	3	50	
SDWC R 7D 0200	2.0	25	3	57	
SDWC R 3D 0210	2.1	14	3	50	
SDWC R 5D 0210	2.1	18	3	50	
SDWC R 7D 0210	2.1	25	3	57	
SDWC R 3D 0220	2.2	14	3	50	
SDWC R 5D 0220	2.2	18	3	50	
SDWC R 7D 0220	2.2	27	3	57	
SDWC R 3D 0230	2.3	14	3	50	
SDWC R 5D 0230	2.3	18	3	50	
SDWC R 7D 0230	2.3	27	3	57	
SDWC R 3D 0240	2.4	14	3	50	
SDWC R 5D 0240	2.4	18	3	50	
SDWC R 7D 0240	2.4	32	3	62	
SDWC R 3D 0250	2.5	14	3	50	
SDWC R 5D 0250	2.5	18	3	50	
SDWC R 7D 0250	2.5	32	3	62	
SDWC R 3D 0260	2.6	16	3	50	
SDWC R 5D 0260	2.6	20	3	50	
SDWC R 7D 0260	2.6	32	3	62	
SDWC R 3D 0270	2.7	16	3	50	
SDWC R 5D 0270	2.7	20	3	50	
SDWC R 7D 0270	2.7	35	3	65	
SDWC R 3D 0280	2.8	16	3	50	
SDWC R 5D 0280	2.8	20	3	50	
SDWC R 7D 0280	2.8	35	3	65	
SDWC R 3D 0290	2.9	16	3	50	
SDWC R 5D 0290	2.9	20	3	50	
SDWC R 7D 0290	2.9	35	3	65	
SDWC R 3D 0300	3.0	16	3	50	
SDWC R 5D 0300	3.0	20	3	50	
SDWC R 7D 0300	3.0	35	3	65	

產品編號 Model No.	直徑 D	溝長 LU	柄徑 d	全長 L	價格 Price
SDWC R 3D 0310	3.1	20	4	55	
SDWC R 5D 0310	3.1	25	4	60	
SDWC R 7D 0310	3.1	38	4	69	
SDWC R 3D 0320	3.2	20	4	55	
SDWC R 5D 0320	3.2	25	4	60	
SDWC R 7D 0320	3.2	38	4	69	
SDWC R 3D 0330	3.3	20	4	55	
SDWC R 5D 0330	3.3	25	4	60	
SDWC R 7D 0330	3.3	38	4	69	
SDWC R 3D 0340	3.4	20	4	55	
SDWC R 5D 0340	3.4	25	4	60	
SDWC R 7D 0340	3.4	41	4	72	
SDWC R 3D 0350	3.5	20	4	55	
SDWC R 5D 0350	3.5	25	4	60	
SDWC R 7D 0350	3.5	41	4	72	
SDWC R 3D 0360	3.6	22	4	55	
SDWC R 5D 0360	3.6	28	4	60	
SDWC R 7D 0360	3.6	41	4	72	
SDWC R 3D 0370	3.7	22	4	55	
SDWC R 5D 0370	3.7	28	4	60	
SDWC R 7D 0370	3.7	41	4	72	
SDWC R 3D 0380	3.8	22	4	55	
SDWC R 5D 0380	3.8	28	4	60	
SDWC R 7D 0380	3.8	45	4	76	
SDWC R 3D 0390	3.9	22	4	55	
SDWC R 5D 0390	3.9	28	4	60	
SDWC R 7D 0390	3.9	45	4	76	
SDWC R 3D 0400	4.0	22	4	55	
SDWC R 5D 0400	4.0	28	4	60	
SDWC R 7D 0400	4.0	45	4	76	
SDWC R 3D 0410	4.1	24	6	62	
SDWC R 5D 0410	4.1	32	6	77	
SDWC R 7D 0410	4.1	45	6	87	

產品編號 Model No.	直徑 D	溝長 LU	柄徑 d	全長 L	價格 Price
SDWC R 3D 0420	4.2	24	6	62	
SDWC R 5D 0420	4.2	32	6	77	
SDWC R 7D 0420	4.2	45	6	87	
SDWC R 3D 0430	4.3	24	6	62	
SDWC R 5D 0430	4.3	32	6	77	
SDWC R 7D 0430	4.3	49	6	91	
SDWC R 3D 0440	4.4	24	6	62	
SDWC R 5D 0440	4.4	32	6	77	
SDWC R 7D 0440	4.4	49	6	91	
SDWC R 3D 0450	4.5	24	6	62	
SDWC R 5D 0450	4.5	32	6	77	
SDWC R 7D 0450	4.5	49	6	91	
SDWC R 3D 0460	4.6	26	6	62	
SDWC R 5D 0460	4.6	40	6	77	
SDWC R 7D 0460	4.6	49	6	91	
SDWC R 3D 0470	4.7	26	6	62	
SDWC R 5D 0470	4.7	40	6	77	
SDWC R 7D 0470	4.7	49	6	91	
SDWC R 3D 0480	4.8	26	6	62	
SDWC R 5D 0480	4.8	40	6	77	
SDWC R 7D 0480	4.8	55	6	97	
SDWC R 3D 0490	4.9	26	6	62	
SDWC R 5D 0490	4.9	40	6	77	
SDWC R 7D 0490	4.9	55	6	97	
SDWC R 3D 0500	5.0	26	6	62	
SDWC R 5D 0500	5.0	40	6	77	
SDWC R 7D 0500	5.0	55	6	97	
SDWC R 3D 0510	5.1	28	6	66	
SDWC R 5D 0510	5.1	44	6	82	
SDWC R 7D 0510	5.1	55	6	97	
SDWC R 3D 0520	5.2	28	6	66	
SDWC R 5D 0520	5.2	44	6	82	
SDWC R 7D 0520	5.2	55	6	97	
SDWC R 3D 0530	5.3	28	6	66	
SDWC R 5D 0530	5.3	44	6	82	
SDWC R 7D 0530	5.3	55	6	97	
SDWC R 3D 0540	5.4	28	6	66	
SDWC R 5D 0540	5.4	44	6	82	
SDWC R 7D 0540	5.4	60	6	102	

單位：mm (Unit : mm)

產品編號 Model No.	直徑 D	溝長 LU	柄徑 d	全長 L	價格 Price
SDWC R 3D 0550	5.5	28	6	66	
SDWC R 5D 0550	5.5	44	6	82	
SDWC R 7D 0550	5.5	60	6	102	
SDWC R 3D 0560	5.6	28	6	66	
SDWC R 5D 0560	5.6	44	6	82	
SDWC R 7D 0560	5.6	60	6	102	
SDWC R 3D 0570	5.7	28	6	66	
SDWC R 5D 0570	5.7	44	6	82	
SDWC R 7D 0570	5.7	60	6	102	
SDWC R 3D 0580	5.8	28	6	66	
SDWC R 5D 0580	5.8	44	6	82	
SDWC R 7D 0580	5.8	60	6	102	
SDWC R 3D 0590	5.9	28	6	66	
SDWC R 5D 0590	5.9	44	6	82	
SDWC R 7D 0590	5.9	60	6	102	
SDWC R 3D 0600	6.0	28	6	66	
SDWC R 5D 0600	6.0	44	6	82	
SDWC R 7D 0600	6.0	60	6	102	
SDWC R 3D 0610	6.1	34	8	79	
SDWC R 5D 0610	6.1	53	8	91	
SDWC R 7D 0610	6.1	66	8	110	
SDWC R 3D 0620	6.2	34	8	79	
SDWC R 5D 0620	6.2	53	8	91	
SDWC R 7D 0620	6.2	66	8	110	
SDWC R 3D 0630	6.3	34	8	79	
SDWC R 5D 0630	6.3	53	8	91	
SDWC R 7D 0630	6.3	66	8	110	
SDWC R 3D 0640	6.4	34	8	79	
SDWC R 5D 0640	6.4	53	8	91	
SDWC R 7D 0640	6.4	66	8	110	
SDWC R 3D 0650	6.5	34	8	79	
SDWC R 5D 0650	6.5	53	8	91	
SDWC R 7D 0650	6.5	66	8	110	
SDWC R 3D 0660	6.6	34	8	79	
SDWC R 5D 0660	6.6	53	8	91	
SDWC R 7D 0660	6.6	66	8	110	
SDWC R 3D 0670	6.7	34	8	79	
SDWC R 5D 0670	6.7	53	8	91	
SDWC R 7D 0670	6.7	66	8	110	

單位 : mm (Unit : mm)

產品編號 Model No.	直徑 D	溝長 LU	柄徑 d	全長 L	價格 Price
SDWC R 3D 0680	6.8	34	8	79	
SDWC R 5D 0680	6.8	53	8	91	
SDWC R 7D 0680	6.8	72	8	116	
SDWC R 3D 0690	6.9	34	8	79	
SDWC R 5D 0690	6.9	53	8	91	
SDWC R 7D 0690	6.9	72	8	116	
SDWC R 3D 0700	7.0	34	8	79	
SDWC R 5D 0700	7.0	53	8	91	
SDWC R 7D 0700	7.0	72	8	116	
SDWC R 3D 0710	7.1	41	8	79	
SDWC R 5D 0710	7.1	53	8	91	
SDWC R 7D 0710	7.1	72	8	116	
SDWC R 3D 0720	7.2	41	8	79	
SDWC R 5D 0720	7.2	53	8	91	
SDWC R 7D 0720	7.2	72	8	116	
SDWC R 3D 0730	7.3	41	8	79	
SDWC R 5D 0730	7.3	53	8	91	
SDWC R 7D 0730	7.3	72	8	116	
SDWC R 3D 0740	7.4	41	8	79	
SDWC R 5D 0740	7.4	53	8	91	
SDWC R 7D 0740	7.4	72	8	116	
SDWC R 3D 0750	7.5	41	8	79	
SDWC R 5D 0750	7.5	53	8	91	
SDWC R 7D 0750	7.5	72	8	116	
SDWC R 3D 0760	7.6	41	8	79	
SDWC R 5D 0760	7.6	53	8	91	
SDWC R 7D 0760	7.6	78	8	122	
SDWC R 3D 0770	7.7	41	8	79	
SDWC R 5D 0770	7.7	53	8	91	
SDWC R 7D 0770	7.7	78	8	122	
SDWC R 3D 0780	7.8	41	8	79	
SDWC R 5D 0780	7.8	53	8	91	
SDWC R 7D 0780	7.8	78	8	122	
SDWC R 3D 0790	7.9	41	8	79	
SDWC R 5D 0790	7.9	53	8	91	
SDWC R 7D 0790	7.9	78	8	122	
SDWC R 3D 0800	8.0	41	8	79	
SDWC R 5D 0800	8.0	53	8	91	
SDWC R 7D 0800	8.0	78	8	122	

產品編號 Model No.	直徑 D	溝長 LU	柄徑 d	全長 L	價格 Price
SDWC R 3D 0810	8.1	47	10	89	
SDWC R 5D 0810	8.1	61	10	103	
SDWC R 7D 0810	8.1	79	10	128	
SDWC R 3D 0820	8.2	47	10	89	
SDWC R 5D 0820	8.2	61	10	103	
SDWC R 7D 0820	8.2	79	10	128	
SDWC R 3D 0830	8.3	47	10	89	
SDWC R 5D 0830	8.3	61	10	103	
SDWC R 7D 0830	8.3	79	10	128	
SDWC R 3D 0840	8.4	47	10	89	
SDWC R 5D 0840	8.4	61	10	103	
SDWC R 7D 0840	8.4	79	10	128	
SDWC R 3D 0850	8.5	47	10	89	
SDWC R 5D 0850	8.5	61	10	103	
SDWC R 7D 0850	8.5	79	10	128	
SDWC R 3D 0860	8.6	47	10	89	
SDWC R 5D 0860	8.6	61	10	103	
SDWC R 7D 0860	8.6	85	10	134	
SDWC R 3D 0870	8.7	47	10	89	
SDWC R 5D 0870	8.7	61	10	103	
SDWC R 7D 0870	8.7	85	10	134	
SDWC R 3D 0880	8.8	47	10	89	
SDWC R 5D 0880	8.8	61	10	103	
SDWC R 7D 0880	8.8	85	10	134	
SDWC R 3D 0890	8.9	47	10	89	
SDWC R 5D 0890	8.9	61	10	103	
SDWC R 7D 0890	8.9	85	10	134	
SDWC R 3D 0900	9.0	47	10	89	
SDWC R 5D 0900	9.0	61	10	103	
SDWC R 7D 0900	9.0	85	10	134	
SDWC R 3D 0910	9.1	47	10	89	
SDWC R 5D 0910	9.1	61	10	103	
SDWC R 7D 0910	9.1	85	10	134	
SDWC R 3D 0920	9.2	47	10	89	
SDWC R 5D 0920	9.2	61	10	103	
SDWC R 7D 0920	9.2	85	10	134	
SDWC R 3D 0930	9.3	47	10	89	
SDWC R 5D 0930	9.3	61	10	103	
SDWC R 7D 0930	9.3	85	10	134	

單位 : mm (Unit : mm)

產品編號 Model No.	直徑 D	溝長 LU	柄徑 d	全長 L	價格 Price
SDWC R 3D 0940	9.4	47	10	89	
SDWC R 5D 0940	9.4	61	10	103	
SDWC R 7D 0940	9.4	85	10	134	
SDWC R 3D 0950	9.5	47	10	89	
SDWC R 5D 0950	9.5	61	10	103	
SDWC R 7D 0950	9.5	85	10	134	
SDWC R 3D 0960	9.6	47	10	89	
SDWC R 5D 0960	9.6	61	10	103	
SDWC R 7D 0960	9.6	92	10	142	
SDWC R 3D 0970	9.7	47	10	89	
SDWC R 5D 0970	9.7	61	10	103	
SDWC R 7D 0970	9.7	92	10	142	
SDWC R 3D 0980	9.8	47	10	89	
SDWC R 5D 0980	9.8	61	10	103	
SDWC R 7D 0980	9.8	92	10	142	
SDWC R 3D 0990	9.9	47	10	89	
SDWC R 5D 0990	9.9	61	10	103	
SDWC R 7D 0990	9.9	92	10	142	
SDWC R 3D 1000	10.0	47	10	89	
SDWC R 5D 1000	10.0	61	10	103	
SDWC R 7D 1000	10.0	92	10	142	
SDWC R 3D 1010	10.1	55	12	102	
SDWC R 5D 1010	10.1	71	12	118	
SDWC R 7D 1010	10.1	92	12	149	
SDWC R 3D 1020	10.2	55	12	102	
SDWC R 5D 1020	10.2	71	12	118	
SDWC R 7D 1020	10.2	92	12	149	
SDWC R 3D 1030	10.3	55	12	102	
SDWC R 5D 1030	10.3	71	12	118	
SDWC R 7D 1030	10.3	92	12	149	
SDWC R 3D 1040	10.4	55	12	102	
SDWC R 5D 1040	10.4	71	12	118	
SDWC R 7D 1040	10.4	92	12	149	
SDWC R 3D 1050	10.5	55	12	102	
SDWC R 5D 1050	10.5	71	12	118	
SDWC R 7D 1050	10.5	92	12	149	
SDWC R 3D 1060	10.6	55	12	102	
SDWC R 5D 1060	10.6	71	12	118	
SDWC R 7D 1060	10.6	92	12	149	

產品編號 Model No.	直徑 D	溝長 LU	柄徑 d	全長 L	價格 Price
SDWC R 3D 1070	10.7	55	12	102	
SDWC R 5D 1070	10.7	71	12	118	
SDWC R 7D 1070	10.7	99	12	156	
SDWC R 3D 1080	10.8	55	12	102	
SDWC R 5D 1080	10.8	71	12	118	
SDWC R 7D 1080	10.8	99	12	156	
SDWC R 3D 1090	10.9	55	12	102	
SDWC R 5D 1090	10.9	71	12	118	
SDWC R 7D 1090	10.9	99	12	156	
SDWC R 3D 1100	11.0	55	12	102	
SDWC R 5D 1100	11.0	71	12	118	
SDWC R 7D 1100	11.0	99	12	156	
SDWC R 3D 1110	11.1	55	12	102	
SDWC R 5D 1110	11.1	71	12	118	
SDWC R 7D 1110	11.1	99	12	156	
SDWC R 3D 1120	11.2	55	12	102	
SDWC R 5D 1120	11.2	71	12	118	
SDWC R 7D 1120	11.2	99	12	156	
SDWC R 3D 1130	11.3	55	12	102	
SDWC R 5D 1130	11.3	71	12	118	
SDWC R 7D 1130	11.3	99	12	156	
SDWC R 3D 1140	11.4	55	12	102	
SDWC R 5D 1140	11.4	71	12	118	
SDWC R 7D 1140	11.4	99	12	156	
SDWC R 3D 1150	11.5	55	12	102	
SDWC R 5D 1150	11.5	71	12	118	
SDWC R 7D 1150	11.5	99	12	156	
SDWC R 3D 1160	11.6	55	12	102	
SDWC R 5D 1160	11.6	71	12	118	
SDWC R 7D 1160	11.6	99	12	156	
SDWC R 3D 1170	11.7	55	12	102	
SDWC R 5D 1170	11.7	71	12	118	
SDWC R 7D 1170	11.7	99	12	156	
SDWC R 3D 1180	11.8	55	12	102	
SDWC R 5D 1180	11.8	71	12	118	
SDWC R 7D 1180	11.8	99	12	156	
SDWC R 3D 1190	11.9	55	12	102	
SDWC R 5D 1190	11.9	71	12	118	
SDWC R 7D 1190	11.9	107	12	163	

單位：mm (Unit : mm)

產品編號 Model No.	直徑 D	溝長 LU	柄徑 d	全長 L	價格 Price
SDWC R 3D 1200	12.0	55	12	102	
SDWC R 5D 1200	12.0	71	12	118	
SDWC R 7D 1200	12.0	107	12	163	
SDWC R 3D 1210	12.1	60	14	107	
SDWC R 5D 1210	12.1	79	14	138	
SDWC R 3D 1220	12.2	60	14	107	
SDWC R 5D 1220	12.2	79	14	138	
SDWC R 3D 1230	12.3	60	14	107	
SDWC R 5D 1230	12.3	79	14	138	
SDWC R 3D 1240	12.4	60	14	107	
SDWC R 5D 1240	12.4	79	14	138	
SDWC R 3D 1250	12.5	60	14	107	
SDWC R 5D 1250	12.5	79	14	138	
SDWC R 7D 1250	12.5	107	14	163	
SDWC R 3D 1260	12.6	60	14	107	
SDWC R 5D 1260	12.6	81	14	138	
SDWC R 3D 1270	12.7	60	14	107	
SDWC R 5D 1270	12.7	81	14	138	
SDWC R 3D 1280	12.8	60	14	107	
SDWC R 5D 1280	12.8	81	14	138	
SDWC R 3D 1290	12.9	60	14	107	
SDWC R 5D 1290	12.9	81	14	138	
SDWC R 3D 1300	13.0	60	14	107	
SDWC R 5D 1300	13.0	81	14	138	
SDWC R 7D 1300	13.0	107	14	163	
SDWC R 3D 1310	13.1	60	14	107	
SDWC R 5D 1310	13.1	87	14	148	
SDWC R 3D 1320	13.2	60	14	107	
SDWC R 5D 1320	13.2	87	14	148	
SDWC R 3D 1330	13.3	60	14	107	
SDWC R 5D 1330	13.3	87	14	148	
SDWC R 3D 1340	13.4	60	14	107	
SDWC R 5D 1340	13.4	87	14	148	
SDWC R 3D 1350	13.5	60	14	107	
SDWC R 5D 1350	13.5	87	14	148	
SDWC R 7D 1350	13.5	114	14	172	
SDWC R 3D 1360	13.6	60	14	107	
SDWC R 5D 1360	13.6	90	14	148	

產品編號 Model No.	直徑 D	溝長 LU	柄徑 d	全長 L	價格 Price
SDWC R 3D 1370	13.7	60	14	107	
SDWC R 5D 1370	13.7	90	14	148	
SDWC R 3D 1380	13.8	60	14	107	
SDWC R 5D 1380	13.8	90	14	148	
SDWC R 3D 1390	13.9	60	14	107	
SDWC R 5D 1390	13.9	90	14	148	
SDWC R 3D 1400	14.0	60	14	107	
SDWC R 5D 1400	14.0	90	14	148	
SDWC R 7D 1400	14.0	114	14	172	
SDWC R 3D 1410	14.1	65	16	115	
SDWC R 5D 1410	14.1	92	16	154	
SDWC R 3D 1420	14.2	65	16	115	
SDWC R 5D 1420	14.2	92	16	154	
SDWC R 3D 1430	14.3	65	16	115	
SDWC R 5D 1430	14.3	92	16	154	
SDWC R 3D 1440	14.4	65	16	115	
SDWC R 5D 1440	14.4	92	16	154	
SDWC R 3D 1450	14.5	65	16	115	
SDWC R 5D 1450	14.5	92	16	154	
SDWC R 7D 1450	14.5	120	16	177	
SDWC R 3D 1460	14.6	65	16	115	
SDWC R 5D 1460	14.6	94	16	154	
SDWC R 3D 1470	14.7	65	16	115	
SDWC R 5D 1470	14.7	94	16	154	
SDWC R 3D 1480	14.8	65	16	115	
SDWC R 5D 1480	14.8	94	16	154	
SDWC R 3D 1490	14.9	65	16	115	
SDWC R 5D 1490	14.9	94	16	154	
SDWC R 3D 1500	15.0	65	16	115	
SDWC R 5D 1500	15.0	94	16	154	
SDWC R 7D 1500	15.0	121	16	185	
SDWC R 3D 1510	15.1	65	16	115	
SDWC R 5D 1510	15.1	97	16	162	
SDWC R 3D 1520	15.2	65	16	115	
SDWC R 5D 1520	15.2	97	16	162	
SDWC R 3D 1530	15.3	65	16	115	
SDWC R 5D 1530	15.3	97	16	162	
SDWC R 3D 1540	15.4	65	16	115	
SDWC R 5D 1540	15.4	97	16	162	

單位：mm (Unit : mm)


產品編號 Model No.	直徑 D	溝長 LU	柄徑 d	全長 L	價格 Price
SDWC R 3D 1550	15.5	65	16	115	
SDWC R 5D 1550	15.5	97	16	162	
SDWC R 7D 1550	15.5	127	16	191	
SDWC R 3D 1560	15.6	65	16	115	
SDWC R 5D 1560	15.6	99	16	162	
SDWC R 3D 1570	15.7	65	16	115	
SDWC R 5D 1570	15.7	99	16	162	

產品編號 Model No.	直徑 D	溝長 LU	柄徑 d	全長 L	價格 Price
SDWC R 3D 1580	15.8	65	16	115	
SDWC R 5D 1580	15.8	99	16	162	
SDWC R 3D 1590	15.9	65	16	115	
SDWC R 5D 1590	15.9	99	16	162	
SDWC R 3D 1600	16.0	65	16	115	
SDWC R 5D 1600	16.0	99	16	162	
SDWC R 7D 1600	16.0	127	16	191	

備註：其他規格，請來電洽詢。 For other specifications, please call to inquire

水孔內冷鎢鋼鑽頭3D.5D.8D (SDWC O Series)

Coolant Hole High Performance Tungsten Carbide Drill Bit-3D.5D.8D (SDWC O Series)



單位：mm (Unit : mm)

產品編號 Model No.	直徑 D	溝長 LU	柄徑 d	全長 L	價格 Price
SDWC O 3D 0300	3.0	20	3	62	
SDWC O 5D 0300	3.0	28	3	66	
SDWC O 8D 0300	3.0	34	3	81	
SDWC O 3D 0310	3.1	20	4	62	
SDWC O 5D 0310	3.1	28	4	66	
SDWC O 8D 0310	3.1	39	4	92	
SDWC O 3D 0320	3.2	20	4	62	
SDWC O 5D 0320	3.2	28	4	66	
SDWC O 8D 0320	3.2	39	4	92	
SDWC O 3D 0330	3.3	20	4	62	
SDWC O 5D 0330	3.3	28	4	66	
SDWC O 8D 0330	3.3	39	4	92	
SDWC O 3D 0340	3.4	20	4	62	
SDWC O 5D 0340	3.4	28	4	66	
SDWC O 8D 0340	3.4	39	4	92	
SDWC O 3D 0350	3.5	20	4	62	
SDWC O 5D 0350	3.5	28	4	66	
SDWC O 8D 0350	3.5	39	4	92	
SDWC O 3D 0360	3.6	20	4	62	
SDWC O 5D 0360	3.6	28	4	66	
SDWC O 8D 0360	3.6	45	4	92	
SDWC O 3D 0370	3.7	20	4	62	
SDWC O 5D 0370	3.7	28	4	66	
SDWC O 8D 0370	3.7	45	4	92	
SDWC O 3D 0380	3.8	24	4	66	
SDWC O 5D 0380	3.8	36	4	74	
SDWC O 8D 0380	3.8	45	4	92	
SDWC O 3D 0390	3.9	24	4	66	
SDWC O 5D 0390	3.9	36	4	74	
SDWC O 8D 0390	3.9	45	4	92	
SDWC O 3D 0400	4.0	24	4	66	
SDWC O 5D 0400	4.0	36	4	74	
SDWC O 8D 0400	4.0	45	4	92	

產品編號 Model No.	直徑 D	溝長 LU	柄徑 d	全長 L	價格 Price
SDWC O 3D 0410	4.1	24	6	66	
SDWC O 5D 0410	4.1	36	6	74	
SDWC O 8D 0410	4.1	50	6	105	
SDWC O 3D 0420	4.2	24	6	66	
SDWC O 5D 0420	4.2	36	6	74	
SDWC O 8D 0420	4.2	50	6	105	
SDWC O 3D 0430	4.3	24	6	66	
SDWC O 5D 0430	4.3	36	6	74	
SDWC O 8D 0430	4.3	50	6	105	
SDWC O 3D 0440	4.4	24	6	66	
SDWC O 5D 0440	4.4	36	6	74	
SDWC O 8D 0440	4.4	50	6	105	
SDWC O 3D 0450	4.5	24	6	66	
SDWC O 5D 0450	4.5	36	6	74	
SDWC O 8D 0450	4.5	50	6	105	
SDWC O 3D 0460	4.6	24	6	66	
SDWC O 5D 0460	4.6	36	6	74	
SDWC O 8D 0460	4.6	56	6	105	
SDWC O 3D 0470	4.7	24	6	66	
SDWC O 5D 0470	4.7	36	6	74	
SDWC O 8D 0470	4.7	56	6	105	
SDWC O 3D 0480	4.8	28	6	66	
SDWC O 5D 0480	4.8	44	6	82	
SDWC O 8D 0480	4.8	56	6	105	
SDWC O 3D 0490	4.9	28	6	66	
SDWC O 5D 0490	4.9	44	6	82	
SDWC O 8D 0490	4.9	56	6	105	
SDWC O 3D 0500	5.0	28	6	66	
SDWC O 5D 0500	5.0	44	6	82	
SDWC O 8D 0500	5.0	56	6	105	
SDWC O 3D 0510	5.1	28	6	66	
SDWC O 5D 0510	5.1	44	6	82	
SDWC O 8D 0510	5.1	62	6	108	

單位：mm (Unit : mm)

產品編號 Model No.	直徑 D	溝長 LU	柄徑 d	全長 L	價格 Price
SDWC O 3D 0520	5.2	28	6	66	
SDWC O 5D 0520	5.2	44	6	82	
SDWC O 8D 0520	5.2	62	6	108	
SDWC O 3D 0530	5.3	28	6	66	
SDWC O 5D 0530	5.3	44	6	82	
SDWC O 8D 0530	5.3	62	6	108	
SDWC O 3D 0540	5.4	28	6	66	
SDWC O 5D 0540	5.4	44	6	82	
SDWC O 8D 0540	5.4	62	6	108	
SDWC O 3D 0550	5.5	28	6	66	
SDWC O 5D 0550	5.5	44	6	82	
SDWC O 8D 0550	5.5	62	6	108	
SDWC O 3D 0560	5.6	28	6	66	
SDWC O 5D 0560	5.6	44	6	82	
SDWC O 8D 0560	5.6	68	6	108	
SDWC O 3D 0570	5.7	28	6	66	
SDWC O 5D 0570	5.7	44	6	82	
SDWC O 8D 0570	5.7	68	6	108	
SDWC O 3D 0580	5.8	28	6	66	
SDWC O 5D 0580	5.8	44	6	82	
SDWC O 8D 0580	5.8	68	6	108	
SDWC O 3D 0590	5.9	28	6	66	
SDWC O 5D 0590	5.9	44	6	82	
SDWC O 8D 0590	5.9	68	6	108	
SDWC O 3D 0600	6.0	28	6	66	
SDWC O 5D 0600	6.0	44	6	82	
SDWC O 8D 0600	6.0	68	6	108	
SDWC O 3D 0610	6.1	36	8	81	
SDWC O 5D 0610	6.1	55	8	93	
SDWC O 8D 0610	6.1	68	8	108	
SDWC O 3D 0620	6.2	36	8	81	
SDWC O 5D 0620	6.2	55	8	93	
SDWC O 8D 0620	6.2	68	8	108	
SDWC O 3D 0630	6.3	36	8	81	
SDWC O 5D 0630	6.3	55	8	93	
SDWC O 8D 0630	6.3	68	8	108	
SDWC O 3D 0640	6.4	36	8	81	
SDWC O 5D 0640	6.4	55	8	93	
SDWC O 8D 0640	6.4	68	8	108	

產品編號 Model No.	直徑 D	溝長 LU	柄徑 d	全長 L	價格 Price
SDWC O 3D 0650	6.5	36	8	81	
SDWC O 5D 0650	6.5	55	8	93	
SDWC O 8D 0650	6.5	68	8	108	
SDWC O 3D 0660	6.6	36	8	81	
SDWC O 5D 0660	6.6	55	8	93	
SDWC O 8D 0660	6.6	68	8	108	
SDWC O 3D 0670	6.7	36	8	81	
SDWC O 5D 0670	6.7	55	8	93	
SDWC O 8D 0670	6.7	68	8	108	
SDWC O 3D 0680	6.8	36	8	81	
SDWC O 5D 0680	6.8	55	8	93	
SDWC O 8D 0680	6.8	68	8	108	
SDWC O 3D 0690	6.9	36	8	81	
SDWC O 5D 0690	6.9	55	8	93	
SDWC O 8D 0690	6.9	78	8	118	
SDWC O 3D 0700	7.0	36	8	81	
SDWC O 5D 0700	7.0	55	8	93	
SDWC O 8D 0700	7.0	78	8	118	
SDWC O 3D 0710	7.1	43	8	81	
SDWC O 5D 0710	7.1	55	8	93	
SDWC O 8D 0710	7.1	78	8	118	
SDWC O 3D 0720	7.2	43	8	81	
SDWC O 5D 0720	7.2	55	8	93	
SDWC O 8D 0720	7.2	78	8	118	
SDWC O 3D 0730	7.3	43	8	81	
SDWC O 5D 0730	7.3	55	8	93	
SDWC O 8D 0730	7.3	78	8	118	
SDWC O 3D 0740	7.4	43	8	81	
SDWC O 5D 0740	7.4	55	8	93	
SDWC O 8D 0740	7.4	78	8	118	
SDWC O 3D 0750	7.5	43	8	81	
SDWC O 5D 0750	7.5	55	8	93	
SDWC O 8D 0750	7.5	78	8	118	
SDWC O 3D 0760	7.6	43	8	81	
SDWC O 5D 0760	7.6	55	8	93	
SDWC O 8D 0760	7.6	78	8	118	
SDWC O 3D 0770	7.7	43	8	81	
SDWC O 5D 0770	7.7	55	8	93	
SDWC O 8D 0770	7.7	78	8	118	

單位：mm (Unit : mm)

產品編號 Model No.	直徑 D	溝長 LU	柄徑 d	全長 L	價格 Price
SDWC O 3D 0780	7.8	43	8	81	
SDWC O 5D 0780	7.8	55	8	93	
SDWC O 8D 0780	7.8	78	8	118	
SDWC O 3D 0790	7.9	43	8	81	
SDWC O 5D 0790	7.9	55	8	93	
SDWC O 8D 0790	7.9	78	8	118	
SDWC O 3D 0800	8.0	43	8	81	
SDWC O 5D 0800	8.0	55	8	93	
SDWC O 8D 0800	8.0	78	8	118	
SDWC O 3D 0810	8.1	47	10	89	
SDWC O 5D 0810	8.1	61	10	103	
SDWC O 8D 0810	8.1	87	10	131	
SDWC O 3D 0820	8.2	47	10	89	
SDWC O 5D 0820	8.2	61	10	103	
SDWC O 8D 0820	8.2	87	10	131	
SDWC O 3D 0830	8.3	47	10	89	
SDWC O 5D 0830	8.3	61	10	103	
SDWC O 8D 0830	8.3	87	10	131	
SDWC O 3D 0840	8.4	47	10	89	
SDWC O 5D 0840	8.4	61	10	103	
SDWC O 8D 0840	8.4	87	10	131	
SDWC O 3D 0850	8.5	47	10	89	
SDWC O 5D 0850	8.5	61	10	103	
SDWC O 8D 0850	8.5	87	10	131	
SDWC O 3D 0860	8.6	47	10	89	
SDWC O 5D 0860	8.6	61	10	103	
SDWC O 8D 0860	8.6	87	10	131	
SDWC O 3D 0870	8.7	47	10	89	
SDWC O 5D 0870	8.7	61	10	103	
SDWC O 8D 0870	8.7	87	10	131	
SDWC O 3D 0880	8.8	47	10	89	
SDWC O 5D 0880	8.8	61	10	103	
SDWC O 8D 0880	8.8	87	10	131	
SDWC O 3D 0890	8.9	47	10	89	
SDWC O 5D 0890	8.9	61	10	103	
SDWC O 8D 0890	8.9	87	10	131	
SDWC O 3D 0900	9.0	47	10	89	
SDWC O 5D 0900	9.0	61	10	103	
SDWC O 8D 0900	9.0	87	10	131	

產品編號 Model No.	直徑 D	溝長 LU	柄徑 d	全長 L	價格 Price
SDWC O 3D 0910	9.1	47	10	89	
SDWC O 5D 0910	9.1	61	10	103	
SDWC O 8D 0910	9.1	95	10	139	
SDWC O 3D 0920	9.2	47	10	89	
SDWC O 5D 0920	9.2	61	10	103	
SDWC O 8D 0920	9.2	95	10	139	
SDWC O 3D 0930	9.3	47	10	89	
SDWC O 5D 0930	9.3	61	10	103	
SDWC O 8D 0930	9.3	95	10	139	
SDWC O 3D 0940	9.4	47	10	89	
SDWC O 5D 0940	9.4	61	10	103	
SDWC O 8D 0940	9.4	95	10	139	
SDWC O 3D 0950	9.5	47	10	89	
SDWC O 5D 0950	9.5	61	10	103	
SDWC O 8D 0950	9.5	95	10	139	
SDWC O 3D 0960	9.6	47	10	89	
SDWC O 5D 0960	9.6	61	10	103	
SDWC O 8D 0960	9.6	95	10	139	
SDWC O 3D 0970	9.7	47	10	89	
SDWC O 5D 0970	9.7	61	10	103	
SDWC O 8D 0970	9.7	95	10	139	
SDWC O 3D 0980	9.8	47	10	89	
SDWC O 5D 0980	9.8	61	10	103	
SDWC O 8D 0980	9.8	95	10	139	
SDWC O 3D 0990	9.9	47	10	89	
SDWC O 5D 0990	9.9	61	10	103	
SDWC O 8D 0990	9.9	95	10	139	
SDWC O 3D 1000	10.0	47	10	89	
SDWC O 5D 1000	10.0	61	10	103	
SDWC O 8D 1000	10.0	95	10	139	
SDWC O 3D 1010	10.1	55	12	102	
SDWC O 5D 1010	10.1	71	12	118	
SDWC O 8D 1010	10.1	106	12	155	
SDWC O 3D 1020	10.2	55	12	102	
SDWC O 5D 1020	10.2	71	12	118	
SDWC O 8D 1020	10.2	106	12	155	
SDWC O 3D 1030	10.3	55	12	102	
SDWC O 5D 1030	10.3	71	12	118	
SDWC O 8D 1030	10.3	106	12	155	

單位：mm (Unit : mm)

產品編號 Model No.	直徑 D	溝長 LU	柄徑 d	全長 L	價格 Price
SDWC O 3D 1040	10.4	55	12	102	
SDWC O 5D 1040	10.4	71	12	118	
SDWC O 8D 1040	10.4	106	12	155	
SDWC O 3D 1050	10.5	55	12	102	
SDWC O 5D 1050	10.5	71	12	118	
SDWC O 8D 1050	10.5	106	12	155	
SDWC O 3D 1060	10.6	55	12	102	
SDWC O 5D 1060	10.6	71	12	118	
SDWC O 8D 1060	10.6	106	12	155	
SDWC O 3D 1070	10.7	55	12	102	
SDWC O 5D 1070	10.7	71	12	118	
SDWC O 8D 1070	10.7	106	12	155	
SDWC O 3D 1080	10.8	55	12	102	
SDWC O 5D 1080	10.8	71	12	118	
SDWC O 8D 1080	10.8	106	12	155	
SDWC O 3D 1090	10.9	55	12	102	
SDWC O 5D 1090	10.9	71	12	118	
SDWC O 8D 1090	10.9	106	12	155	
SDWC O 3D 1100	11.0	55	12	102	
SDWC O 5D 1100	11.0	71	12	118	
SDWC O 8D 1100	11.0	106	12	155	
SDWC O 3D 1110	11.1	55	12	102	
SDWC O 5D 1110	11.1	71	12	118	
SDWC O 8D 1110	11.1	114	12	163	
SDWC O 3D 1120	11.2	55	12	102	
SDWC O 5D 1120	11.2	71	12	118	
SDWC O 8D 1120	11.2	114	12	163	
SDWC O 3D 1130	11.3	55	12	102	
SDWC O 5D 1130	11.3	71	12	118	
SDWC O 8D 1130	11.3	114	12	163	
SDWC O 3D 1140	11.4	55	12	102	
SDWC O 5D 1140	11.4	71	12	118	
SDWC O 8D 1140	11.4	114	12	163	
SDWC O 3D 1150	11.5	55	12	102	
SDWC O 5D 1150	11.5	71	12	118	
SDWC O 8D 1150	11.5	114	12	163	
SDWC O 3D 1160	11.6	55	12	102	
SDWC O 5D 1160	11.6	71	12	118	
SDWC O 8D 1160	11.6	114	12	163	

產品編號 Model No.	直徑 D	溝長 LU	柄徑 d	全長 L	價格 Price
SDWC O 3D 1170	11.7	55	12	102	
SDWC O 5D 1170	11.7	71	12	118	
SDWC O 8D 1170	11.7	114	12	163	
SDWC O 3D 1180	11.8	55	12	102	
SDWC O 5D 1180	11.8	71	12	118	
SDWC O 8D 1180	11.8	114	12	163	
SDWC O 3D 1190	11.9	55	12	102	
SDWC O 5D 1190	11.9	71	12	118	
SDWC O 8D 1190	11.9	114	12	163	
SDWC O 3D 1200	12.0	55	12	102	
SDWC O 5D 1200	12.0	71	12	118	
SDWC O 8D 1200	12.0	114	12	163	
SDWC O 3D 1210	12.1	60	14	107	
SDWC O 5D 1210	12.1	77	14	124	
SDWC O 8D 1210	12.1	133	14	182	
SDWC O 3D 1220	12.2	60	14	107	
SDWC O 5D 1220	12.2	77	14	124	
SDWC O 8D 1220	12.2	133	14	182	
SDWC O 3D 1230	12.3	60	14	107	
SDWC O 5D 1230	12.3	77	14	124	
SDWC O 8D 1230	12.3	133	14	182	
SDWC O 3D 1240	12.4	60	14	107	
SDWC O 5D 1240	12.4	77	14	124	
SDWC O 8D 1240	12.4	133	14	182	
SDWC O 3D 1250	12.5	60	14	107	
SDWC O 5D 1250	12.5	77	14	124	
SDWC O 8D 1250	12.5	133	14	182	
SDWC O 3D 1260	12.6	60	14	107	
SDWC O 5D 1260	12.6	77	14	124	
SDWC O 8D 1260	12.6	133	14	182	
SDWC O 3D 1270	12.7	60	14	107	
SDWC O 5D 1270	12.7	77	14	124	
SDWC O 8D 1270	12.7	133	14	182	
SDWC O 3D 1280	12.8	60	14	107	
SDWC O 5D 1280	12.8	77	14	124	
SDWC O 8D 1280	12.8	133	14	182	
SDWC O 3D 1290	12.9	60	14	107	
SDWC O 5D 1290	12.9	77	14	124	
SDWC O 8D 1290	12.9	133	14	182	

單位：mm (Unit : mm)

產品編號 Model No.	直徑 D	溝長 LU	柄徑 d	全長 L	價格 Price
SDWC O 3D 1300	13.0	60	14	107	
SDWC O 5D 1300	13.0	77	14	124	
SDWC O 8D 1300	13.0	133	14	182	
SDWC O 3D 1310	13.1	60	14	107	
SDWC O 5D 1310	13.1	77	14	124	
SDWC O 8D 1310	13.1	133	14	182	
SDWC O 3D 1320	13.2	60	14	107	
SDWC O 5D 1320	13.2	77	14	124	
SDWC O 8D 1320	13.2	133	14	182	
SDWC O 3D 1330	13.3	60	14	107	
SDWC O 5D 1330	13.3	77	14	124	
SDWC O 8D 1330	13.3	133	14	182	
SDWC O 3D 1340	13.4	60	14	107	
SDWC O 5D 1340	13.4	77	14	124	
SDWC O 8D 1340	13.4	133	14	182	
SDWC O 3D 1350	13.5	60	14	107	
SDWC O 5D 1350	13.5	77	14	124	
SDWC O 8D 1350	13.5	133	14	182	
SDWC O 3D 1360	13.6	60	14	107	
SDWC O 5D 1360	13.6	77	14	124	
SDWC O 8D 1360	13.6	133	14	182	
SDWC O 3D 1370	13.7	60	14	107	
SDWC O 5D 1370	13.7	77	14	124	
SDWC O 8D 1370	13.7	133	14	182	
SDWC O 3D 1380	13.8	60	14	107	
SDWC O 5D 1380	13.8	77	14	124	
SDWC O 8D 1380	13.8	133	14	182	
SDWC O 3D 1390	13.9	60	14	107	
SDWC O 5D 1390	13.9	77	14	124	
SDWC O 8D 1390	13.9	133	14	182	
SDWC O 3D 1400	14.0	60	14	107	
SDWC O 5D 1400	14.0	77	14	124	
SDWC O 8D 1400	14.0	133	14	182	
SDWC O 3D 1410	14.1	65	16	115	
SDWC O 5D 1410	14.1	83	16	133	
SDWC O 8D 1410	14.1	152	16	204	
SDWC O 3D 1420	14.2	65	16	115	
SDWC O 5D 1420	14.2	83	16	133	
SDWC O 8D 1420	14.2	152	16	204	

產品編號 Model No.	直徑 D	溝長 LU	柄徑 d	全長 L	價格 Price
SDWC O 3D 1430	14.3	65	16	115	
SDWC O 5D 1430	14.3	83	16	133	
SDWC O 8D 1430	14.3	152	16	204	
SDWC O 3D 1440	14.4	65	16	115	
SDWC O 5D 1440	14.4	83	16	133	
SDWC O 8D 1440	14.4	152	16	204	
SDWC O 3D 1450	14.5	65	16	115	
SDWC O 5D 1450	14.5	83	16	133	
SDWC O 8D 1450	14.5	152	16	204	
SDWC O 3D 1460	14.6	65	16	115	
SDWC O 5D 1460	14.6	83	16	133	
SDWC O 8D 1460	14.6	152	16	204	
SDWC O 3D 1470	14.7	65	16	115	
SDWC O 5D 1470	14.7	83	16	133	
SDWC O 8D 1470	14.7	152	16	204	
SDWC O 3D 1480	14.8	65	16	115	
SDWC O 5D 1480	14.8	83	16	133	
SDWC O 8D 1480	14.8	152	16	204	
SDWC O 3D 1490	14.9	65	16	115	
SDWC O 5D 1490	14.9	83	16	133	
SDWC O 8D 1490	14.9	152	16	204	
SDWC O 3D 1500	15.0	65	16	115	
SDWC O 5D 1500	15.0	83	16	133	
SDWC O 8D 1500	15.0	152	16	204	
SDWC O 3D 1510	15.1	65	16	115	
SDWC O 5D 1510	15.1	83	16	133	
SDWC O 8D 1510	15.1	152	16	204	
SDWC O 3D 1520	15.2	65	16	115	
SDWC O 5D 1520	15.2	83	16	133	
SDWC O 8D 1520	15.2	152	16	204	
SDWC O 3D 1530	15.3	65	16	115	
SDWC O 5D 1530	15.3	83	16	133	
SDWC O 8D 1530	15.3	152	16	204	
SDWC O 3D 1540	15.4	65	16	115	
SDWC O 5D 1540	15.4	83	16	133	
SDWC O 8D 1540	15.4	152	16	204	
SDWC O 3D 1550	15.5	65	16	115	
SDWC O 5D 1550	15.5	83	16	133	
SDWC O 8D 1550	15.5	152	16	204	

單位：mm (Unit : mm)

產品編號 Model No.	直徑 D	溝長 LU	柄徑 d	全長 L	價格 Price
SDWC O 3D 1560	15.6	65	16	115	
SDWC O 5D 1560	15.6	83	16	133	
SDWC O 8D 1560	15.6	152	16	204	
SDWC O 3D 1570	15.7	65	16	115	
SDWC O 5D 1570	15.7	83	16	133	
SDWC O 8D 1570	15.7	152	16	204	
SDWC O 3D 1580	15.8	65	16	115	
SDWC O 5D 1580	15.8	83	16	133	
SDWC O 8D 1580	15.8	152	16	204	


備註：其他規格，請來電洽詢。 For other specifications, please call to inquire

產品編號 Model No.	直徑 D	溝長 LU	柄徑 d	全長 L	價格 Price
SDWC O 3D 1590	15.9	65	16	115	
SDWC O 5D 1590	15.9	83	16	133	
SDWC O 8D 1590	15.9	152	16	204	
SDWC O 3D 1600	16.0	65	16	115	
SDWC O 5D 1600	16.0	83	16	133	
SDWC O 8D 1600	16.0	152	16	204	

錫鋼直柄短刃鑽頭

Solid Carbide Straight Shank Drills

頂角：φ 1~φ 6=120°
Top Angle φ 6.1~φ 13=140°



單位：mm (Unit : mm)

刃徑 D Diameter	溝長 Le Ditch Length	全長 L Overall Length	價格 Price
1.0	6	26	
1.1	7	28	
1.2	8	30	
1.3	8	30	
1.4	9	32	
1.5	9	32	
1.6	10	34	
1.7	10	34	
1.8	11	36	
1.9	11	36	
2.0	12	38	
2.1	12	38	
2.2	13	40	
2.3	13	40	
2.4	14	43	
2.5	14	43	
2.6	14	43	
2.7	16	46	
2.8	16	46	
2.9	16	46	
3.0	16	46	
3.1	18	49	
3.2	18	49	
3.3	18	49	
3.4	20	52	
3.5	20	52	
3.6	20	52	
3.7	20	52	
3.8	22	55	
3.9	22	55	
4.0	22	55	
4.1	22	55	
4.2	22	55	
4.3	24	58	
4.4	24	58	
4.5	24	58	
4.6	24	58	
4.7	24	58	
4.8	26	62	
4.9	26	62	
5.0	26	62	


刃徑 D Diameter	溝長 Le Ditch Length	全長 L Overall Length	價格 Price
5.1	26	62	
5.2	26	62	
5.3	26	62	
5.4	28	66	
5.5	28	66	
5.6	28	66	
5.7	28	66	
5.8	28	66	
5.9	28	66	
6.0	28	66	
6.1	31	70	
6.2	31	70	
6.3	31	70	
6.4	31	70	
6.5	31	70	
6.6	31	70	
6.7	31	70	
6.8	34	74	
6.9	34	74	
7.0	34	74	
7.1	34	74	
7.2	34	74	
7.3	34	74	
7.4	34	74	
7.5	34	74	
7.6	37	79	
7.7	37	79	
7.8	37	79	
7.9	37	79	
8.0	37	79	
8.1	37	79	
8.2	37	79	
8.3	37	79	
8.4	37	79	
8.5	37	79	
8.6	40	84	
8.7	40	84	
8.8	40	84	
8.9	40	84	
9.0	40	84	

刃徑 D Diameter	溝長 Le Ditch Length	全長 L Overall Length	價格 Price
9.1	40	84	
9.2	40	84	
9.3	40	84	
9.4	40	84	
9.5	40	84	
9.6	43	89	
9.7	43	89	
9.8	43	89	
9.9	43	89	
10.0	43	89	
10.1	43	89	
10.2	43	89	
10.3	43	89	
10.4	43	89	
10.5	43	89	
10.6	43	89	
10.7	47	95	
10.8	47	95	
10.9	47	95	
11.0	47	95	
11.1	47	95	
11.2	47	95	
11.3	47	95	
11.4	47	95	
11.5	47	95	
11.6	47	95	
11.7	47	95	
11.8	47	95	
11.9	51	102	
12.0	51	102	
12.1	51	102	
12.2	51	102	
12.3	51	102	
12.4	51	102	
12.5	51	102	
12.6	51	102	
12.7	51	102	
12.8	51	102	
12.9	51	102	
13.0	51	102	

錫鋼直柄長刃鑽頭

Solid Carbide Long Flute Straight Shank Drills

頂角：φ 1~φ 6=120°
Top Angle φ 6.1~φ 13=140°



單位：mm (Unit : mm)

刃徑 D Diameter	溝長 Le Ditch Length	全長 L Overall Length	價格 Price
1.0	12	34	
1.1	12	36	
1.2	16	38	
1.3	16	38	
1.4	18	40	
1.5	18	40	
1.6	20	43	
1.7	20	43	
1.8	22	46	
1.9	22	46	
2.0	24	49	
2.1	24	49	
2.2	27	53	
2.3	27	53	
2.4	30	57	
2.5	30	57	
2.6	30	57	
2.7	33	61	
2.8	33	61	
2.9	33	61	
3.0	33	61	
3.1	36	65	
3.2	36	65	
3.3	36	65	
3.4	39	70	
3.5	39	70	
3.6	39	70	
3.7	39	70	
3.8	43	75	
3.9	43	75	
4.0	43	75	
4.1	43	75	
4.2	43	75	
4.3	47	80	
4.4	47	80	
4.5	47	80	
4.6	47	80	
4.7	47	80	
4.8	52	86	
4.9	52	86	
5.0	52	86	

刃徑 D Diameter	溝長 Le Ditch Length	全長 L Overall Length	價格 Price
5.1	52	86	
5.2	52	86	
5.3	52	86	
5.4	57	93	
5.5	57	93	
5.6	57	93	
5.7	57	93	
5.8	57	93	
5.9	57	93	
6.0	57	93	
6.1	63	101	
6.2	63	101	
6.3	63	101	
6.4	63	101	
6.5	63	101	
6.6	63	101	
6.7	63	101	
6.8	69	109	
6.9	69	109	
7.0	69	109	
7.1	69	109	
7.2	69	109	
7.3	69	109	
7.4	69	109	
7.5	69	109	
7.6	75	117	
7.7	75	117	
7.8	75	117	
7.9	75	117	
8.0	75	117	
8.1	75	117	
8.2	75	117	
8.3	75	117	
8.4	75	117	
8.5	75	117	
8.6	75	125	
8.7	75	125	
8.8	75	125	
8.9	75	125	
9.0	75	125	

刃徑 D Diameter	溝長 Le Ditch Length	全長 L Overall Length	價格 Price
9.1	75	125	
9.2	75	125	
9.3	75	125	
9.4	75	125	
9.5	75	125	
9.6	80	133	
9.7	80	133	
9.8	80	133	
9.9	80	133	
10.0	80	133	
10.1	80	133	
10.2	80	133	
10.3	80	133	
10.4	80	133	
10.5	80	133	
10.6	80	133	
10.7	80	142	
10.8	80	142	
10.9	80	142	
11.0	80	142	
11.1	80	142	
11.2	80	142	
11.3	80	142	
11.4	80	142	
11.5	80	142	
11.6	80	142	
11.7	80	142	
11.8	80	142	
11.9	80	151	
12.0	80	151	
12.1	80	151	
12.2	80	151	
12.3	80	151	
12.4	80	151	
12.5	80	151	
12.6	80	151	
12.7	80	151	
12.8	80	151	
12.9	80	151	
13.0	80	151	

錫鋼鑽頭、鉸刀


錫鋼鑽頭、鉸刀

鎢鋼直柄機械鉸刀

Solid Carbide Straight Shank Machine Reamers

左旋右刃：7°

刃徑公差：+0.002~+0.008



單位：mm (Unit : mm)

刃徑 D Diameter	刃長 L1 Flute Length	有效長 L2 Effective Length	刃數 T Teeth	全長 L Overall Length	價格 Price
2	11	24	4	49	
2.1	11	24	4	49	
2.2	12	26	4	53	
2.3	12	26	4	53	
2.4	14	28	4	57	
2.5	14	28	4	57	
2.6	14	28	4	57	
2.7	15	32	4	61	
2.8	15	32	4	61	
2.9	15	32	4	61	
3	15	32	4	61	
3.1	16	35	4	65	
3.2	16	35	4	65	
3.3	16	35	4	65	
3.4	18	40	4	70	
3.5	18	40	4	70	
3.6	18	40	4	70	
3.7	18	40	4	70	
3.8	19	43	4	75	
3.9	19	43	4	75	
4	19	43	4	75	
4.1	19	43	4	75	
4.2	19	43	4	75	
4.3	21	47	4	80	
4.4	21	47	4	80	
4.5	21	47	4	80	
4.6	21	47	4	80	
4.7	21	47	4	80	
4.8	23	52	4	86	
4.9	23	52	4	86	
5	23	52	4	86	
5.1	23	52	4	86	
5.2	23	52	4	86	
5.3	23	52	4	86	
5.4	26	57	4	93	
5.5	26	57	4	93	
5.6	26	57	4	93	
5.7	26	57	4	93	
5.8	26	57	4	93	
5.9	26	57	4	93	


刃徑 D Diameter	刃長 L1 Flute Length	有效長 L2 Effective Length	刃數 T Teeth	全長 L Overall Length	價格 Price
6	26	57	6	93	
6.1	28	63	6	101	
6.2	28	63	6	101	
6.3	28	63	6	101	
6.4	28	63	6	101	
6.5	28	63	6	101	
6.6	28	63	6	101	
6.7	28	63	6	101	
6.8	31	69	6	109	
6.9	31	69	6	109	
7	31	69	6	109	
7.1	31	69	6	109	
7.2	31	69	6	109	
7.3	31	69	6	109	
7.4	31	69	6	109	
7.5	31	69	6	109	
7.6	33	75	6	117	
7.7	33	75	6	117	
7.8	33	75	6	117	
7.9	33	75	6	117	
8	33	75	6	117	
8.1	33	75	6	117	
8.2	33	75	6	117	
8.3	33	75	6	117	
8.4	33	75	6	117	
8.5	33	75	6	117	
8.6	36	81	6	125	
8.7	36	81	6	125	
8.8	36	81	6	125	
8.9	36	81	6	125	
9	36	81	6	125	
9.1	36	81	6	125	
9.2	36	81	6	125	
9.3	36	81	6	125	
9.4	36	81	6	125	
9.5	36	81	6	125	
9.6	38	87	6	133	
9.7	38	87	6	133	
9.8	38	87	6	133	
9.9	38	87	6	133	

鎢鋼直柄機械鉸刀

Solid Carbide Straight Shank Machine Reamers

左旋右刃：7°

刃徑公差：+0.002~+0.008



單位：mm (Unit : mm)

刃徑 D Diameter	刃長 L1 Flute Length	有效長 L2 Effective Length	刃數 T Teeth	全長 L Overall Length	價格 Price
10	38	87	6	133	
10.1	38	87	6	133	
10.2	38	87	6	133	
10.3	38	87	6	133	
10.4	38	87	6	133	
10.5	38	87	6	133	
10.6	38	87	6	133	
10.7	41	96	6	142	
10.8	41	96	6	142	
10.9	41	96	6	142	
11	41	96	6	142	
11.1	41	96	6	142	
11.2	41	96	6	142	
11.3	41	96	6	142	
11.4	41	96	6	142	
11.5	41	96	6	142	
11.6	41	96	6	142	
11.7	41	96	6	142	
11.8	41	96	6	142	
11.9	44	105	6	151	


刃徑 D Diameter	刃長 L1 Flute Length	有效長 L2 Effective Length	刃數 T Teeth	全長 L Overall Length	價格 Price
12	44	105	6	151	
12.1	44	105	6	151	
12.2	44	105	6	151	
12.3	44	105	6	151	
12.4	44	105	6	151	
12.5	44	105	6	151	
12.6	44	105	6	151	
12.7	44	105	6	151	
12.8	44	105	6	151	
12.9	44	105	6	151	
13	44	105	6	151	
14	44	105	6	151	
15	44	105	6	151	
16	44	105	6	151	

鎢鋼直柄機械鉸刀(加長型)

Tungsten Carbide Machine Reamer(Long Shank)

左旋右刃：7° 刃徑公差：+0.002~+0.008

★刃徑以0.01為單位



單位：mm (Unit : mm)


刃徑 D Diameter	刃長 L1 Flute Length	有效長 L2 Effective Length	刃數 T Teeth	全長 L Overall Length	價格 Price	備註
3	15	32	4	100		
4	19	43	4	120		
5	23	52	4	132		
6	26	57	6	150		
7	31	69	6	150		
8	33	75	6	150		
9	36	81	6	180		
10	38	87	6	180		

鎢鋼鑽頭、鉸刀

鎢鋼鑽頭、鉸刀

鎢鋼直柄機械鉸刀(精密型)

Tungsten Carbide Machine Reamer(Micro Decimal Diameter)



左旋右刃：7° 刃徑公差：+0.003~+0.005


★刃徑以0.01為單位

單位：mm (Unit : mm)

刃徑 D Diameter	刃長 L1 Flute Length	有效長 L2 Effective Length	刃數 T Teeth	全長 L Overall Length	價格 Price	備註
1.95 ~ 1.99	11	24	4	49		
2.95 ~ 2.99	15	32	4	61		
3.95 ~ 3.99	19	43	4	75		
4.95 ~ 4.99	23	52	4	86		
5.95 ~ 5.99	26	57	6	93		
6.95 ~ 6.99	31	69	6	109		
7.95 ~ 7.99	33	75	6	117		
8.95 ~ 8.99	36	81	6	125		
9.95 ~ 9.99	38	87	6	133		
10.95 ~ 10.99	41	96	6	142		
11.95 ~ 11.99	44	105	6	151		
12.95 ~ 12.99	44	105	6	151		

鎢鋼機械鉸刀銑刀柄

Solid Carbide Machine Reamers



左旋右刃：7°

刃徑公差：+0.003~+0.005


※刃徑以0.01為最小單位

單位：mm (Unit : mm)

刃徑 D Diameter	刃長 L1 Flute Length	有效長 L2 Effective Length	柄徑 d Shank Diameter	刃數 T Teeth	全長 L Overall Length	價格 Price	備註
1.5	8	18	3	4	50		
1.6	9	20	3	4	50		
1.7	9	20	3	4	50		
1.8	10	22	3	4	50		
1.9	10	22	3	4	50		

HSS 高速鋼星型六角起子頭

HSS High Speed Steel TORX Professional Bit



單位：mm (Unit : mm)

產品編號 Model No.		長度 l Length	柄徑 D Handle Diameter	全長 L Overall Length	價格 Price	備註 Note
FYW02T06BIT	T06	22.5	6.35 (1/4")	55		
FYW02T07BIT	T07	22.5	6.35 (1/4")	55		
FYW02T08BIT	T08	22.5	6.35 (1/4")	55		
FYW02T09BIT	T09	22.5	6.35 (1/4")	55		
FYW02T10BIT	T10	22.5	6.35 (1/4")	55		
FYW02T15BIT	T15	22.5	6.35 (1/4")	55		
FYW02T20BIT	T20	22.5	6.35 (1/4")	55		
FY520 Handle	—	—	—	—		

HSS 高速鋼十字起子頭

HSS High Speed Steel Phillips Professional Bit




單位：mm (Unit : mm)

產品編號 Model No.		l x d	柄徑 D Handle Diameter	全長 L Overall Length	價格 Price	備註 Note
FYW02PH00BIT	PH00	45 x 2.0	6.35 (1/4")	78		
FYW02PH0BIT	PH0	62 x 3.0	6.35 (1/4")	92		
FYW02PH1BIT	PH1	73 x 4.0	6.35 (1/4")	104		
FYW02PH2BIT	PH2	73 x 4.0	6.35 (1/4")	104		
FY520 Handle	—	—	—	—		

HSS 高速鋼六角起子頭

HSS High Speed Steel HEX Professional Bit



單位：mm (Unit : mm)

產品編號 Model No.		長度 Length	柄徑 D Handle Diameter	全長 L Overall Length	價格 Price	備註 Note
FYW02H015BIT	H1.5	44.0	6.35 (1/4")	75		
FYW02H020BIT	H2.0	50.0	6.35 (1/4")	80		
FYW02H025BIT	H2.5	59.5	6.35 (1/4")	90		
FYW02H030BIT	H3.0	61.0	6.35 (1/4")	92		
FY520 Handle	—	—	—	—		

HSS 高速鋼捨棄式刀具專用星型起子

HSS High Speed Steel TORX Screwdriver



單位：mm (Unit : mm)

產品編號 Model No.		長度 Length	柄徑 D Handle Diameter	全長 L Overall Length	價格 Price	備註 Note
VV1GT06HSS488	T06	23	18	130		
VV1GT07HSS488	T07	23	18	130		
VV1GT08HSS488	T08	23	18	130		
VV1GT09HSS488	T09	23	18	130		
VV1GT10HSS488	T10	23	18	130		
VV1GT15HSS488	T15	23	18	130		
VV1GT20HSS488	T20	23	18	130		

HSS 高速鋼捨棄式刀具專用星型起子芯

HSS High Speed Steel TORX Screwdriver Interchangeable Bit



單位：mm (Unit : mm)

產品編號 Model No.		長度 Bit Length	價格 Price	備註 Note
FYW5VT06HSS36	T06	36		
FYW5VT07HSS36	T07	36		
FYW5VT08HSS36	T08	36		
FYW5VT09HSS36	T09	36		
FYW5VT10HSS36	T10	36		
FYW5VT15HSS36	T15	36		
FYW5VT20HSS36	T20	36		

專利走心式車床專用螺帽棘輪扳手

Ratchet Wrench for Swiss Type CNC Lathe



單位：mm (Unit : mm)

產品編號 Model No.		總長度 L Overall Length	價格 Price	備註 Note
RX1GER11M	ER11M	110		
RX1GER16M	ER16M	130		
RX1GER20M	ER20M	160		

專利走心式車床專用星型棘輪扳手

TORX Bit of Ratchet Wrench for Swiss Type CNC Lathe



單位：mm (Unit : mm)

產品編號 Model No.		總長度 L Overall Length	價格 Price	備註 Note
RX1G02510	T8~T15	140		


鎢鋼倒角起子頭

Made in Taiwan Tungsten Carbide Steel Chamfering / Deburring Tool



單位：mm (Unit : mm)

產品編號 Model No.	刃徑 D Diameter	角度 Top Angle	刃數 T Number of Flute	柄徑 D Handle Diameter	價格 Price	備註 Note
2R2FYW 0803	8	90°	3	6.35 (1/4")		
2R2FYW 1103	11	90°	3	6.35 (1/4")		
2R2FYW 1303	13	90°	3	6.35 (1/4")		
2R2FYW 1703	17	90°	3	6.35 (1/4")		
2R2FYW 2103	21	90°	3	6.35 (1/4")		
FY520 Handle	—	—	—	—		



主軸速度表 Spindle Speed Table

直徑 Mill Dia mm	切削速度 V Cutting Speed (mm/min)														
	20	30	40	50	60	70	80	90	100	120	150	180	200	250	300
0.5	12740	19110	25480	31850	38220	44590	50960	57320	63690	76430	95540	114650	127390	159240	191080
0.6	10620	15920	21230	26540	31850	37150	42460	47770	53080	63690	79620	95540	106160	132700	159240
0.7	9100	13650	18200	22750	27300	31850	36400	40950	45500	54590	68240	81890	90990	113740	136490
0.8	7960	11940	15920	19900	23890	27870	31850	35830	39810	47770	59710	71660	79620	99520	119430
0.9	7080	10620	14150	17690	21230	24770	28310	31850	35390	42640	53080	63690	70770	88460	106160
1	6370	9550	12740	15920	19110	22290	25480	28660	31850	38220	47770	57320	63390	79620	95540
2	3180	4780	6370	7960	9550	11150	12740	14330	15920	19110	23890	28660	31850	39810	47770
3	2120	3180	4250	5310	6370	7430	8490	9550	10620	12740	15920	19110	21230	26540	31850
4	1590	2390	3180	3980	4780	5570	6370	7170	7960	9550	11940	14330	15920	19900	23890
5	1270	1910	2550	3180	3820	4460	5100	5730	6370	7640	9550	11460	12740	15920	19110
6	1060	1590	2120	2650	3180	3720	4250	4780	5310	6370	7960	9550	10620	13270	15920
8	800	1190	1590	1990	2390	2790	3180	3580	3980	4780	5970	7170	7960	9950	11940
10	640	960	1270	1590	1910	2230	2550	2870	3180	3820	4780	5730	6370	7960	9550
12	530	800	1060	1330	1590	1860	2120	2390	2650	3180	3980	4780	5310	6630	7960
14	450	680	910	1140	1360	1590	1820	2050	2270	2730	3410	4090	4550	5690	6820
15	420	640	850	1060	1270	1490	1700	1910	2120	2550	3180	3820	4250	5310	6370
16	400	600	800	1000	1190	1390	1590	1790	1990	2390	2990	3580	3980	4980	5970
20	320	480	640	800	960	1110	1270	1430	1590	1910	2390	2870	3180	3980	4780
25	250	380	510	640	760	890	1020	1150	1270	1530	1910	2290	2550	3180	3820

換算公式 Reduction Formula


$$V = \frac{\pi DN}{1000}$$

$$F = N \times Z \times f$$

V	切削速度	Cutting Speed (m/min)
	圓周率	Circular Constant (3.14)
D	銑刀直徑	Diameter (mm)
N	轉速	RPM (min ⁻¹)
Z	銑刀刃數	Number of Flutes
f	每刃進給	Feed per Tooth (mm/tooth)
F	進給	Feed (m/min)




■ 側面切削 Side Milling

ERVD

工件材料 Work Material	一般構造用鋼，碳素鋼，鑄鐵 Mild steels, Carbon Steel, Cast Iron SS400, S55c, FC250 (~750N/mm)		調質鋼，不銹鋼 (38~45HRC) Hardened Steel Stainless Steel SUS304, NAK, SKD		耐熱合金，鈦合金 Ti-6Al-4V Nickel Alloy Titanium Alloy		超耐熱合金，鎳鎢合金718 Super-heat resistant Alloy inconel718	
切削速度 (Vc) Cutting Speed	75-160 m/min		120 m/min		85 m/min		35 m/min	
直徑 (mm) Diameter	回轉數 (rpm) Speed	進給速度 (mm/min) Feed Rate	回轉數 (rpm) Speed	進給速度 (mm/min) Feed Rate	回轉數 (rpm) Speed	進給速度 (mm/min) Feed Rate	回轉數 (rpm) Speed	進給速度 (mm/min) Feed Rate
3	9,550	1,146	9,550	760	6,685	532	3,750	220
4	7,960	1,900	7,960	950	5,572	665	2,800	230
5	7,640	2,139	7,320	1,200	5,124	840	2,240	260
6	6,900	2,800	6,900	1,650	4,830	1,155	1,865	260
8	5,570	2,897	5,570	1,560	3,899	1,092	1,400	260
10	5,093	3,056	4,770	1,630	3,339	1,141	1,120	210
12	3,980	3,180	3,980	1,430	2,786	1,001	935	190
16	2,980	2,380	2,380	950	1,666	665	700	140
切削量基準 Depth of cut (D:直徑Dia.)	 Ap ≤ 2.0D Ae ≤ 0.1D		 Ap ≤ 1.0D Ae ≤ 0.1D		 Ap ≤ 1.0D Ae ≤ 0.05D			

■ 溝切削 Slotting

ERVD

工件材料 Work Material	一般構造用鋼，碳素鋼，鑄鐵 Mild steels, Carbon Steel, Cast Iron SS400, S55c, FC250 (~750N/mm)		調質鋼，不銹鋼 (38~45HRC) Hardened Steel Stainless Steel SUS304, NAK, SKD		耐熱合金，鈦合金 Ti-6Al-4V Nickel Alloy Titanium Alloy		超耐熱合金，鎳鎢合金718 Super-heat resistant Alloy inconel718	
切削速度 (Vc) Cutting Speed	75-160 m/min		120 m/min		75 m/min		30 m/min	
直徑 (mm) Diameter	回轉數 (rpm) Speed	進給速度 (mm/min) Feed Rate	回轉數 (rpm) Speed	進給速度 (mm/min) Feed Rate	回轉數 (rpm) Speed	進給速度 (mm/min) Feed Rate	回轉數 (rpm) Speed	進給速度 (mm/min) Feed Rate
3	9,550	700	9,550	300	6,685	210	3,200	130
4	8,000	800	7,960	450	5,572	315	2,900	130
5	7,320	880	7,320	530	5,124	371	1,920	130
6	6,900	1,103	6,366	630	4,456	441	1,600	150
8	5,570	1,114	4,775	670	3,343	532	1,200	150
10	4,500	1,250	4,138	660	2,897	462	960	130
12	3,450	1,035	3,180	510	2,226	350	800	120
16	2,380	760	2,380	380	1,666	266	600	90
切削量基準 Depth of cut (D:直徑Dia.)	 Ap ≤ 1.0D Ae ≤ 1.0D		 Ap ≤ 0.5D Ae ≤ 1.0D		 Ap ≤ 0.15D Ae ≤ 1.0D			

【注意】

- 1) 請使用剛性及精準度較佳之機械與夾頭。
- 2) 當切削量過大或機械剛性不足時，請降低回轉數及進給速度。
- 3) 請使用不易產生煙霧之切削液。
- 4) 在乾式切削時，請用空氣將切屑吹離加工範圍。

【NOTE】

- 1) Use a rigid and precise machine and holder.
- 2) Please adjust the speed and feed when the cutting depth is large or when machines with low rigidity are used.
- 3) Please use a suitable fluid with high smoke rstartant properties.
- 4) During DRY (no fluid) milling, please use air blow to remove disposable chips from the moilling area and to eliminate chip packing.

■ 側面切削 Side Milling

CED

工件材料 Work Material	一般構造用鋼, 碳素鋼, 鑄鐵 Mild steels, Carbon Steel, Cast Iron SS400, S55c, FC250 (~750N/mm ²)		調質鋼, 不鏽鋼 (38~45HRC) Hardened Steel, Stainless Steel, SUS304, NAK, SKD		耐熱合金, 鈦合金 TI-6Al-4V, Nickel Alloy, Titanium Alloy	
切削速度 (Vc) Cutting Speed	130 m/min		120 m/min		85 m/min	
直徑 (mm) Diameter	回轉數 (rpm) Speed	進給速度 mm/min Feed Rate	回轉數 (rpm) Speed	進給速度 mm/min Feed Rate	回轉數 (rpm) Speed	進給速度 mm/min Feed Rate
3	8,500	800	8,500	500	6,685	420
4	7,162	860	7,960	800	5,572	560
5	7,000	1,100	6,366	860	4,676	602
6	6,366	1,528	5,840	930	4,088	651
8	5,173	1,655	4,775	1,050	3,343	805
10	4,500	2,180	3,820	993	2,898	812
12	3,710	2,228	3,183	830	2,597	833
16	2,590	2,070	2,188	610	1,813	1,302
切削量基準 Depth of cut (D:直徑Dia.)	<p>$Ap \leq 2.0D$ $Ae \leq 0.1D$</p>		<p>$Ap \leq 1.0D$ $Ae \leq 0.1D$</p>			

MHD.EAVD.CHD

■ 側面切削 Side Milling

被削材 Work Material	一般構造用鋼, 碳素鋼, 鑄鐵 Mild steels, Carbon Steel, Cast Iron SS400, S55c, FC250 (~750N/mm ²)		合金鋼, 工具鋼 Alloy Steel, Tool Steel SCM, SKT, SKS, SKD (~30HRC)		(30~38HRC) 預硬鋼 (快削) Hardened Steel Pre-hardened Steel (Free Cutting) SKT, SKD, NAK, HPM1		調質鋼, 不鏽鋼 (38~45HRC) Hardened Steel, Stainless Steel, SUS304, NAK, SKD		熱處理鋼 (45~55HRC) 鈦合金, 耐熱合金 Hardened Steel, Titanium Alloy, SKD61, SKD11, STAVAX 等		熱處理鋼 (55~60HRC) Hardened steel SKD11, SKH, SKS 等, AISI H13, AISI D2 etc	
切削速度 Cutting Speed	100 m/min		78 m/min		66 m/min		62 m/min		60 m/min		30 m/min	
直徑 (mm) Diameter	回轉數 (min ⁻¹) Speed	進給速度 mm/min Feed Rate	回轉數 (min ⁻¹) Speed	進給速度 mm/min Feed Rate	回轉數 (min ⁻¹) Speed	進給速度 mm/min Feed Rate	回轉數 (min ⁻¹) Speed	進給速度 mm/min Feed Rate	回轉數 (min ⁻¹) Speed	進給速度 mm/min Feed Rate	回轉數 (min ⁻¹) Speed	進給速度 mm/min Feed Rate
3	9,000	800	8,300	760	7,000	560	6,600	555	6,350	485	3,200	190
4	7,000	980	6,200	820	5,300	570	4,950	590	4,750	515	2,400	190
5	6,400	1,200	5,000	850	4,200	590	3,950	630	3,800	535	1,900	190
6	5,500	1,500	4,200	950	3,500	700	3,300	660	3,200	545	1,600	190
8	4,800	1,600	3,100	895	2,650	660	2,450	640	2,400	555	1,200	175
10	4,350	2,000	2,500	855	2,100	605	1,950	590	1,900	525	955	160
12	3,000	1,500	2,050	850	1,750	565	1,650	535	1,600	475	795	160
16	2,300	1,000	1,550	745	1,300	500	1,250	445	1,200	400	595	160
20	1,600	900	1,250	595	1,050	455	985	395	955	355	475	160
切削量基準 Depth of cut (D:直徑Dia.)	<p>Ad Rd 1.5D 0.1D</p>		<p>Ad Rd 1.5D 0.1D</p>		<p>Ad Rd 1D 0.05D</p>		<p>Ad Rd 1D 0.05D</p>		<p>Ad Rd 1D 0.05D</p>		<p>Ad Rd 1D 0.05D</p>	

■ 溝切削 Slotting

CED

工件材料 Work Material	一般構造用鋼, 碳素鋼, 鑄鐵 Mild steels, Carbon Steel, Cast Iron SS400, S55c, FC250 (~750N/mm ²)		調質鋼, 不鏽鋼 (38~45HRC) Hardened Steel, Stainless Steel, SUS304, NAK, SKD		耐熱合金, 鈦合金 TI-6Al-4V, Nickel Alloy, Titanium Alloy	
切削速度 (Vc) Cutting Speed	130 m/min		120 m/min		75 m/min	
直徑 (mm) Diameter	回轉數 (rpm) Speed	進給速度 mm/min Feed Rate	回轉數 (rpm) Speed	進給速度 mm/min Feed Rate	回轉數 (rpm) Speed	進給速度 mm/min Feed Rate
3	9,550	500	8,488	200	6,685	210
4	7,960	570	6,765	320	5,572	315
5	7,100	600	5,730	350	5,124	371
6	6,366	700	5,305	420	4,456	441
8	5,173	750	3,980	480	3,343	532
10	3,979	875	3,180	510	2,897	462
12	2,920	700	2,653	420	2,226	350
16	2,190	530	1,990	280	1,666	266
切削量基準 Depth of cut (D:直徑Dia.)	<p>$Ap \leq 1.0D$ $Ae \leq 1.0D$</p>		<p>$Ap \leq 0.5D$ $Ae \leq 1.0D$</p>			

■ 溝切削 Slotting

被削材 Work Material	一般構造用鋼, 碳素鋼, 鑄鐵 Mild steels, Carbon Steel, Cast Iron SS400, S55c, FC250 (~750N/mm ²)		合金鋼, 工具鋼 Alloy Steel, Tool Steel SCM, SKT, SKS, SKD (~30HRC)		(30~38HRC) 預硬鋼 (快削) Hardened Steel Pre-hardened Steel (Free Cutting) SKT, SKD, NAK, HPM1		調質鋼, 不鏽鋼 (38~45HRC) Hardened Steel, Stainless Steel, SUS304, NAK, SKD		熱處理鋼 (45~55HRC) 鈦合金, 耐熱合金 Hardened Steel, Titanium Alloy, SKD61, SKD11, STAVAX 等		熱處理鋼 (55~60HRC) Hardened steel SKD11, SKH, SKS 等, AISI H13, AISI D2 etc	
切削速度 Cutting Speed	80 m/min		60 m/min		55 m/min		52 m/min		42 m/min		20 m/min	
直徑 (mm) Diameter	回轉數 (min ⁻¹) Speed	進給速度 mm/min Feed Rate	回轉數 (min ⁻¹) Speed	進給速度 mm/min Feed Rate	回轉數 (min ⁻¹) Speed	進給速度 mm/min Feed Rate	回轉數 (min ⁻¹) Speed	進給速度 mm/min Feed Rate	回轉數 (min ⁻¹) Speed	進給速度 mm/min Feed Rate	回轉數 (min ⁻¹) Speed	進給速度 mm/min Feed Rate
3	9,000	600	6,350	595	5,850	455	5,500	400	4,450	320	2,100	110
4	7,000	800	4,750	675	4,400	455	4,150	450	3,350	360	1,600	120
5	6,400	850	3,800	660	3,500	475	3,300	475	2,650	385	1,250	125
6	5,500	900	3,200	560	2,900	500	2,750	495	2,250	400	1,050	125
8	4,800	1,000	2,400	550	2,200	545	2,050	515	1,650	415	795	125
10	4,350	1,200	1,900	535	1,750	475	1,650	470	1,350	380	635	115
12	3,000	1,000	1,600	475	1,450	450	1,400	440	1,100	355	530	115
16	2,300	600	1,200	430	1,100	370	1,050	370	835	300	400	88
20	1,600	400	955	380	875	350	830	330	670	265	320	89
切削量基準 Depth of cut (D:直徑Dia.)	<p>$Ad = 1D$</p>		<p>Ad $Ad = 0.5D$</p>		<p>$Ad = 0.05D$</p>		<p>$Ad = 0.05D$</p>		<p>$Ad = 0.05D$</p>		<p>$Ad = 0.05D$</p>	

【注意】

- 1) 請使用剛性及精準度較佳之機械與夾頭。
- 2) 當切削量過大或機械剛性不足時,請降低回轉數及進給速度。
- 3) 請使用不易產生煙霧之切削液。
- 4) 在乾式切削時,請用空氣將切屑吹離加工範圍。

【NOTE】

- 1) Use a rigid and precise machine and holder.
- 2) Please adjust the speed and feed when the cutting depth is large or when machines with low rigidity are used.
- 3) Please use a suitable fluid with high smoke rstartant properties.
- 4) During DRY (no fluid) milling, please use air blow to remove disposable chips from the moilling area and to eliminate chip packing.

【注意】

- 1) 請使用剛性及精準度較佳之機械與夾頭。
- 2) 當切削量過大或機械剛性不足時,請降低回轉數及進給速度。
- 3) 請使用不易產生煙霧之切削液。
- 4) 在乾式切削時,請用空氣將切屑吹離加工範圍。

【NOTE】

- 1) Use a rigid and precise machine and holder.
- 2) Please adjust the speed and feed when the cutting depth is large or when machines with low rigidity are used.
- 3) Please use a suitable fluid with high smoke rstartant properties.
- 4) During DRY (no fluid) milling, please use air blow to remove disposable chips from the moilling area and to eliminate chip packing.

■ 高速側面切削 High Speed Side Milling

MHD.EAVD.CHD

被削材 Work Material	一般構造用鋼, 碳素鋼, 鑄鐵 Mild steels, Carbon Steel, Cast Iron SS400, S55c, FC250 (~750N/mm ²)		合金鋼, 工具鋼 Alloy Steel, Tool Steel SCM, SKT, SKS, SKD (~30HRC)		(30~38HRC) 預硬鋼 (快削) Hardened Steel Pre-hardened Steel (Free Cutting) SKT, SKD, NAK, HPM1		調質鋼, 不鏽鋼 (38~45HRC) Hardened Steel Stainless Steel SUS304, NAK, SKD		熱處理鋼 (45~55HRC) 鈦合金, 耐熱合金 Hardened Steel, Titanium Alloy SKD61, SKD11, STAVAX 等		熱處理鋼 (55~60HRC) Hardened steel SKD11, SKH, SKS 等 AISI H13, AISI D2 etc		
	200 m/min		200 m/min		200 m/min		150 m/min		100 m/min		80 m/min		
削材速度 Cutting Speed	直徑 (mm) Diameter	回轉數 (min ⁻¹) Speed	進給速度 mm/min Feed Rate	回轉數 (min ⁻¹) Speed	進給速度 mm/min Feed Rate	回轉數 (min ⁻¹) Speed	進給速度 mm/min Feed Rate	回轉數 (min ⁻¹) Speed	進給速度 mm/min Feed Rate	回轉數 (min ⁻¹) Speed	進給速度 mm/min Feed Rate	回轉數 (min ⁻¹) Speed	進給速度 mm/min Feed Rate
3	21,200	2,150	21,200	2,400	21,200	1,300	15,900	1,150	10,600	680	8,500	440	
4	15,900	2,050	15,900	2,300	15,900	1,300	11,900	1,250	7,950	795	6,350	460	
5	12,700	1,900	12,700	2,150	12,700	1,250	9,550	1,350	6,350	840	5,100	510	
6	10,600	3,050	10,600	2,650	10,600	2,000	7,950	1,450	5,300	910	4,250	610	
8	7,950	2,800	7,950	2,400	7,950	1,900	5,950	1,400	4,000	860	3,200	575	
10	6,350	2,550	6,350	2,200	6,350	1,850	4,750	1,350	3,200	830	2,550	510	
12	5,300	2,550	5,300	2,200	5,300	1,800	4,000	1,350	2,650	830	2,100	510	
16	4,000	1,900	4,000	1,900	4,000	1,700	3,000	1,350	2,000	830	1,600	510	
20	3,200	1,550	3,200	1,550	3,200	1,550	2,400	1,150	1,600	730	1,250	510	

Ad
Rd

Rd Max=0.5mm

Ad	Rd
D, $\leq \phi 6$	1.5D, 0.02D
<math>\phi 6="" \leq="" d<="" math><="" td=""><td>1.5D, 0.05D</td></math>\phi>	1.5D, 0.05D

Rd Max=0.5mm

Ad	Rd
D, $\leq \phi 6$	1.5D, 0.01D
<math>\phi 6="" \leq="" d<="" math><="" td=""><td>1.5D, 0.02D</td></math>\phi>	1.5D, 0.02D

Rd Max=0.5mm

Ad	Rd
D, $\leq \phi 6$	1.5D, 0.01D
<math>\phi 6="" \leq="" d<="" math><="" td=""><td>1.5D, 0.02D</td></math>\phi>	1.5D, 0.02D

Rd Max=0.5mm

■ 高速溝切削 High Speed Slotting

被削材 Work Material	一般構造用鋼, 碳素鋼, 鑄鐵 Mild steels, Carbon Steel, Cast Iron SS400, S55c, FC250 (~750N/mm ²)		合金鋼, 工具鋼 Alloy Steel, Tool Steel SCM, SKT, SKS, SKD (~30HRC)		(30~38HRC) 預硬鋼 (快削) Hardened Steel Pre-hardened Steel (Free Cutting) SKT, SKD, NAK, HPM1		調質鋼, 不鏽鋼 (38~45HRC) Hardened Steel Stainless Steel SUS304, NAK, SKD		
	120 m/min		110 m/min		90~100 m/min		60~70 m/min		
削材速度 Cutting Speed	直徑 (mm) Diameter	回轉數 (min ⁻¹) Speed	進給速度 mm/min Feed Rate	回轉數 (min ⁻¹) Speed	進給速度 mm/min Feed Rate	回轉數 (min ⁻¹) Speed	進給速度 mm/min Feed Rate	回轉數 (min ⁻¹) Speed	進給速度 mm/min Feed Rate
4	9,550	1,150	7,950	1,000	7,150	745	5,150	560	
5	7,650	1,200	7,000	1,100	6,350	865	4,150	595	
6	6,350	1,550	5,850	1,150	5,300	910	3,700	670	
8	4,750	1,450	4,400	1,300	4,000	985	2,800	690	
10	3,800	1,400	3,500	1,200	3,200	865	2,250	635	
12	3,200	1,250	2,900	1,150	2,650	815	1,850	595	
16	2,400	1,050	2,200	965	2,000	675	1,400	500	
20	1,900	840	1,750	770	1,600	635	1,100	445	

Ad

Ad=0.2D
Ad Max=3mm

注意：
加工時產生的火花及破損引起的發熱，可能導致燃燒或
火災；請務必要有防火措施

Caution:
Sparks generated during operation or heat caused by tool breakage
can cause fire. Be sure to use all proper fire-prevention measures.

切削條件表 Standard Cutting Conditions

SE.MHD.RTA

被削材 Work Material	炭素鋼, 合金鋼 (~30HRC) Carbon Steel, Alloy Steel S50C, SCM, 鑄鐵 FC250 等 AISI 1049, Cast iron		合金鋼, 工具鋼 (30~45HRC) Alloy steel, Tool steel 預硬鋼, SKD61, NAK 等 Pre-hardened steel, AISI H13		沃斯田鐵系列不鏽鋼 Austenitic stainless steel SUS304, SUS316 等 AISI 304, AISI 316		熱處理鋼 (45~55HRC) Hardened steel SKD61, SKD11, NAK, STAVAX 等 AISI H13		熱處理鋼 (55~60HRC) Hardened steel SKD11 等 AISI D2						
	50~100 m/min		50~70 m/min		30~60 m/min		30~50 m/min		15~30 m/min						
削材速度 Cutting Speed	直徑 (mm) Diameter	回轉數 (min ⁻¹) Speed	進給速度 mm/min Feed Rate	回轉數 (min ⁻¹) Speed	進給速度 mm/min Feed Rate	回轉數 (min ⁻¹) Speed	進給速度 mm/min Feed Rate	回轉數 (min ⁻¹) Speed	進給速度 mm/min Feed Rate	回轉數 (min ⁻¹) Speed	進給速度 mm/min Feed Rate				
												側面 Side Milling	溝 Slotting	側面 Side Milling	溝 Slotting
1	30,000	900	720	20,000	600	480	12,600	450	270	15,000	180	140	4,800	30	24
1.5	20,000	900	720	14,000	600	480	8,400	450	270	10,000	180	140	3,200	35	28
2	15,000	900	720	10,000	600	480	6,300	450	270	8,000	180	140	2,400	40	32
2.5	12,000	900	720	8,200	600	480	5,100	450	270	6,100	180	140	2,100	45	36
3	10,000	900	720	7,000	600	480	4,200	450	270	5,000	180	140	1,800	55	44
4	7,500	900	720	5,200	600	480	3,100	450	270	4,000	180	140	1,400	75	60
5	6,000	900	720	4,200	600	480	2,500	450	270	3,200	180	140	1,200	75	60
6	5,000	900	430	3,500	600	480	2,100	450	270	2,700	180	140	1,000	75	60
8	4,000	780	620	2,800	520	410	1,600	390	230	2,000	160	125	800	70	56
10	3,200	680	540	2,200	450	360	1,300	340	200	1,600	140	110	650	65	52
12	2,700	620	490	1,900	410	320	1,100	310	180	1,300	120	95	530	55	44

切削量基準
Depth of cut
(D: 直徑 Dia.)

$\leq 0.1D (D \leq \phi 3)$
 $\leq 0.2D (D > \phi 3)$

$\leq 1.5D$

$\leq 0.1D (D < \phi 2)$
 $\leq 0.2D (D \leq \phi 2)$

$\leq 0.05D$
 $\leq 1D$

$\leq 0.05D (D \leq \phi 2)$
 $\leq 0.1D (D > \phi 2)$

$\leq 0.02D$
 $\leq 1D$

$\leq 0.05D$

【注意】【NOTE】

- 1) 切削60 HRC的材料時，請使用MS6P銑刀。
Please Use MS6P for work materials of 60 HRC or above.
- 2) 切削沃斯田鐵系列不鏽鋼系列及耐熱合金時，請使用非水溶性切削油效果較好。
In Cutting Austenitic stainless steels, the use of non-water-soluble cutting fluid is especially effective.
- 3) 機械設備或工件的夾持剛性不足、出現震動時，請以相同比例按上表降低回轉數及進給速度。
If the rigidity of the machine or the work material installation is very low, or chattering is generated, please reduce the revolution and the feed rate proportionately.
- 4) 縱向進給時，進給速度請設定為上表之1/3以下。
When drilling, please set feed rate at 1/3 or below of the above value.

高速切削條件表 High-Speed Milling Conditions

被削材 Work Material	炭素鋼, 合金鋼 (~30HRC) Carbon Steel, Alloy Steel S50C, SCM, 鑄鐵 FC250 等 AISI 1049, Cast iron		合金鋼, 工具鋼 (30~45HRC) Alloy steel, Tool steel 預硬鋼, SKD61, NAK 等 Pre-hardened steel, AISI H13		熱處理鋼 (45~55HRC) Hardened steel SKD61, SKD11, NAK, STAVAX 等 AISI H13		熱處理鋼 (55~60HRC) Hardened steel SKD11 等 AISI D2		
	300 m/min		200 m/min		150 m/min		50 m/min		
削材速度 Cutting Speed	直徑 (mm) Diameter	回轉數 (min ⁻¹) Speed	進給速度 mm/min Feed Rate	回轉數 (min ⁻¹) Speed	進給速度 mm/min Feed Rate	回轉數 (min ⁻¹) Speed	進給速度 mm/min Feed Rate	回轉數 (min ⁻¹) Speed	進給速度 mm/min Feed Rate
2	40,000	2,400	30,000	1,800	23,800	530	7,900	130	
3	30,000	2,700	21,200	1,800	15,900	530	5,300	160	
4	23,800	2,850	15,900	1,800	11,900	530	4,000	210	
5	19,000	2,850	12,700	1,800	9,500	530	3,200	200	
6	15,900	2,850	10,600	1,800	7,900	530	2,650	200	
8	11,900	2,325	7,900	1,485	5,900	470	2,000	175	
10	9,500	2,000	6,300	1,290	4,700	410	1,600	160	
12	7,900	1,800	5,300	1,125	3,900	360	1,300	135	

切削量基準
Depth of cut
(D: 直徑 Dia.)

$\leq 0.02D$
 $\leq 1D$

■ 側面切削 Side Milling

工件材料 Work Material	鋁合金 Aluminum		銅合金 Copper	
	回轉數 (rpm) Speed	每刀進給 Fz mm/tooth	回轉數 (rpm) Speed	每刀進給 Fz mm/tooth
切削速度 (Vc) Cutting Speed	100~300 m/min		60~120 m/min	
直徑 (mm) Diameter				
1	31831	.002-.005	31831	.001-.002
2	15916	.005-.015	15916	.005-.01
3	13793	.01-.03	10610	.01-.02
4	11937	.01-.04	7958	.01-.03
5	10186	.02-.06	6366	.02-.05
6	9019	.02-.08	5305	.02-.07
8	8754	.03-.10	3979	.03-.08
10	7639	.03-.12	3183	.03-.10
12	6366	.04-.14	2653	.04-.12
16	4775	.05-.18	1989	.05-.16
20	3820	.06-.22	1592	.06-.18

切削量基準
Depth of cut
(D:直徑Dia.)

$Ap \leq 2.0D$
 $Ae \leq 0.2D$

■ 溝切削 Slotting

AEC

工件材料 Work Material	鋁合金 Aluminum		銅合金 Copper	
	回轉數 (rpm) Speed	每刀進給 Fz mm/tooth	回轉數 (rpm) Speed	每刀進給 Fz mm/tooth
切削速度 (Vc) Cutting Speed	100~300 m/min		60~110 m/min	
直徑 (mm) Diameter				
1	31831	.001-.002	28648	.001-.002
2	15916	.002-.004	14324	.001-.003
3	13793	.005-.01	9549	.002-.005
4	11937	.01-.02	7162	.005-.01
5	10186	.01-.04	5730	.01-.03
6	9019	.02-.05	4775	.02-.04
8	8754	.03-.07	3581	.03-.06
10	7639	.04-.09	2865	.04-.08
12	6366	.05-.11	2387	.05-.10
16	4775	.06-.12	1790	.05-.11
20	3820	.06-.12	1432	.05-.11

切削量基準
Depth of cut
(D:直徑Dia.)

$Ap \leq 1.0D$
 $Ae = 1.0D$

■ 側面切削 Side Milling

工件材料 Work Material	鋁合金 Aluminum		銅合金 Copper	
	回轉數 (rpm) Speed	每刀進給 Fz mm/tooth	回轉數 (rpm) Speed	每刀進給 Fz mm/tooth
切削速度 (Vc) Cutting Speed	100~250 m/min		50~120 m/min	
直徑 (mm) Diameter				
1	31831	.002-.005	15916	.002-.005
2	15916	.005-.015	11141	.005-.01
3	13793	.005-.03	8488	.01-.015
4	11937	.01-.04	6366	.01-.03
5	10186	.02-.05	5730	.02-.05
6	8488	.025-.08	4775	.025-.06
8	8356	.03-.10	3581	.03-.08
10	7639	.03-.12	2865	.04-.11
12	6366	.04-.15	2387	.05-.12
14	5229	.05-.18	2046	.06-.15
16	4576	.06-.20	1790	.07-.17
20	3501	.08-.22	1432	.08-.19

切削量基準
Depth of cut
(D:直徑Dia.)

$Ap \leq 2.0D$
 $Ae \leq 0.2D$

■ 溝切削 Slotting

AE&AR

工件材料 Work Material	鋁合金 Aluminum		銅合金 Copper	
	回轉數 (rpm) Speed	每刀進給 Fz mm/tooth	回轉數 (rpm) Speed	每刀進給 Fz mm/tooth
切削速度 (Vc) Cutting Speed	100~250 m/min		50~120 m/min	
直徑 (mm) Diameter				
1	31831	.001-.002	15916	.001-.002
2	15916	.005-.01	11141	.001-.005
3	13793	.005-.01	8488	.005-.01
4	11937	.01-.02	6366	.01-.015
5	10186	.01-.03	5730	.01-.025
6	8488	.02-.04	4775	.015-.04
8	8356	.03-.06	3581	.02-.05
10	7639	.04-.07	2865	.03-.06
12	6101	.05-.08	2387	.04-.08
14	5229	.06-.09	2046	.05-.10
16	4576	.07-.10	1790	.06-.12
20	3501	.08-.11	1432	.08-.14

切削量基準
Depth of cut
(D:直徑Dia.)

$Ap \leq 1.0D$
 $Ae = 1.0D$

■ 側面切削 Side Milling

工件材料 Work Material	鋁合金 Aluminum		銅合金 Copper	
	回轉數 (rpm) Speed	每刀進給 Fz mm/tooth	回轉數 (rpm) Speed	每刀進給 Fz mm/tooth
切削速度 (Vc) Cutting Speed	100~300 m/min		80~120 m/min	
直徑 (mm) Diameter				
3	13793	.01-.03	10610	.01-.02
4	11937	.01-.05	7958	.01-.03
5	10186	.02-.08	6366	.02-.04
6	9019	.02-.10	5305	.02-.05
8	8754	.02-.12	3979	.03-.06
10	7639	.03-.14	3183	.04-.09
12	6366	.04-.16	2653	.04-.11
16	4775	.05-.20	1989	.05-.13
20	3820	.06-.22	1592	.06-.15

切削量基準
Depth of cut
(D:直徑Dia.)

$Ap \leq 2.0D$
 $Ae \leq 0.25D$

■ 溝切削 Slotting

AED

工件材料 Work Material	鋁合金 Aluminum		銅合金 Copper	
	回轉數 (rpm) Speed	每刀進給 Fz mm/tooth	回轉數 (rpm) Speed	每刀進給 Fz mm/tooth
切削速度 (Vc) Cutting Speed	100~300 m/min		80~120 m/min	
直徑 (mm) Diameter				
3	13793	.01-.02	10610	.01-.015
4	11937	.02-.04	7958	.01-.02
5	10186	.03-.06	6366	.02-.03
6	9019	.04-.08	5305	.02-.04
8	8754	.05-.10	3979	.03-.06
10	7639	.05-.13	3183	.03-.08
12	6366	.08-.15	2653	.04-.10
16	4775	.08-.17	1989	.05-.11
20	3820	.08-.20	1592	.05-.12

切削量基準
Depth of cut
(D:直徑Dia.)

$Ap \leq 1.0D$
 $Ae = 1.0D$

■ 側面切削 Side Milling

ACB

工件材料 Work Material	鋁合金 Aluminum		銅合金 Copper	
	回轉數 (rpm) Speed	每刀進給 Fz mm/tooth	回轉數 (rpm) Speed	每刀進給 Fz mm/tooth
切削速度 (Vc) Cutting Speed	60~150 m/min		50~100 m/min	
直徑 (mm) Diameter				
0.4	47747	.001-.005	39789	.001-.005
0.5	44563	.001-.005	31831	.001-.005
0.6	42441	.001-.005	26526	.001-.005
0.8	39789	.001-.005	19894	.001-.005
1	31831	.005-.01	17507	.005-.01
2	28648	.01-.02	14324	.01-.02
3	15916	.01-.06	9549	.01-.03
4	11937	.02-.08	7162	.02-.06
5	9549	.02-.10	5730	.02-.08
6	7958	.03-.12	4775	.03-.10
8	5968	.04-.18	3581	.04-.12
10	4775	.06-.20	2865	.06-.15
12	3980	.08-.22	2387	.08-.18

切削量基準
Depth of cut
(D:直徑Dia.)


$Ap \leq 0.5D$
 $Ae \leq 0.2D$

切削條件表

切削條件表


■ 側面切削 Side Milling

工件材料 Work Material	鋁合金 Aluminum		銅合金 Copper	
	回轉數 (rpm) Speed	每刀進給 Fz mm/tooth	回轉數 (rpm) Speed	每刀進給 Fz mm/tooth
切削速度 (Vc) Cutting Speed	150~250 m/min		100~150 m/min	
直徑 (mm) Diameter				
6	12732	.03-.08	6897	.02-.04
8	9549	.04-.12	5173	.03-.06
10	7639	.06-.14	4138	.04-.08
12	6366	.07-.16	3448	.04-.10
16	4775	.08-.20	2586	.05-.12
20	3820	.08-.22	2069	.05-.12

切削量基準 Depth of cut (D:直徑Dia.)	 <p>$A_p \leq 2.0D$ $A_e \leq 0.25D$</p>
-------------------------------------	-----------------------------------------------------------------------------------------------------------------------------------------------------

■ 溝切削 Slotting

工件材料 Work Material	鋁合金 Aluminum		銅合金 Copper	
	回轉數 (rpm) Speed	每刀進給 Fz mm/tooth	回轉數 (rpm) Speed	每刀進給 Fz mm/tooth
切削速度 (Vc) Cutting Speed	240 m/min		110 m/min	
直徑 (mm) Diameter				
6	12732	.04-.08	5836	.02-.04
8	9549	.05-.11	4377	.03-.06
10	7639	.06-.14	3501	.03-.08
12	6366	.08-.16	2918	.04-.10
16	4775	.10-.18	2188	.05-.11
20	3820	.12-.12	1751	.05-.12



切削量基準 Depth of cut (D:直徑Dia.)	 <p>$A_p \leq 1.0D$ $A_e = 1.0D$</p>
-------------------------------------	--------------------------------------------------------------------------------------------------------------------------------------------------

AEW

切削條件表 Standard Cutting Conditions

SB

被削材 Work Material	炭素鋼 Carbon steels S50C		合金鋼, 調質鋼 Alloy steels Pre-hardened steels, SCM, SKD,SUS,HPM,NAK		熱處理鋼 Hardened steels SKD61(~55HRC)		鋁 Aluminum		銅 Copper	
	回轉數 (min ⁻¹) Speed	進給速度 mm/min Feed Rate	回轉數 (min ⁻¹) Speed	進給速度 mm/min Feed Rate	回轉數 (min ⁻¹) Speed	進給速度 mm/min Feed Rate	回轉數 (min ⁻¹) Speed	進給速度 mm/min Feed Rate	回轉數 (min ⁻¹) Speed	進給速度 mm/min Feed Rate
切削速度 Cutting Speed	150 m/min		120~150 m/min		80~100 m/min		100~200 m/min		100~150 m/min	
R										
0.15	40,000	400	40,000	360	40,000	330	40,000	440	40,000	400
0.2	40,000	500	40,000	480	40,000	500	40,000	480	40,000	480
0.25	40,000	620	40,000	610	40,000	620	40,000	540	40,000	540
0.3	40,000	750	40,000	1,000	40,000	750	40,000	600	40,000	600
0.4	40,000	960	40,000	1,200	36,000	900	40,000	800	40,000	800
0.5	40,000	1,200	38,000	1,100	29,000	900	40,000	1,000	40,000	830
0.75	30,000	1,270	25,500	800	19,000	700	40,000	1,360	30,000	1,160
1	24,000	1,160	19,000	670	14,000	600	40,000	2,000	24,000	1,200
1.25	19,000	1,000	15,300	600	11,500	510	38,000	2,400	19,000	1,200
1.5	16,000	930	13,000	580	9,600	460	32,000	2,400	16,000	1,200
1.75	13,700	930	11,400	570	8,200	450	27,300	2,400	13,000	1,200
2	12,000	930	10,000	560	7,200	450	24,000	2,400	12,000	1,200
2.5	9,600	930	8,000	540	5,700	450	19,000	2,400	9,600	1,200
3	8,000	930	6,400	540	4,800	450	16,000	2,400	8,000	1,200
4	6,000	900	4,800	540	3,600	450	12,000	2,400	6,000	1,200
5	4,800	900	3,800	540	2,900	450	9,600	2,300	4,800	1,150
6	4,000	900	3,200	540	2,400	450	8,000	2,100	4,000	1,050

切削量基準 Depth of cut (R:球頭半徑)	 <p>0.1xR (~45HRC) ~0.08xR (~55HRC)</p>	 <p>(R0.1~0.5=0.2xR) 0.3xR</p> <p>~0.16xR R ≤ 0.3 (~45HRC) ~0.25xR R ≤ 3 (~45HRC) ~0.17xR R ≤ 4 (~45HRC) ~0.05xR (~45HRC)</p>
-----------------------------------	----------------------------------------------------------------------------------------------------------------------------------	------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

【注意】【NOTE】

- 溝加工時之進給速度，請設定為上數值之60%。
When slotting, reduce the feed by 60% from above values.
- 刀具夾持突出量，以4D為基準，超出上述場合時；請將切削條件作適度之調整。
Length of overhang is 4 times dia. as standard. When it is longer then 4 times dia., flow figures of above table.
- 請使用油霧(Oil-mist)冷卻或吹氣方式(Air blow)進行切削。
Use Oil-mist coolant or Air blow.
- 主軸回轉數及床台進給速度，請以相同比例作適度調整。
Adjust both spindle speed and feed according to milling conditions and machine rigidity.

高速切削條件表 High-Speed Milling Conditions

SB

被削材 Work Material	炭素鋼 Carbon steels S50C		合金鋼 Alloy steels SCM,SKD,SUS		調質鋼 Pre-hardned steels HPM,NAK		熱處理鋼 Hardened steels SKD61(~55HRC)	
	250 m/min		200 m/min		180 m/min		100 m/min	
削材速度 Cutting Speed	250 m/min		200 m/min		180 m/min		100 m/min	
R	回轉數 (min ⁻¹) Speed	進給速度 mm/min Feed Rate	回轉數 (min ⁻¹) Speed	進給速度 mm/min Feed Rate	回轉數 (min ⁻¹) Speed	進給速度 mm/min Feed Rate	回轉數 (min ⁻¹) Speed	進給速度 mm/min Feed Rate
0.15	~40,000	~1,200	~40,000	~960	~40,000	~800	~40,000	350
0.2	~40,000	~1,200	~40,000	~960	~40,000	~800	~40,000	480
0.25	~40,000	~1,200	~40,000	~960	~40,000	~800	~40,000	520
0.3	~40,000	~1,200	~40,000	~960	~40,000	~800	~40,000	560
0.4	~40,000	~2,400	~40,000	~2,000	~40,000	~1,760	40,000	1,000
0.5	~40,000	~2,400	~40,000	~2,000	~40,000	~1,760	32,000	1,500
0.75	~40,000	~3,700	~40,000	~3,000	38,000	2,700	21,300	1,500
1	40,000	5,000	32,000	3,200	29,000	2,900	16,000	1,500
1.25	32,000	5,000	25,000	3,200	23,000	2,900	12,800	1,500
1.5	27,000	5,000	21,000	3,200	19,000	2,900	10,600	1,500
1.75	23,000	5,000	18,000	3,200	16,400	2,900	9,100	1,500
2	20,000	4,000	16,000	3,200	14,000	2,900	8,000	1,500
2.5	16,000	3,500	12,800	2,500	11,500	2,300	6,400	1,300
3	13,500	3,000	10,600	2,000	9,500	1,800	5,300	1,200
4	10,000	3,000	8,000	2,000	7,200	1,800	4,000	1,200
5	8,000	3,000	6,400	2,000	5,700	1,800	3,200	1,200
6	6,700	2,500	5,300	1,800	4,800	1,800	2,700	1,200

切削量基準
Depth of cut
(R:球頭半徑)


【注意】【NOTE】

- 1) 溝加工時之進給速度，請設定為上數值之60%。
When slotting, reduce the feed by 60% from above values.
- 2) 請使用油霧(Oil-mist)冷卻或吹氣方式(Air blow)進行切削。
Use Oil-mist coolant or Air blow.
- 3) 機械設備或工件的夾持剛性不足、出現震動時，請以相同比例按上表降低回轉數及進給速度。
If the rigidity of the machine or the work material installation is very low, or chattering is generated, please reduce the revolution and the feed rate proportionately.
- 4) 請使用較具有剛性之機械設備及夾頭。
Use a rigid machine and holder.

球型銑刀實際加工直徑速查表 Ball End Milling Actual Diameter





SB

R半徑 R	刃徑 D	加工深度 Depth of cut (mm)														
		0.01	0.02	0.03	0.04	0.05	0.08	0.1	0.15	0.2	0.3	0.5	0.8	1	2	3
0.1	0.2	0.087	0.12	0.143	0.16	0.173	0.196	0.2								
0.2	0.4	0.125	0.174	0.211	0.24	0.265	0.32	0.35	0.39	0.4						
0.3	0.6	0.154	0.215	0.262	0.299	0.332	0.41	0.45	0.52	0.57	0.6					
0.4	0.8	0.178	0.25	0.304	0.349	0.387	0.48	0.53	0.62	0.69	0.77					
0.5	1	0.199	0.28	0.341	0.392	0.436	0.54	0.6	0.71	0.8	0.92	1				
1	2	0.282	0.398	0.486	0.56	0.624	0.78	0.87	1.05	1.2	1.43	1.73	1.96	2		
1.5	3	0.346	0.488	0.597	0.688	0.768	0.97	1.08	1.31	1.5	1.8	2.24	2.65	2.83		
2	4	0.399	0.564	0.69	0.796	0.889	1.12	1.25	1.52	1.74	2.11	2.65	3.2	3.46	4	
2.5	5	0.447	0.631	0.722	0.891	0.995	1.25	1.4	1.71	1.96	2.37	3	3.67	4	4.9	
3	6	0.489	0.692	0.846	0.977	1.091	1.38	1.54	1.87	2.15	2.62	3.32	4.08	4.47	5.66	6
4	8	0.565	0.799	0.978	1.129	1.261	1.59	1.78	2.17	2.5	3.04	3.87	4.8	5.29	6.93	7.75
5	10	0.632	0.894	1.094	1.262	1.411	1.78	1.99	2.43	2.8	3.41	4.36	5.43	6	8	9.17
6	12	0.693	0.979	1.198	1.383	1.546	1.95	2.18	2.67	3.07	3.75	4.8	5.99	6.63	8.94	10.39
7	14	0.748	1.058	1.295	1.495	1.67	2.11	2.36	2.88	3.32	4.05	5.2	6.5	7.21	9.8	11.49
8	16	0.8	1.131	1.384	1.598	1.786	2.26	2.52	3.08	3.56	4.34	5.57	6.97	7.75	10.58	12.49
9	18	0.848	1.199	1.468	1.695	1.895	2.39	2.68	3.27	3.77	4.61	5.92	7.42	8.25	11.31	13.42
10	20	0.894	1.264	1.548	1.787	1.997	2.52	2.82	3.45	3.98	4.86	6.24	7.84	8.72	12	14.28



切削條件表 Standard Cutting Conditions

SE.RTA



被削材 Work Material	炭素鋼 合金鋼(~30HRC) Carbon steel, Alloy steel S50C, SCM, 鑄鐵 FC250等 AISI 1049, Cast iron			合金鋼, 工具鋼(30~45HRC) Alloy steel, Tool steel 預硬鋼, SKD61, NAK等 Pre-hardened steel, AISI H13			沃斯田鐵系列不鏽鋼 Austenitic stainless steel SUS304, SUS316等 AISI 304, AISI 316			熱處理鋼(45~55HRC) Hardened steel SKD61, SKD11, NAK, STAVAX等 AISI H13			銅 Copper											
	50~100 m/min			50~70 m/min			30~60 m/min			20~40 m/min			80~150 m/min											
	直徑 (mm) Diameter	進給速度 mm/min Feed Rate		回轉數 (min ⁻¹) Speed	進給速度 mm/min Feed Rate		回轉數 (min ⁻¹) Speed	進給速度 mm/min Feed Rate		回轉數 (min ⁻¹) Speed	進給速度 mm/min Feed Rate		回轉數 (min ⁻¹) Speed	進給速度 mm/min Feed Rate										
側面 Side Milling		溝 Slotting	側面 Side Milling		溝 Slotting	側面 Side Milling		溝 Slotting	側面 Side Milling		溝 Slotting	側面 Side Milling		溝 Slotting										
0.2	40,000	—	120	40,000	—	100	28,000	—	60	32,000	—	25	40,000	90	30									
0.3	40,000	—	160	40,000	—	120	28,000	—	70	32,000	—	35	40,000	130	40									
0.4	40,000	—	200	40,000	—	160	28,000	—	90	24,000	—	35	40,000	170	55									
0.5	40,000	320	250	40,000	240	190	25,000	200	120	19,000	75	60	40,000	210	70									
0.6	38,000	380	300	33,000	270	210	21,000	220	130	16,000	75	60	40,000	245	85									
0.7	36,000	420	330	28,000	300	240	18,000	240	140	14,000	75	60	40,000	285	95									
0.8	34,000	480	380	25,000	340	270	16,000	260	150	12,000	75	60	40,000	330	110									
0.9	32,000	540	430	22,000	370	290	14,000	280	160	10,600	75	60	40,000	375	125									
1	30,000	600	480	20,000	400	320	12,600	300	180	9,600	75	60	40,000	420	140									
1.5	20,000	600	480	14,000	400	320	8,400	300	180	6,400	75	60	32,000	800	270									
2	15,000	600	480	10,000	400	320	6,300	300	180	4,800	75	60	24,000	1,000	330									
2.5	12,000	600	480	8,200	400	320	5,100	300	180	3,800	75	60	19,000	1,000	330									
3	10,000	600	480	7,000	400	320	4,200	300	180	3,200	75	60	16,000	1,000	330									
4	7,500	600	480	5,200	400	320	3,100	300	180	2,400	75	60	12,000	1,000	330									
5	6,000	600	480	4,200	400	320	2,500	300	180	1,900	75	60	9,600	1,000	330									
6	5,000	600	480	3,500	400	320	2,100	300	180	1,600	75	60	8,000	1,000	330									
8	4,000	520	410	2,800	350	280	1,600	260	150	1,200	65	50	6,000	1,000	330									
10	3,200	450	360	2,200	300	240	1,300	230	130	1,000	65	50	4,800	1,000	330									
12	2,700	410	320	1,900	270	210	1,100	210	120	800	65	50	4,000	1,000	330									
切削量基準 Depth of cut (D:直徑 Dia.)	$\leq 0.1D (D \leq \phi 3)$ $\leq 0.2D (D > \phi 3)$ 						$\leq 0.02D$ $\leq 1D$ 						$\leq 0.1D (D < \phi 2)$ $\leq 0.2D (D \leq \phi 2)$ 						$\leq 0.02D (D < \phi 0.5)$ $\leq 0.05D (\phi 0.5 \leq D \leq \phi 2)$ $\leq 0.1D (D > \phi 2)$ 					

【注意】【NOTE】

- 1) 切削 55~60 HRC 的材料時，請使用4刃或6刃 (SE4或MS6P等) 銑刀。
Please Use SE4 or MS6P for work materials of 55~60 HRC.
- 2) 切削沃斯田鐵系列不鏽鋼時，請使用非水溶性切削油效果較好。
In Cutting Austenitic stainless steels, the use of non-water-soluble cutting fluid is especially effective.
- 3) 機械設備或工件的夾持剛性不足、出現震動時，請以相同比例按上表降低回轉數及進給速度。
If the rigidity of the machine or the work material installation is very low, or chattering is generated, please reduce the revolution and the feed rate proportionately.
- 4) 縱向進給時，進給速度請設定為上表之1/3以下。
When drilling, please set feed rate at 1/3 or below of the above value.

高速切削條件表 High-Speed Milling Conditions

SE.RTA

被削材 Work Material	炭素鋼, 合金鋼(~30HRC) Carbon steel, Alloy steel S50C, SCM, 鑄鐵 FC250等 AISI 1049, Cast iron			合金鋼, 工具鋼(30~45HRC) Alloy steel, Tool steel 預硬鋼, SKD61, NAK等 Pre-hardened steel, AISI H13			熱處理鋼(45~55HRC) Hardened steel SKD61, SKD11, NAK, STAVAX等 AISI H13		
	300 m/min			200 m/min			100 m/min		
	直徑 (mm) Diameter	回轉數 (min ⁻¹) Speed	進給速度 mm/min Feed Rate		回轉數 (min ⁻¹) Speed	進給速度 mm/min Feed Rate		回轉數 (min ⁻¹) Speed	進給速度 mm/min Feed Rate
側面 Side Milling			溝 Slotting	側面 Side Milling		溝 Slotting	側面 Side Milling		溝 Slotting
1	40,000	800	640	30,000	600	480	30,000	240	190
2	40,000	1,600	1,280	30,000	1,200	960	15,900	240	190
3	30,000	1,800	1,440	21,200	1,200	960	10,600	240	190
4	28,000	1,900	1,520	15,900	1,200	960	7,900	240	190
5	19,000	1,900	1,520	12,700	1,200	960	6,300	240	190
6	15,000	1,900	1,520	10,600	1,200	960	5,300	240	190
8	11,000	1,550	1,240	7,900	990	790	4,000	220	175
10	9,500	1,330	1,060	6,300	860	680	3,200	200	160
12	7,900	1,200	960	5,300	750	600	2,600	200	160
切削量基準 Depth of cut (D:直徑 Dia.)	 								

P 鋼 K 鑄鐵 H 淬硬鋼 M 不銹鋼 S 高溫合金和鈦合金 N 有色金屬材料

Foundations for economically efficient milling 經濟效益高的銑削加工基礎

Peripheral requirements

Applicable in every material group

- P K H M S N
- easy to machine materials = increase in productivity
- difficult to machine materials = increase in process reliability

High-dynamic machining centres

- short acceleration distances
- higher speed range
- small to medium tool diameters

Heavy machines

- stable feed axes
- high spindle torque
- medium to large tool diameters

Unstable to stable workpiece clamping

- stable = vibration-free machining = maximum metal removal rate
- unstable = reduction of radial forces = increased process reliability

周邊外圍需求的考量因素

適用於每個物料群組

- P K H M S N
- 容易加工的材料 = 提高生產率
- 難加工的材料 = 提高加工過程的穩定性

高轉速加工中心機

- 加速距離短
- 更高的切削速度範圍
- 盡量使用小、中尺寸直徑的刀具

重型機器

- 穩定的進給軸向控制
- 高主軸扭力
- 盡量使用中、大尺寸直徑刀具

不穩定或是穩定的工件夾持狀況

- 穩定 = 無振動的加工 = 最大金屬去除率
- 不穩定 = 減少徑向力 = 提高加工過程穩定性

Application parameters

Low cutting width a_e to $0.33 \times D$

- low angle of engagement $< 70^\circ$
- short time of contact between cutting edge and component

Very high tooth feed f_z

- reduced chip thickness allows considerably higher f_z

Very high cutting speed v_c

- reduced heating up and prolonged cooling down allow very high v_c values

High cutting depth a_p

- improved leverage effect
- high metal removal rate
- increase in contact points between tool and component

加工參數應用

低的切削寬度 a_e 到 $0.33 \times D$

- 低切削啣合角 $< 70^\circ$
- 切削刃與工件之間的接觸時間短

極高進給率 f_z


- 切屑厚度減少、可顯著提高 f_z

非常高的切削速度 v_c

- 高切削速度時減少加工時熱的產生、並延長冷卻時間

高切削深度 a_p

- 改善槓桿效應
- 高金屬去除率
- 增加刀具與零件之間的接觸點



Tool angle of engagement & tool contact time
刀具切削啣合角度 & 刀具接觸時間

Metal removal rate 金屬去除率 (單位時間內材料切除的體積)

The metal removal rate specifies how high the actual chip removal is per minute.

It is especially suitable for comparing different machining strategies.

金屬去除率是指每分鐘實際去除切屑的量，特別適合用於比較不同的加工策略。

$$a_p \text{ (mm)} \times a_e \text{ (mm)} \times v_f \text{ (m/min)} = Q \text{ (cm}^3\text{/min)}$$

切深 a_p 切寬 a_e 每分鐘進給 每分鐘移除量 cm^3

General recommendation 一般建議

Steel	P		<ul style="list-style-type: none"> • Avoid thermal shock 避免熱產生對刀具的衝擊
Cast iron	K	Dry machining, compressed air, MQL: 乾式切削、噴壓縮空氣、MQL霧化切削液冷卻	<ul style="list-style-type: none"> • Dissipate machining temperature via chip 切屑把熱帶走 • Supporting chip evacuation 幫助排屑
Hardened	H		
Stainless	M	Soluble oil, neat oil: 乳化液、純油性	<ul style="list-style-type: none"> • Cooling of tool cutting edge 切削刃口冷卻 • Preventing built-up edge 避免刃口沾黏積屑 • Supporting chip evacuation 幫助排屑
Special alloy	S		
Non-ferrous metals	N	Soluble oil, neat oil: 乳化液、純油性	<ul style="list-style-type: none"> • Preventing built-up edge 避免刃口沾黏積屑 • Supporting chip evacuation 幫助排屑

Exceptions for material ranges 材料範圍以外的注意事項

P K

When coolant is not available the cutting speed(v_c)and/or the radial feed(a_e)should be reduced. The resulting reduced temperature reduces the risk of thermal shock.

冷卻條件不佳時，則應該降低切削速度(v_c)及降低切寬(a_e)，這樣才能降低溫度，降低熱對刃口的衝擊風險

If there are chip evacuation problems the application of coolant should be taken into consideration, poor evacuation of chips can lead to massive tool wear and even tool breakage.

如果排屑不良有問題，則應考慮使用冷卻液，排屑不良會大大導致刀刃磨損甚至斷刀。

When heat is being generated due to poor chip evacuation, it should be checked if through coolant is available. By using a specifically directed "coolant jet", coolant can be supplied where congested without hitting the cutting area. Alternatively, the application of coolant for the entire machining operation is recommended.

當排屑不良而產生熱能時，應檢查是否可以使用冷卻液，透過使用專門的“冷卻液噴嘴”，可以將冷卻液供應到堵塞處而不會碰到切削區域，另外，建議在整個加工過程中使用冷卻液。

Other notes 其他注意事項

A. Finishing

The application of coolant is principally an advantage as a better surface finish can be achieved.

精銑削

- 使用冷卻液原則上是一個優勢，因為可以實現更好的表面光潔度

B. Very long tools

Coolant can result in a smoother process, as the lubricant has a vibration-reducing effect

長刀型銑削

- 使用冷卻液可以使加工過程更順暢，因為潤滑劑具有減振作用

C. Alignment of coolant

- as accurate as possible in the cutting area from at least three directions
- no flushing back of small chips to the cutting area

冷卻液對準加工區域

- 至少有三個方向的切削液噴嘴，需對準切削區域噴射
- 不要將小切屑衝回切削區域

E. Solid carbide milling cutters with internal cooling

- optimal chip evacuation, very good cutting edge cooling, very effective against built-up edges
- to be recommended especially for larger tool diameters and tough materials

中心出水型銑刀

- 最佳的排屑性，非常好的切削刃口冷卻，避免刃口沾黏積屑非常有效
- 特別推薦用於較大尺寸的刀具和堅韌的難切削材料銑削

D. Peripheral cooling/Guhrojet

Best external option: Optimal tool cooling and chip evacuation thanks to the direct route from coolant exit to cutting area

Guhrojet 刀具周邊外圍冷卻

- 由於冷卻液直接噴到切削區域，達到最佳的刀具冷卻和排屑性



Influence on process through tool engagement 刀具切削與工件的接觸角度對加工過程的影響

Angle of engagement 切削角度


The angle of engagement inscribes the cutting range of the tool from start of chip formation to exit from the material. With these parameters the stress impacting on the tool can be assessed. With straight milling paths the angle is constant, with concave milling paths it increases and with convex milling paths it decreases.

啮合角度確定了從切屑形成開始到從退出材料時刀具的切削範圍。利用這些參數，可以評估影響刀具的受力。在直線銑削路徑中，角度是恆定的；在凹形銑削路徑中，角度是逐漸增大的；而在凸形銑削路徑中，角度則是減小。

Straight milling path 直線銑削路徑

- constant angle of engagement 啮合角度固定
- constant tool stress 刀具的受力固定

Example: $a_e 0.20 \times D = 53^\circ$ engagement 切寬 $a_e 0.2D = 53^\circ$ 啮合角
Engagement remains a constant 53° 固定的啮合角度 53°




側銑切削啮合角度固定 53°

Angle of engagement with convex contour radii 外凸形繞銑啮合角度變化

Convex milling path 外凸形繞銑路徑

- decreasing angle of engagement 啮合角度減少
- reduced tool stress 刀具的受力減少

Example: $a_e 0.20 \times D = 53^\circ$ engagement 切寬 $a_e 0.2D = 53^\circ$ 啮合角
Engagement reduces to 45° 啮合角度減少至 45°




側銑切削啮合角度從 53° 降低至 45°
(切寬 a_e 及每刃進給 f_z 可以增加)

Angle of engagement with concave contour radii 內凹形繞銑啮合角度變化

Concave milling path 內凹形繞銑路徑

- increasing angle of engagement 啮合角度增加
- increased tool stress 刀具的受力增加

Example: $a_e 0.20 \times D = 53^\circ$ engagement 切寬 $a_e 0.2D = 53^\circ$ 啮合角
Engagement increases to 74° 啮合角度增加至 74°



側銑切削啮合角度從 53° 增加至 74°
(切寬 a_e 及每刃進給 f_z 必須減少)

Influence on process through tool engagement 刀具切削與工件的接觸角度對加工過程的影響

Angle of engagement with 90° corner radii

90° 內凹圓形繞銑啮合角度變化


Tool radius = Corner radius 刀具半徑 = 工件圓弧半徑

- very unfavourable for tool dynamics 非常不利的刀具動態路徑
- change of stress direction 刀具的受力改變
- abrupt increase in tool stress 刀具受力突然增加

Example: Increase of engag. angle from 53° to 143° (270°)
接觸啮合角度由 53° 增加至 143°

Measures: v_c and f_z must be heavily reduced

改善措施：必須大幅降低 v_c 和 f_z



改善措施：必須大幅降低 v_c 和 f_z


Tool radius < Corner radius 刀具半徑 < 工件圓弧半徑

- machine can interpolate the path 機器可以插補路徑
- no "impact" on tool 對刀具無 "影響"
- lower increase of tool stress 降低刀具受力

Example: Increase of engag. angle from 53° to 92° (174°)
接觸啮合角度由 53° 增加至 92°

Measures: a_e must be reduced 切寬 a_e 必須減少
 f_z must be heavily reduced in radius

改善措施： f_z 每刃進給於圓角加工時必須大幅降低




改善措施：於圓角加工時必須大幅降低 f_z

Ratio of flute width to tool diameter with trochoidal milling
擺線銑削時槽寬與刀具直徑之比

Flute width $1.7-2.0 \times D$ 槽寬 $1.7-2.0 \times D$


- cut in C arc C形圓弧切削
- a_e max. $0.10 \times D$ (theor. 37°) 切寬 a_e 最多 $0.10D$ (理論上啮合 37°)
- increase of angles of engagement by up to 50%
- 切削啮合角度增加最多至 50% ◦ ($37^\circ \times 1.5 = 55.5^\circ$)



接觸啮合角度由 37° 增加至 55°

Flute width $2.1-3.0 \times D$ 槽寬 $2.1-3.0 \times D$


- cut in C arc C形圓弧切削
- a_e max. $0.15 \times D$ (theor. 46°) 切寬 a_e 最多 $0.15D$ (理論上啮合 46°)
- increase of angles of engagement by up to 50%
- 切削啮合角度增加最多至 50% ◦ ($46^\circ \times 1.5 = 69^\circ$)



接觸啮合角度由 46° 增加至 69°

Flute width from $3.1 \times D$ 槽寬 $3.1 \times D$

- cut in C arc C形圓弧切削
- a_e max. $0.20 \times D$ (theor. 53°) 切寬 a_e 最多 $0.20D$ (理論上啮合 53°)
- increase of angles of engagement by up to 40%
- 切削啮合角度增加最多至 40% ◦ ($53^\circ \times 1.4 = 74.2^\circ$)



接觸啮合角度由 53° 增加至 74°

泛用型加工外冷鎢鋼鑽頭3D.5D.7D (SDWC R Series)
High Performance Tungsten Carbide Drill Bit-3D.5D.7D (SDWC R Series)

被削材	構造用鋼Structural Steel 碳素鋼Carbon Steel 鑄鐵Cast Iron SS400 / S45C / FC250				合金鋼Alloy Steel 調質鋼Heat Treated Steel SCM440 / SNCM / NAK				模具鋼Mold Steel 預硬鋼Prehardened Steel SKD / HPM1 / NAK				高硬度鋼Hardened Steel 熱處理鋼材 SKD61 / SKT4				球墨鑄鐵Ductile Cast Iron FCD400 / FCD700				沃斯田鐵系不銹鋼 Austenitic Stainless Steel SUS304 / SUS316									
	~200HB				20~30HRC				30~40HRC				40~50HRC																	
直徑	轉速	切削	進給	每迴轉	轉速	切削	進給	每迴轉	轉速	切削	進給	每迴轉	轉速	切削	進給	每迴轉	轉速	切削	進給	每迴轉	轉速	切削	進給	每迴轉	轉速	切削	進給	每迴轉		
	r.p.m min-1	V m/min	Feed mm/min	f mm/rev	r.p.m min-1	V m/min	Feed mm/min	f mm/rev	r.p.m min-1	V m/min	Feed mm/min	f mm/rev	r.p.m min-1	V m/min	Feed mm/min	f mm/rev	r.p.m min-1	V m/min	Feed mm/min	f mm/rev	r.p.m min-1	V m/min	Feed mm/min	f mm/rev	r.p.m min-1	V m/min	Feed mm/min	f mm/rev		
3D																														
2.0	12800	80	800	0.06	10200	64	640	0.06	5760	36	280	0.05	3840	24	150	0.04	9600	60	600	0.06	2560	16	110	0.04						
3.0	8500	80	880	0.10	6800	64	710	0.10	3840	36	310	0.08	2560	24	170	0.07	6400	60	660	0.10	1700	16	120	0.07						
4.0	6400	80	880	0.14	5120	64	710	0.14	2880	36	310	0.11	1920	24	170	0.09	4800	60	660	0.14	1280	16	120	0.09						
5.0	5120	80	880	0.17	4100	64	710	0.17	2320	36	310	0.13	1520	24	170	0.11	3840	60	660	0.17	1020	16	120	0.12						
6.0	4240	80	880	0.21	3400	64	710	0.21	1920	36	310	0.16	1280	24	170	0.13	3200	60	660	0.21	850	16	120	0.14						
8.0	3200	80	880	0.28	2560	64	710	0.28	1440	36	310	0.22	960	24	170	0.18	2400	60	660	0.28	640	16	120	0.19						
10.0	2560	80	840	0.33	2000	63	670	0.34	1120	35	300	0.27	800	25	160	0.20	1920	60	640	0.33	510	16	120	0.24						
12.0	2120	80	800	0.38	1680	63	640	0.38	960	36	280	0.29	640	24	150	0.23	1600	60	600	0.38	420	16	110	0.26						
16.0	1600	80	790	0.49	1280	64	560	0.44	720	36	250	0.35	480	24	140	0.29	1200	60	530	0.44	320	16	100	0.31						
5D																														
2.0	12800	80	720	0.06	10160	64	580	0.06	5800	36	260	0.04	3840	24	140	0.04	9600	60	540	0.06	2560	16	100	0.04						
3.0	8480	80	800	0.09	6800	64	650	0.10	3840	36	290	0.08	2560	24	150	0.06	6400	60	610	0.10	1700	16	110	0.06						
4.0	6400	80	800	0.13	5120	64	650	0.13	2880	36	290	0.10	1920	24	150	0.08	4800	60	610	0.13	1280	16	110	0.09						
5.0	5120	80	800	0.16	4080	64	650	0.16	2320	36	290	0.13	1520	24	150	0.10	3840	60	610	0.16	1020	16	110	0.11						
6.0	4240	80	800	0.19	3360	63	650	0.19	1920	36	290	0.15	1280	24	150	0.12	3200	60	610	0.19	850	16	110	0.13						
8.0	3200	80	800	0.25	2560	64	650	0.25	1440	36	280	0.19	960	24	150	0.16	2400	60	610	0.25	640	16	110	0.17						
10.0	2560	80	770	0.30	2000	63	610	0.31	1120	35	270	0.24	800	25	140	0.18	1920	60	580	0.30	510	16	100	0.20						
12.0	2120	80	720	0.34	1680	63	580	0.35	960	36	250	0.26	640	24	140	0.22	1600	60	540	0.34	420	16	100	0.24						
16.0	1600	80	650	0.41	1280	64	520	0.41	720	36	230	0.32	480	24	120	0.25	1200	60	480	0.40	320	16	90	0.28						
7D																														
2.0	9600	60	540	0.06	7640	48	430	0.06	4320	27	190	0.04	2930	18	110	0.04	7140	45	410	0.06	1920	12	80	0.04						
3.0	6400	60	600	0.09	5100	48	490	0.10	2880	27	220	0.08	1950	18	120	0.06	4750	45	460	0.10	1280	12	85	0.07						
4.0	4800	60	600	0.13	3840	48	490	0.13	2160	27	220	0.10	1480	19	120	0.08	3570	45	460	0.13	960	12	85	0.09						
5.0	3800	60	600	0.16	3060	48	490	0.16	1720	27	220	0.13	1170	18	120	0.10	2860	45	460	0.16	770	12	85	0.11						
6.0	3200	60	600	0.19	2560	48	490	0.19	1440	27	220	0.15	980	18	120	0.12	2370	45	460	0.19	640	12	85	0.13						
8.0	2400	60	600	0.25	1920	48	490	0.26	1080	27	210	0.19	740	19	120	0.16	1790	45	440	0.25	480	12	85	0.18						
10.0	1920	60	580	0.30	1520	48	460	0.30	860	27	210	0.24	580	18	110	0.19	1420	45	420	0.30	380	12	80	0.21						
12.0	1600	60	540	0.34	1280	48	440	0.34	720	27	190	0.26	490	18	110	0.22	1190	45	400	0.34	320	12	80	0.25						
16.0	1200	60	480	0.40	960	48	380	0.40	540	27	180	0.33	370	19	90	0.24	900	45	360	0.40	240	12	65	0.27						

■ 泛用型加工外冷鎢鋼鑽頭 3D/5D/7D (SDWC R Series)
切削條件表使用注意事項

1. 根據機床剛性或工件夾持狀態，加工形狀，周邊環境因素等調整切削條件。
2. 機械或加工物安裝過程中，當機床剛性不良或發生顫振時，請依照同比例降低轉速和進給速度。
3. 濕式加工是指使用水溶性切削液進行鑽孔加工。
4. 使用非水溶性切削液時，請降低轉速和進給速度20%。
5. 不推薦鋁合金的加工。
6. 加工不銹鋼當孔深度超過2xDC時，請使用(step feed)間歇式進給。
7. 乾式加工時，請使用(AIR)吹風，進行冷卻和排屑。
8. 鑽孔加工時或鑽頭破損產生火花，有火災危險，請採取防火保護措施。
9. 3xDX以上鑽孔深度，可能因被削材與切削條件影響切屑排出性，建議使用(step feed)間歇式進給。
10. 間歇式(step feed)進給，要回到孔的頂部。
11. 間歇式(step feed)進給，基本設定標準為0.5~1.0xDC。
12. 請將鑽頭夾持震動幅度控制在0.02mm以下，小直徑、高速切削的夾持震動幅度控制在0.01mm以下。

■ High Performance Tungsten Carbide Drill Bit-3D/5D/7D(SDWC R Series)
Attention on using the cutting condition tables

1. Adjust cutting condition according to the rigidity of machine or work clamp state.
2. In machine or installation of machining step. When there is no rigidity of machine or chattering occurs, reduce the rotation and feed rate.
3. Wet condition are the drilling with water soluble cutting fluid.
4. In non-water soluble cutting fluid, reduce the rotation and feed rate by 20%.
5. Drilling Aluminum Alloy, are not recommended.
6. Drilling the step feed in Stainless Steel when hole depth more than 2xDC deep.
7. Use air blow for cooling and the chip exclusion in dry process.
8. By sparks during cutting, or heat by breakage, or hot chip, there is danger of fire.
Take fire prevention measures.
9. A work material and cutting condition to chip removal may be worse. In that case, please feed. It is recommended to step feeding for drilling depth of more than 3xDC.
10. Retraction of the step feed is to be returned to the top of the hole.
11. Step feed is recommended to 0.5~1.0xDC.
12. Please use the fixture to control the amplitude of the drill bit below 0.02mm, for small diameter, high-speed cutting control amplitude of the drill bit 0.01mm or less.

切削條件表

切削條件表

水孔內冷鎢鋼鑽頭3D.5D.8D (SDWC O Series)

Coolant Hole High Performance Tungsten Carbide Drill Bit-3D.5D.8D (SDWC O Series)

被削材	一般構造用鋼 碳素鋼 / 鑄鐵 Structural Steel Carbon Steel Cast Iron SS400 / S50C FC250		合金鋼 調質鋼 Alloy Steel Heat Treated SCM440 SNCM		模具鋼 預硬鋼 Mold Steel Prehardened Steel SKD / HPM NAK		高硬度鋼 Hardened Steel		球墨鑄鐵 Ductile Cast Iron FCD400		不鏽鋼 Stainless Steel SUS430 SUS304		不鏽鋼 Stainless Steel SUS630		鈦合金 Titanium Alloy Ti-6Al-4V		鎳基合金 Nickel based Alloy Inconel718	
	~200HB		20~30HRC		30~40HRC		40~50HRC											
直徑	回轉速 r.p.m min-1	進給速度 Feed mm/min	回轉速 r.p.m min-1	進給速度 Feed mm/min	回轉速 r.p.m min-1	進給速度 Feed mm/min	回轉速 r.p.m min-1	進給速度 Feed mm/min	回轉速 r.p.m min-1	進給速度 Feed mm/min	回轉速 r.p.m min-1	進給速度 Feed mm/min	回轉速 r.p.m min-1	進給速度 Feed mm/min	回轉速 r.p.m min-1	進給速度 Feed mm/min	回轉速 r.p.m min-1	進給速度 Feed mm/min
	3D/5D 濕式加工 Wet Condition (水溶性切削液)																	
3.0	10160	980	8480	740	6800	610	3400	210	8480	760	6800	540	4240	320	3360	260	3360	150
4.0	7680	980	6400	740	5120	610	2560	210	6400	760	5120	540	3200	320	2560	260	2560	150
6.0	5120	980	4240	740	3360	570	1680	190	4240	760	3360	530	2080	320	1680	260	1680	150
8.0	3840	980	3200	740	2560	570	1280	190	3200	700	2560	510	1600	320	1280	260	1280	150
10.0	3040	910	2560	690	2000	510	1040	180	2560	630	2000	470	1280	300	1040	240	1040	140
12.0	2560	860	2160	660	1680	430	840	180	2160	540	1680	450	1040	280	840	220	840	140
16.0	1920	770	1600	640	1280	380	640	170	1600	500	1280	410	800	260	640	210	640	120
3D/5D MQL加工 MQL Condition (油霧式冷卻)																		
3.0	6800	620	5920	410	5120	430	2040	110	5920	500	**	**	**	**	**	**	**	**
4.0	5120	620	4480	410	3840	430	1520	110	4480	500	**	**	**	**	**	**	**	**
6.0	3360	620	2960	410	2560	430	1040	100	2960	500	**	**	**	**	**	**	**	**
8.0	2560	620	2240	410	1920	400	800	100	2240	460	**	**	**	**	**	**	**	**
10.0	2000	580	1760	380	1520	350	640	100	1760	400	**	**	**	**	**	**	**	**
12.0	1680	540	1520	360	1280	300	520	100	1520	370	**	**	**	**	**	**	**	**
16.0	1280	480	1120	360	960	270	380	80	1120	320	**	**	**	**	**	**	**	**
8D 濕式加工 Wet Condition (水溶性切削液)																		
3.0	10160	810	8480	740	6800	500	3400	180	8480	640	6800	400	4240	260	3360	230	3360	140
4.0	7680	860	6400	740	5120	500	2560	180	6400	640	5120	450	3200	280	2560	230	2560	140
6.0	5120	920	4240	740	3360	480	1680	180	4240	590	3360	480	2080	290	1680	230	1680	140
8.0	3840	980	3200	740	2560	470	1280	180	3200	590	2560	510	1600	290	1280	230	1280	140
10.0	3040	910	2560	690	2000	420	1040	170	2560	540	2000	470	1280	260	1040	210	1040	130
12.0	2560	860	2160	660	1680	380	840	160	2160	500	1680	450	1040	260	840	200	840	120
16.0	1920	770	1600	640	1280	350	640	150	1600	440	1280	410	800	230	640	180	640	110
8D MQL加工 MQL Condition (油霧式冷卻)																		
3.0	6800	510	5920	410	5120	320	2040	100	5920	400	**	**	**	**	**	**	**	**
4.0	5120	540	4480	410	3840	320	1520	100	4480	400	**	**	**	**	**	**	**	**
6.0	3360	560	2960	410	2560	300	1040	100	2960	380	**	**	**	**	**	**	**	**
8.0	2560	620	2240	410	1920	300	800	100	2240	380	**	**	**	**	**	**	**	**
10.0	2000	580	1760	380	1520	270	640	80	1760	350	**	**	**	**	**	**	**	**
12.0	1680	540	1520	360	1280	270	520	80	1520	340	**	**	**	**	**	**	**	**
16.0	1280	480	1120	360	960	260	380	70	1120	290	**	**	**	**	**	**	**	**

水孔內冷鎢鋼鑽頭 3D/5D/8D (SDWC O Series) 切削條件表使用注意事項

1. 根據機床剛性或工作夾狀態調整切削條件。請依照同比例降低轉速和進給速度。
2. 濕式加工是指使用水溶性切削液進行鑽孔加工。
3. 在非水溶性切削液中，降低轉速和進給速度20%。請依照同比例降低轉速和進給速度。
4. 雙螺旋油孔鑽用於內冷，內部給油可幫助冷卻與排屑。可使用不歇式(Non-step)鑽孔加工。
5. 在工件材料和切削條件配合排屑不良場合，請使用(step feed)間歇式進給。
6. 排屑不良場合，即使在預定的孔深以下，也請使用(step feed)間歇式進給。
7. 使用(step feed)間歇式進給時，鑽頭要設定回到工件入口孔。
8. 使用(step feed)間歇式進給時，進給間隔約為 0.2~1xDc。

Coolant Hole High Performance Tungsten Carbide Drill Bit-3D/5D/8D (SDWC O Series) Attention on using the cutting condition tables

1. Adjust cutting condition according to the rigidity of machine or work clamp state.
2. Wet condition are the drilling with water soluble cutting fluid.
3. In non-water soluble cutting fluid, reduce the rotation and feed rate by 20%.
4. Use on internal coolant. Non-step drilling is possible.
5. However, a work material and cutting condition to chip removal may be worse.
6. In that case, even if under predetermined hole depth, please step feed.
7. In step feed, return to the entrance hole.
8. Step feed interval is about 0.2~1xDc.

HD.MIT



GL Tungsten Carbide Anti-Vibration Tools Holder



以生產效率 帶動節能減碳

因為堅持。看到希望

快速 ▶ 節能 ▶ 效率 ▶ 耐用

一桿多用替換快速 (成本更低)

- Made of high quality Tungsten Carbide.
- Keep the cost down of the cutting tools.
- Ultra-long, Ultra-deep, and Ultra-high-precision process.


抗震效果佳 裝卸方便



HD.

模具三寶 Three Treasures for Mold

鎢鋼抗震刀柄



鎖牙式刀把



鎢鋼抗震刀柄優點

1. 使用高級碳化鎢材質製成，剛性優異、吸震性佳，不會因橫向鑽力過大，而扭曲變形。
2. 延長加工深度，提升加工面精度，實現超長、超深、超高精度加工之可行性。
3. 沒有焊接處斷裂之虞慮，強調刀頭之多變化性。縱使刀頭損壞，立即更換即可上線。

* 產品豐富，其他規格請洽詢...

HDC / HUC 錫鋼後拉刀桿


Tungsten Carbide Toolholder-HDC/HUC Collet Chuck

快速 ▶ 節能 ▶ 效率 ▶ 耐用



HDC6L Collet
HUC Collet
HDC Collet

HDC4 HDC6 HDC6L HUC8 HUC10



優異剛度
Excellent Stiffness

振動吸收
Vibration absorption

延長刀具壽命
Increase tools service life

CO₂ ESG Reduce carbon footprint

1. 使用高級碳化錫材質製成。
Made of high quality Tungsten Carbide.
2. 超長、超深、超高精度工藝。
Ultra-long, Ultra-deep, and Ultra-high-precision process.
3. 降低刀具成本。
Keep the cost down of the cutting tools.

HD.MIT



慧德刀具五金有限公司 | 和東五金商行
Hwe Der Machinery and Hardware Pty Ltd. | Ho Dung Hardware Co.,Ltd.

GLCK 錫鋼抗震搪刀柄

Tungsten Carbide Anti-Vibration Boring System Toolholder

全錫鋼材質製成，延長加工深度，提升搪孔加工面精度，實現超長、超深、超高精度加工之可行性。



◎可搭配BIG系列搪孔頭使用◎

產品編號	Model No.	L	D	GLCK	M
GLCK1-19-150L	150	19	GLCK1	4	
GLCK1-19-200L	200	19	GLCK1	4	
GLCK1-19-250L	250	19	GLCK1	4	
GLCK1-20-150L	150	20	GLCK1	4	
GLCK1-20-200L	200	20	GLCK1	4	
GLCK1-20-250L	250	20	GLCK1	4	
GLCK2-24-200L	200	24	GLCK2	5	
GLCK2-24-250L	250	24	GLCK2	5	
GLCK2-24-300L	300	24	GLCK2	5	
GLCK2-25-200L	200	25	GLCK2	5	
GLCK2-25-250L	250	25	GLCK2	5	
GLCK2-25-300L	300	25	GLCK2	5	
GLCK3-31-250L	250	31	GLCK3	6	
GLCK3-31-300L	300	31	GLCK3	6	
GLCK3-31-350L	350	31	GLCK3	6	
GLCK3-31-400L	400	31	GLCK3	6	
GLCK3-32-250L	250	32	GLCK3	6	
GLCK3-32-300L	300	32	GLCK3	6	
GLCK3-32-350L	350	32	GLCK3	6	
GLCK3-32-400L	400	32	GLCK3	6	
GLCK4-42-250L	250	42	GLCK4	8	
GLCK4-42-300L	300	42	GLCK4	8	
GLCK4-42-400L	400	42	GLCK4	8	
GLCK4-42-500L	500	42	GLCK4	8	

剛性優異
吸震性佳

錫鋼柄搪刀桿

產品編號	Dimensions mm			Shape	適用搪刀頭 Suitable Boring Cutter Head	適用套筒 Suitable Collet
	D	M	L			
SC08H-M5-115	8	M5	115		BE09A、BE10.5A	EC1608
SC10H-M6-115	10	M6	115		BE12A、BE14A BE16A	EC1610
SC10H-M6-135	10	M6	135			EC1610
SC10H-M6-160	10	M6	160			EC1610
SC12H-M6-135	12	M6	135			EC1612
SC12H-M6-165	12	M6	165		EC1612	
SC14H-M6-160	14	M6	160		BE14A、BE16A	EC1614
SC16H-M10-105	16	M10	105		BE18A-BE50A	-
SC16H-M10-140	16	M10	140		BE18A-BE50A	
SC16H-M10-180	16	M10	180		BE18A-BE50A	



HD.MIT

慧德刀具五金有限公司 | 和東五金商行
Hwe Der Machinery and Hardware Pty Ltd. | Ho Dung Hardware Co.,Ltd.

HSS
高速鋼



星型六角起子頭

HSS High Speed Steel Torx Screwdriver Bits

星型形狀保持度佳、高硬度、耐磨耗、不易滑牙

單位: mm



規格	柄徑	全長
T-6	6.35	54
T-7	6.35	54
T-8	6.35	54
T-9	6.35	54
T-10	6.35	54
T-15	6.35	54
T-20	6.35	54

可快速互換



捨棄式刀具專用星型起子

HSS Torx Screwdriver for Indexable Insert Cutting Tools

易握手把、省力防滑



其他款式需求，歡迎與我們詢問



T-6 T-7 T-8 T-9 T-10 T-15 T-20

HD.MIT

慧德刀具五金有限公司
和東五金商行
TEL:886-4-7559458.7567158
FAX:886-4-7564341



鎢鋼倒角刀起子頭

Tungsten Carbide Chamfering cutter

手持式去毛刺工具


Material are all tungsten Carbide

全鎢鋼
材質



可快速互換
Easy to quick interchangeable

充電式手持倒角刀



耐磨耗/快速便利/可裝於起子柄
也可用於電鑽上使用
電動手持倒角刀
多種長度變化可供選擇
使用不受場地限制
狹小處亦可操作

HD.MIT



專利走心式車床專用
星型棘輪扳手



- 1 72齒設計，轉動角度小即可鎖緊
- 2 耐用的鋁合金手柄、止滑設計
- 3 耐磨且有效防止滑牙
- 4 便利於狹小空間內操作

專利走心式車床專用
螺帽棘輪扳手

- 1 72齒設計，轉動角度小即可鎖緊
- 2 縮短換刀時間，增加工作效率
- 3 便利於狹小空間內操作

ER11M
ER16M
ER20M



新
上市

換刀神器 杜絕工傷

HD.

慧德刀具五金有限公司 / 和東五金商行
Hwe Der Machinery and Hardware Pty Ltd. Ho Dung Hardware Co.,Ltd.

HD. ▶▶ WH系列陶瓷尋邊器

特性 韌性強 耐磨損 硬度高 不導磁 不生鏽 壽命長

WH-1010



WH-1020



WH-P1



WH-P2



WH-420L



▶▶ Z 軸設定器系列

型號	有無磁	說明
NZH-50	有磁/無磁	尺寸63x50mm
NZM-50	有磁/無磁	尺寸48x50mm
NZD-100	無磁	尺寸57x50x100mm

NZH-50



NZM-50



NZD-100



HD.MIT

慧德刀具五金有限公司

www.hdtools.com.tw

LINE ID: @hdtools

▶ 航太領域 ◀ 專用切削刀具

Aerospace Cutting Tools Series



Special For

Nickel Alloy 718 and
64 Alloy Titanium



HD. 刀具檢查與量測

加強檢查準確性，提升刀具品質



高
強度

高
負荷

抗
熱變

鎳基合金專用刀

高性能刀具切削效率高、效果好
超高速、抗黏屑、高效率專用

刀具材料對於切削刀具的成功具有根本重要性
優異鍍層銑刀，讓您在航太材料加工事半功倍

航太材料加工，慧德刀具是您最有力的助手！



✉ hdtools168@gmail.com

慧德刀具五金有限公司

Hwe Der Machinery and Hardware Pty Ltd.

TEL: 886-4-7559458

FAX: 886-4-7564341

E-mail: hdtools168@gmail.com

